
PIONEER
HIGH RESOLUTION INDUCTION COMPENSATED DEFORMATION
Company: Sundance Energy Inc.
Well: 4C2-31-2
Field: Gallivan
Location:
Latitude:
Longitude:
Elevation: KB 1,234.00 m
DF 1,233.00 m
GL 1,229.00 m
Permanent Datum: Mean Sea Level
Log Measured From: KB, 5.00 m Above Permanent Datum
Drilling Measured From: KB
Date: 12-Dec-12
Run Number: ONE
Depth Driller: 3,900.00 m
Depth Logger: 3,900.00 m
Bottom Logged Interval: 3,900.00 m
Top Logged Interval: 1,000.00 m
Casing Driller Size @ Depth: 244.5 mm @ 1,000.00 m
Casing Logger Size @ Depth: 244.5 mm @ 1,000.00 m
Bit Size: 222.3 mm
Type Fluid in Hole: Water Based Mud
Density: 1.10 g/cm3
Viscosity: 50.00 s
PH: 9.00
Fluid Loss: 5.00 cm3/30min
Source of Sample: Flowline
Rm @ Measured Temp: 0.200 ohmm @ 20.00 degC
Rmf @ Measured Temp: 0.150 ohmm @ 20.00 degC
Rmc @ Measured Temp: 0.300 ohmm @ 20.00 degC
Source of Rmf / Rmc: Measured / Measured
Rm @ BHT: 0.120 ohmm @ 90.00 degC
Time Since Circulation: 12.00 hr
Max Recorded Temp: 90.00 degC
Equipment Number: 1
Location: 1
Recorded By: Jones
Witnessed By: Smith