

FORM 5A Rev 06/12

State of Colorado Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



Table with columns DE, ET, OE, ES

Document Number: 400310562 Date Received: 07/30/2012

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reoperation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 100322 2. Name of Operator: NOBLE ENERGY INC 3. Address: 1625 BROADWAY STE 2200 City: DENVER State: CO Zip: 80202 4. Contact Name: Andrea Rawson Phone: (303) 228-4253 Fax: (303) 228-4286

5. API Number 05-123-23768-00 6. County: WELD 7. Well Name: MOEN J Well Number: 8-9 8. Location: QtrQtr: NESE Section: 8 Township: 5N Range: 66W Meridian: 6 9. Field Name: WATTENBERG Field Code: 90750

Completed Interval

FORMATION: CODELL Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 05/07/2012 End Date: 05/07/2012 Date of First Production this formation: 01/26/2008 Perforations Top: 7284 Bottom: 7292 No. Holes: 72 Hole size: 0.42

Provide a brief summary of the formation treatment: Open Hole: [ ]

Re-Frac'd Codell w/ 170272 gals of Slick Water, Vistar, and 15% HCl with 236878#'s of Ottawa sand.

This formation is commingled with another formation: [X] Yes [ ] No Total fluid used in treatment (bbl): 4054 Max pressure during treatment (psi): 3849 Total gas used in treatment (mcf): 0 Fluid density at initial fracture (lbs/gal): Type of gas used in treatment: Min frac gradient (psi/ft): 0.74 Total acid used in treatment (bbl): Number of staged intervals: 8 Recycled water used in treatment (bbl): Flowback volume recovered (bbl): Fresh water used in treatment (bbl): Disposition method for flowback: RECYCLE Total proppant used (lbs): 236878 Rule 805 green completion techniques were utilized: [ ] Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: Hours: Bbl oil: Mcf Gas: Bbl H2O: Calculated 24 hour rate: Bbl oil: Mcf Gas: Bbl H2O: GOR: Test Method: Casing PSI: Tubing PSI: Choke Size: Gas Disposition: Gas Type: Btu Gas: API Gravity Oil: Tubing Size: Tubing Setting Depth: Tbg setting date: Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: [ ] Yes [ ] No If yes, number of sacks cmt

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA-CODELL Status: PRODUCING Treatment Type: \_\_\_\_\_

Treatment Date: 05/07/2012 End Date: 05/07/2012 Date of First Production this formation: \_\_\_\_\_

Perforations Top: 6966 Bottom: 7292 No. Holes: 120 Hole size: \_\_\_\_\_

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole:

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_

Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): \_\_\_\_\_

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_

Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: \_\_\_\_\_

Total proppant used (lbs): \_\_\_\_\_ Rule 805 green completion techniques were utilized:

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: 05/18/2012 Hours: 24 Bbl oil: 11 Mcf Gas: 65 Bbl H2O: 1

Calculated 24 hour rate: Bbl oil: 11 Mcf Gas: 65 Bbl H2O: 1 GOR: 5909

Test Method: Flowing Casing PSI: 875 Tubing PSI: \_\_\_\_\_ Choke Size: 15

Gas Disposition: SOLD Gas Type: WET Btu Gas: 1264 API Gravity Oil: 58

Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIORBARA Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 05/07/2012 End Date: 05/07/2012 Date of First Production this formation: 05/09/2012  
Perforations Top: 6966 Bottom: 7104 No. Holes: 48 Hole size: 0.72

Provide a brief summary of the formation treatment: Open Hole:

Frac'd Niobrara w/ 164862 gals of Slick Water and Vistar with 249706#'s of Ottawa sand.

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): 3925 Max pressure during treatment (psi): 4658

Total gas used in treatment (mcf): 0 Fluid density at initial fracture (lbs/gal): \_\_\_\_\_

Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): 0.94

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: 7

Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: RECYCLE

Total proppant used (lbs): 249706 Rule 805 green completion techniques were utilized:

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: \_\_\_\_\_ Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_

Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_

Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_

Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_

Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

Comment: \_\_\_\_\_

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.  
Signed: \_\_\_\_\_ Print Name: Andrea Rawson  
Title: Regulatory Specialist Date: 7/30/2012 Email: arawson@nobleenergyinc.com

**Attachment Check List**

Att Doc Num	Name

Total Attach: 0 Files

**General Comments**

User Group	Comment	Comment Date
Permit	Operator reported as typo and asked perms be changed to 7284'.	10/18/2012 11:04:52 AM
Permit	On hold. Codell perms at 7274' are above the top of the Codell at 7282'.	10/17/2012 10:33:48 AM

Total: 2 comment(s)