

FORM 5A Rev 06/12

State of Colorado Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



Table with columns DE, ET, OE, ES

Document Number: 400340939

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 100322 2. Name of Operator: NOBLE ENERGY INC 3. Address: 1625 BROADWAY STE 2200 City: DENVER State: CO Zip: 80202 4. Contact Name: JEAN MUSE-REYNOLDS Phone: (303) 228-4316 Fax: (303) 228-4286

5. API Number 05-123-35557-00 6. County: WELD 7. Well Name: THOMSEN USX 8. Location: QtrQtr: SWSW Section: 6 Township: 2N Range: 65W Meridian: 6 9. Field Name: WATTENBERG Field Code: 90750

Completed Interval

FORMATION: CODELL Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 08/06/2012 End Date: 08/06/2012 Date of First Production this formation: 08/22/2012 Perforations Top: 7517 Bottom: 7533 No. Holes: 64 Hole size: 0.4

Provide a brief summary of the formation treatment: Open Hole: [ ]

PUMPED 242763# Ottawa sand in 127800gals of Clearstar, Gelled Water, Slick Water, 15% HCL downhole. CODELL AND J SAND ARE PRODUCING THROUGH COMPOSITE FLOW-THROUGH PLUGS

This formation is commingled with another formation: [X] Yes [ ] No

Total fluid used in treatment (bbl): 3043 Max pressure during treatment (psi): 4957 Total gas used in treatment (mcf): Fluid density at initial fracture (lbs/gal): 8.34 Type of gas used in treatment: Min frac gradient (psi/ft): 0.88 Total acid used in treatment (bbl): 13 Number of staged intervals: 7 Recycled water used in treatment (bbl): Flowback volume recovered (bbl): Fresh water used in treatment (bbl): Disposition method for flowback: RECYCLE Total proppant used (lbs): 242763 Rule 805 green completion techniques were utilized: [X]

Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: Hours: Bbl oil: Mcf Gas: Bbl H2O: Calculated 24 hour rate: Bbl oil: Mcf Gas: Bbl H2O: GOR: Test Method: Casing PSI: Tubing PSI: Choke Size: Gas Disposition: Gas Type: Btu Gas: API Gravity Oil: Tubing Size: Tubing Setting Depth: Tbg setting date: Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: [ ] Yes [ ] No If yes, number of sacks cmt

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

FORMATION: J-NIOBRARA-CODELL Status: COMMINGLED Treatment Type: \_\_\_\_\_

Treatment Date: \_\_\_\_\_ End Date: \_\_\_\_\_ Date of First Production this formation: 08/22/2012

Perforations Top: 7286 Bottom: 7993 No. Holes: 120 Hole size: 0.4

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole:

**CODELL AND J SAND ARE PRODUCING THROUGH COMPOSITE FLOW-THROUGH PLUGS**

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_

Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): \_\_\_\_\_

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_

Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: \_\_\_\_\_

Total proppant used (lbs): \_\_\_\_\_ Rule 805 green completion techniques were utilized:

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: 08/22/2012 Hours: 24 Bbl oil: 109 Mcf Gas: 276 Bbl H2O: 20

Calculated 24 hour rate: Bbl oil: 109 Mcf Gas: 276 Bbl H2O: 20 GOR: 2532

Test Method: FLOWING Casing PSI: 605 Tubing PSI: 0 Choke Size: 12/64

Gas Disposition: SOLD Gas Type: WET Btu Gas: 1248 API Gravity Oil: 49

Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: J SAND Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 08/06/2012 End Date: 08/06/2012 Date of First Production this formation: 08/22/2012  
Perforations Top: 7985 Bottom: 7993 No. Holes: 32 Hole size: 0.4

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole:

PUMPED 251869# Ottawa sand and 16792# SB Excel in 161671gals of Clearstar, Gelled Water, Fresh Water downhole.  
CODELL AND J SAND ARE PRODUCING THROUGH COMPOSITE FLOW-THROUGH PLUGS

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): 3849 Max pressure during treatment (psi): 4161

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): 8.34

Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): 0.63

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: 10

Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: RECYCLE

Total proppant used (lbs): 268661 Rule 805 green completion techniques were utilized:

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: \_\_\_\_\_ Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_

Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_

Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_

Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_

Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA-CODELL Status: PRODUCING Treatment Type: \_\_\_\_\_

Treatment Date: \_\_\_\_\_ End Date: \_\_\_\_\_ Date of First Production this formation: 08/22/2012

Perforations Top: 7286 Bottom: 7533 No. Holes: 88 Hole size: 0.4

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole:

CODELL AND J SAND ARE PRODUCING THROUGH COMPOSITE FLOW-THROUGH PLUGS

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_

Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): \_\_\_\_\_

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_

Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: \_\_\_\_\_

Total proppant used (lbs): \_\_\_\_\_ Rule 805 green completion techniques were utilized:

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: \_\_\_\_\_ Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_

Calculated 24 hour rate: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_

Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_

Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_

Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 08/06/2012 End Date: 08/06/2012 Date of First Production this formation: 08/22/2012  
Perforations Top: 7286 Bottom: 7392 No. Holes: 24 Hole size: 2

Provide a brief summary of the formation treatment: Open Hole:

PUMPED 249233# Ottawa sand in 165701gals of Clearstar, Gelled Water, Slick Water, Fresh Water downhole.  
CODELL AND J SAND ARE PRODUCING THROUGH COMPOSITE FLOW-THROUGH PLUGS

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): 3945 Max pressure during treatment (psi): 5535

Total gas used in treatment (mcf): Fluid density at initial fracture (lbs/gal): 8.34

Type of gas used in treatment: Min frac gradient (psi/ft): 0.90

Total acid used in treatment (bbl): Number of staged intervals: 7

Recycled water used in treatment (bbl): Flowback volume recovered (bbl):

Fresh water used in treatment (bbl): Disposition method for flowback: RECYCLE

Total proppant used (lbs): 249233 Rule 805 green completion techniques were utilized:

Reason why green completion not utilized:

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: Hours: Bbl oil: Mcf Gas: Bbl H2O:

Calculated 24 hour rate: Bbl oil: Mcf Gas: Bbl H2O: GOR:

Test Method: Casing PSI: Tubing PSI: Choke Size:

Gas Disposition: Gas Type: Btu Gas: API Gravity Oil:

Tubing Size: Tubing Setting Depth: Tbg setting date: Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze:  Yes  No If yes, number of sacks cmt

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

Comment:  
CODELL AND J SAND ARE PRODUCING THROUGH COMPOSITE FLOW-THROUGH PLUGS  
LOG COPIES SENT UNDER SEPARATE COVER.

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.  
Signed: Print Name: JEAN MUSE-REYNOLDS  
Title: REGULATORY COMPLIANCE Date: Email jmuse@nobleenergyinc.com

**Attachment Check List**

Att Doc Num	Name

Total Attach: 0 Files

**General Comments**

User Group	Comment	Comment Date

Total: 0 comment(s)