

FORM
2A

Rev
04/01

State of Colorado
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



Document Number:

400296794

Date Received:

09/13/2012

Oil and Gas Location Assessment

New Location Amend Existing Location Location#: _____

Submit original plus one copy. This form is to be submitted to the COGCC prior to any ground disturbance activity associated with oil and gas development operations. This Assessment may be approved as a standalone application or submitted as an informational report accompanying an Application for Permit-To-Drill, Form 2. Approval of this Assessment will allow for the construction of the below specified location; however, it does not supersede any land use rules applied by the local land use authority. This form may serve as notice to land owners and other interested parties, please see the COGCC web site at <http://colorado.gov/cogcc/> for all accompanying information pertinent to this Oil and Gas Location Assessment.

Location ID:

430834

Expiration Date:

11/22/2015

This location assessment is included as part of a permit application.

1. CONSULTATION

- This location is included in a Comprehensive Drilling Plan. CDP # _____
- This location is in a sensitive wildlife habitat area.
- This location is in a wildlife restricted surface occupancy area.
- This location includes a Rule 306.d.(1)A.ii. variance request.

2. Operator

Operator Number: 10411
 Name: ENDEAVOUR OPERATING CORPORATION
 Address: 1125 17TH STREET #1525
 City: DENVER State: CO Zip: 80202

3. Contact Information

Name: Terry Hoffman
 Phone: (720) 542-8287
 Fax: ()
 email: terry@rockymountainpermitting.com

4. Location Identification:

Name: Wiley Number: 22-3-97-1
 County: RIO BLANCO
 Quarter: NWNW Section: 22 Township: 3N Range: 97W Meridian: 6 Ground Elevation: 5868

Define a single point as a location reference for the facility location. This point should be used as the point of measurement in the drawings to be submitted with this application. When the location is to be used as a well site then the point shall be a well location.

Footage at surface: 1144 feet FNL, from North or South section line, and 879 feet FWL, from East or West section line.
 Latitude: 40.218568 Longitude: -108.270778 PDOP Reading: 1.9 Date of Measurement: 05/11/2012
 Instrument Operator's Name: Shay Young

5. Facilities (Indicate the number of each type of oil and gas facility planned on location):

Special Purpose Pits: <input type="checkbox"/>	Drilling Pits: <input type="checkbox"/>	Wells: <input type="checkbox"/> <u>1</u>	Production Pits: <input type="checkbox"/>	Dehydrator Units: <input type="checkbox"/>
Condensate Tanks: <input type="checkbox"/>	Water Tanks: <input type="checkbox"/> <u>2</u>	Separators: <input type="checkbox"/> <u>1</u>	Electric Motors: <input type="checkbox"/>	Multi-Well Pits: <input type="checkbox"/>
Gas or Diesel Motors: <input type="checkbox"/>	Cavity Pumps: <input type="checkbox"/>	LACT Unit: <input type="checkbox"/>	Pump Jacks: <input type="checkbox"/> <u>1</u>	Pigging Station: <input type="checkbox"/>
Electric Generators: <input type="checkbox"/>	Gas Pipeline: <input type="checkbox"/>	Oil Pipeline: <input type="checkbox"/>	Water Pipeline: <input type="checkbox"/>	Flare: <input type="checkbox"/>
Gas Compressors: <input type="checkbox"/>	VOC Combustor: <input type="checkbox"/>	Oil Tanks: <input type="checkbox"/> <u>2</u>	Fuel Tanks: <input type="checkbox"/>	

Other: A trench will be on the proposed pad for cuttings only.

6. Construction:

Date planned to commence construction: 11/15/2012 Size of disturbed area during construction in acres: 4.65
 Estimated date that interim reclamation will begin: 10/01/2013 Size of location after interim reclamation in acres: 3.10
 Estimated post-construction ground elevation: 5868 Will a closed loop system be used for drilling fluids: Yes
 Will salt sections be encountered during drilling: Yes No Is H2S anticipated? Yes No
 Will salt (>15,000 ppm TDS Cl) or oil based muds be used: Yes No
 Mud disposal: Offsite Onsite Method: Land Farming Land Spreading Disposal Facility
 Other: _____

7. Surface Owner:

Name: _____ Phone: _____
 Address: _____ Fax: _____
 Address: _____ Email: _____
 City: _____ State: _____ Zip: _____ Date of Rule 306 surface owner consultation: _____

Surface Owner: Fee State Federal Indian
 Mineral Owner: Fee State Federal Indian

The surface owner is: the mineral owner committed to an oil and gas lease
 is the executer of the oil and gas lease the applicant

The right to construct the location is granted by: oil and gas lease Surface Use Agreement Right of Way
 applicant is owner

Surface damage assurance if no agreement is in place: \$2000 \$5000 Blanket Surety ID _____

8. Reclamation Financial Assurance:

Well Surety ID: _____ Gas Facility Surety ID: _____ Waste Mgnt. Surety ID: _____

9. Cultural:

Is the location in a high density area (Rule 603.b.): Yes No
 Distance, in feet, to nearest building: 2693, public road: 18774, above ground utilit: 28671
 , railroad: 274560, property line: 1440

10. Current Land Use (Check all that apply):

Crop Land: Irrigated Dry land Improved Pasture Hay Meadow CRP
 Non-Crop Land: Rangeland Timber Recreational Other (describe): _____
 Subdivided: Industrial Commercial Residential

11. Future Land Use (Check all that apply):

Crop Land: Irrigated Dry land Improved Pasture Hay Meadow CRP
 Non-Crop Land: Rangeland Timber Recreational Other (describe): _____
 Subdivided: Industrial Commercial Residential

12. Soils:

List all soil map units that occur within the proposed location. Attach the National Resource Conservation Service (NRCS) report showing the "Map Unit Description" report listing the soil typical vertical profile. This data is to used when segregating topsoil.

The required information can be obtained from the NRCS web site at <http://soildatamart.nrcs.usda.gov/> or from the COGCC web site GIS Online map page found at <http://colorado.gov/cogcc>. Instructions are provided within the COGCC web site help section.

NRCS Map Unit Name: 48 - Kobar silty clay loam, 3 to 8 percent slopes

NRCS Map Unit Name: 61 - Patent loam, 3 to 8 percent slopes.

NRCS Map Unit Name: 74 - Rentsac-Moyerson-Rock outcrop complex, 5 to 65 percent slopes.

13. Plant Community:

Complete this section only if any portion of the disturbed area of the location's current land use is on non-crop land.

Are noxious weeds present: Yes No

Plant species from: NRCS or, field observation Date of observation: 05/11/2012

List individual species: _____

Check all plant communities that exist in the disturbed area.

- Disturbed Grassland (Cactus, Yucca, Cheatgrass, Rye)
- Native Grassland (Bluestem, Grama, Wheatgrass, Buffalograss, Fescue, Oatgrass, Brome)
- Shrub Land (Mahogany, Oak, Sage, Serviceberry, Chokecherry)
- Plains Riparian (Cottonwood, Willow, Aspen, Maple, Poplar, Russian Olive, Tamarisk)
- Mountain Riparian (Cottonwood, Willow, Blue Spruce)
- Forest Land (Spruce, Fir, Ponderosa Pine, Lodgepole Pine, Juniper, Pinyon, Aspen)
- Wetlands Aquatic (Bullrush, Sedge, Cattail, Arrowhead)
- Alpine (above timberline)
- Other (describe): Sagebrush and Native Grasses

14. Water Resources:

Rule 901.e. may require a sensitive area determination be performed. If this determination is performed the data is to be submitted with the Form 2A.

Is this a sensitive area: No Yes Was a Rule 901.e. Sensitive Areas Determination performed: No Yes

Distance (in feet) to nearest surface water: 436, water well: 5154, depth to ground water: 100

Is the location in a riparian area: No Yes Was an Army Corps of Engineers Section 404 permit filed No Yes

Is the location within a Rule 317B Surface Water Suppl Area buffer zone:

No 0-300 ft. zone 301-500 ft. zone 501-2640 ft. zone

If the location is within a Rule 317B Surface Water Supply Area buffer have all public water supply systems within 15 miles been notified: No Yes

15. Comments:

Footages listed as 5280' are greater than one (1) mile. Closest water well permit is #66373. This well is being drilled primarily as a "Pilot Hole" (with the potential to be produce). Possible lateral to be permitted in the future.

I hereby certify that the statements made in this form are, to the best of my knowledge, true, correct and complete.

Signed: _____ Date: 09/13/2012 Email: terry@rockymountainpermitting.com

Print Name: Terry L. Hoffman Title: Permit Agent

Based on the information provided herein, this Application for Permit-to-Drill complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved: Matthew Lee Director of COGCC Date: 11/23/2012

CONDITIONS OF APPROVAL, IF ANY:

All representations, stipulations and conditions of approval stated in this Form 2A for this location shall constitute representations, stipulations and conditions of approval for any and all subsequent operations on the location unless this Form 2A is modified by Sundry Notice, Form 4 or an Amended Form 2A.

GROUNDWATER/SURFACE WATER BASELINE SAMPLING

Baseline Water Testing: Prior to drilling, operator shall sample the two (2) closest domestic water wells, springs, or surface water features within a one (1) mile radius of the proposed oil and gas location. Testing preference shall be given to domestic water wells and springs over surface water. Testing of surface water features shall only be conducted if two (2) water wells or springs do not exist within a one (1) mile radius of the selected oil and gas location. If possible, the water wells or springs selected should be on opposite sides of the oil and gas location not exceeding a one (1) mile radius. If water wells or springs on opposite sides of the oil and gas location cannot be identified, then the two (2) closest wells or springs within a one (1) mile radius of the oil and gas location shall be sampled. The sample location shall be surveyed in accordance with Rule 215. Sampling and analysis shall be conducted in conformance with an accepted industry standard as described in Rule 910.b.(2).

Initial baseline testing shall include: pH, specific conductance, total dissolved solids (TDS), dissolved gases (methane, ethane, propane), alkalinity (total bicarbonate and carbonate as CaCO₃), major anions (bromide, chloride, fluoride, sulfate, nitrate and nitrite as N, phosphorus), major cations (calcium, iron, magnesium, manganese, potassium, sodium), other elements (barium, boron, selenium and strontium), presence of bacteria (iron related, sulfate reducing, slime and coliform), total petroleum hydrocarbons (TPH) and BTEX compounds (benzene, toluene, ethylbenzene and xylenes). Hydrogen sulfide shall also be measured using a field test method. Field observations such as pH, temperature, specific conductance, odor, water color, sediment, bubbles, and effervescence shall also be included. COGCC recommends that the latest version of EPA SW 846 analytical methods be used where possible and that analyses of samples be performed by laboratories that maintain state or national accreditation programs.

If free gas or a dissolved methane concentration greater than 1.0 milligram per liter (mg/l) is detected in a water well, gas compositional analysis and stable isotope analysis of the methane (carbon and hydrogen – 12C, 13C, 1H and 2H) shall be performed to determine gas type. If test results indicated thermogenic or a mixture of thermogenic and biogenic gas. If the methane concentration increases by more than 5.0 mg/l between sampling periods, or increases to more than 10. mg/l, the operator shall notify the Director and the owner of the water well immediately.

After 90 days, but less than 180 days of completion of the first proposed well a "post-completion" test shall be performed for the same analytical parameters listed above and repeated one (1), three (3) and six (6) years thereafter. If the well is a non-producing well, then the one (1), three (3) and six (6) year samples will not be required. If no significant changes from the baseline have been identified after the third test (i.e. the six-year test), no further testing shall be required.

Additional "post-completion" test(s) may be required if changes in water quality are identified during follow-up testing. The Director may require further water well sampling at any time in response to complaints from water well owners.

Copies of all test results described above shall be provided to the Director and the landowner where the water quality testing well is located within three (3) months of collecting the samples used for the test. The analytical data and surveyed well locations shall also be submitted to the Director in an electronic data deliverable format.

Operator may conduct baseline groundwater sampling (if water wells are available for sampling) in accordance with the Colorado Oil and Gas Association (COGA) Voluntary Baseline Groundwater Quality Sampling Program (updated November 15, 2011).

Documented refusal to grant access by well owner or surface owner (for surface water and spring sampling) shall not constitute a violation of this COA.

SITE SPECIFIC COAs:

Operator must implement best management practices to contain any unintentional release of fluids, including any fluids conveyed via temporary surface or buried pipelines.

Operator must ensure secondary containment for any volume of fluids contained at well site during drilling and completion operations (as shown on the Proposed BMPs attachment); including, but not limited to, construction of a berm or diversion dike, diversion/collection trenches within and/or outside of berms/dikes, site grading, or other comparable measures (i.e., best management practices (BMPs) associated with stormwater management) sufficiently protective of nearby surface water. Any berm constructed at the well pad location will be stabilized, inspected at regular intervals (at least every 14 days), and maintained in good condition.

Notify the COGCC 48 hours prior to start of pad construction, rig mobilization, spud, and start of hydraulic stimulation operations using Form 42 (the appropriate COGCC individuals will automatically be email notified, including the LGD for hydraulic stimulation operations).

The moisture content of any cuttings in a cuttings pit, trench, or pile shall be as low as practicable to prevent accumulation of liquids greater than de minimis amounts. At the time of closure, if the drill cuttings are to be left onsite, they must also meet the applicable standards of table 910-1.

Flowback and stimulation fluids must be sent to tanks, separators, or other containment/filtering equipment before the fluids can be placed into any pipeline, storage vessel, or lined pit (only if an amended Form 2A has been submitted/approved and a Form 15 Earthen Pit Permitted has been submitted/approved) located on the well pad; or into tanker trucks for offsite disposal. The flowback and stimulation fluid tanks, separators, or other containment/filtering equipment must be placed on the well pad in an area with additional downgradient perimeter berming. The area where flowback fluids will be stored/reused must be constructed to be sufficiently impervious to contain any spilled or released material.

Berms or other containment devices shall be constructed to be sufficiently impervious (preferably corrugated steel with poly liner) to contain any spilled or released material around crude oil, condensate, and produced water storage tanks.

The access road will be constructed to prevent sediment migration from the access road to nearby surface water or any drainages leading to other nearby surface waters or wetlands areas.

Attachment Check List

Att Doc Num	Name
2106473	CORRESPONDENCE
400296794	FORM 2A SUBMITTED
400296937	NRCS MAP UNIT DESC
400296938	OTHER
400306989	LOCATION PICTURES
400306994	REFERENCE AREA PICTURES
400315439	ACCESS ROAD MAP
400315440	HYDROLOGY MAP
400315442	LOCATION DRAWING
400315443	REFERENCE AREA MAP

Total Attach: 10 Files

General Comments

User Group	Comment	Comment Date
Permit	No LGD or public comments. Final Review--passed.	11/21/2012 10:58:33 AM
DOW	CPW has reviewed the applicants permit for this well pad location. CPW affirms that the lease stipulations and conditions of approval that will be assigned to this permit by the BLM will suffice to address wildlife habitat and mitigation concerns. Jacob Davidson, 15:46, 10-25-2012	10/25/2012 3:46:56 PM
OGLA	Initiated/Completed OGLA Form 2A review on 10-23-12 by Dave Kubeczko; requested acknowledgement of fluid containment, spill/release BMPs, baseline GW/SW sampling, tank berming, flowback to tanks, sediment control access road, baseline water testing, and cuttings low moisture content COAs from operator on 10-23-12; received acknowledgement of COAs from operator on 11-20-12; passed by CPW on 10-25-12 with BLM stipulations and COAs acceptable; passed OGLA Form 2A review on 11-21-12 by Dave Kubeczko; fluid containment, spill/release BMPs, baseline GW/SW sampling, tank berming, flowback to tanks, sediment control access road, baseline water testing, and cuttings low moisture content COAs.	10/23/2012 12:29:44 PM
Permit	Removed plugging bond.	10/18/2012 9:35:13 AM

Total: 4 comment(s)

BMP

<u>Type</u>	<u>Comment</u>
Storm Water/Erosion Control	<p>Endeavour Operating Corporation Wiley #22-3-97-1 NWNW Section 22-T3N-R97W Rio Blanco Co., Colorado</p> <p>Best Management Practices Summary</p> <p>Stormwater Management Plans (SWMP) will be in place to address construction, drilling and operations associated with Oil & Gas development throughout the state of Colorado in accordance with Colorado Department of Public Health and Environment (CDPHE). BMP's will be constructed around the perimeter of the site prior to, or at the beginning of construction. The BMP's used will vary according to the location, and will remain in place until the pad reaches final reclamation.</p> <p>Spill Prevention Control and Counter measures (SPCC) plans will be in place to address any possible spills associated with Oil & Gas operations throughout the state of Colorado in accordance with CFR12.</p> <p>Housekeeping will consist of neat and orderly storage of materials and fluids. Wastes will be temporarily stored in sealed containers and regularly collected and disposed of at offsite, suitable facilities. If spills occur prompt cleanup will be required to minimize any commingling of waste materials with stormwater runoff. Routine maintenance will be limited to fueling and lubrication of equipment. Drip pans will be used during routine fueling and maintenance to contain spills or leaks. Any waste product from maintenance will be containerized and transported offsite for disposal or recycling. There will be no major equipment overhauls conducted onsite. Equipment will be transported offsite for major overhauls. Cleanup will consist of patrolling the roadways, access areas, and other work areas to pick up trash, scrap debris, other discarded materials, and any contaminated soil. These materials will be disposed of properly.</p> <p>The above BMP's will be provided to all Endeavour Operating Corporation, contractors and will be posted in the company trailer located on location during drilling, completion and production operations.</p>

Total: 1 comment(s)