

Well

Operator Encana Oil & Gas (USA) Inc.
Location NESE Section 27-T4N-R65W
County Weld
State Colorado
Field Wattenberg
Footages 2482' FSL AND 289' FEL
Elevation 4727' GR
API 05-123-26204-00

Libsack 8-4-27

Spud Date 02-13-2008
First Production 03-05-2008

Log Tops

Sussex	4292'
Shannon	4980'
Niobrara	6774'
Codell	7059'
J Sand	7527'
TD	7745'

TOC
6520'

Set CIBP @ 7120' on 8/11/11.
Drilled out 10/25/11

Set CFP @ 6910' on 8/11/11.
Drilled out 10/25/11

Production Tubing
2 3/8" @ 7519'

Production Casing and Cement
4-1/2", 11.6 ppf, landed at 7724'
with 220 sxs

7673' — PBDT

7745' — TD

Surface Hole
12-1/4"

Surface Casing
24# 8-5/8" landed at 639'
Cement w/ 335 sxs to surface

Main Hole
7-7/8" to TD

Stage Cement
4036' - 4720'

Niobrara Refrac
Perfed 6774-6790', 112 holes
Frac'd 6774-6868 with 131,741 gal
frac fluid and 250,100# sand.
8/11/11

Codell Refrac
Frac'd 7058' - 7076'
with 114,375 gal frac fluid and
250,120# sand. 8/11/11

Niobrara - Codell Perf
6848' - 6868'
7058' - 7076'
w/ 112 holes

NB-CD RECOMPLETION; SET CFP
@7170'. FRAC CODL W/113,484 GAL
FRAC FLUID AND 253,040# SAND
3/5/2008. SET CFP @6960'. FRAC
NBRR W/170,226 GAL FRAC FLUID
AND 253,540# SAND
3/5/2008

J-Sand Perf
7544' - 7562'
w/ 36 holes

JSND COMPLETION; FRAC JSND
W/165,948 GAL FRAC FLUID AND
253,340# SAND.
3/5/2008

