

CANYON CREEK 43-13

Operator	EnCana Oil & Gas (USA) Inc.
Location	NWSE Section 13-T1N-R69W
County	BOULDER
State	Colorado
Field	Wattenberg
Footages	2045' FSL & 2133' FEL

Spud Date: 06-27-12
TD Date: 07-01-12

Log Tops

Sussex	4723'
Niobrara	7644'
Codell	8048'
J Sand	8484'

Production Tubing

2-3/8" tubing, set 8462'

8650' — Driller's
TD

Conductor

Set @ 182'

Surface Casing and Cement

8 5/8", 24#, landed @838', cemented with 400 sxs

Main Hole

7-7/8" to TD

Production Casing and Cement

4-1/2", 11.6#, landed @ 8637', cemented with 700 sxs

CBP

Set @ 7570'. 08-15-12

Drilled out on 08-16-12

Perf'd the Niobrara from 7,648-7,654'; 7,806-7817' @ 4 spf

Frac'd the Niobrara 7,648-7,654'; 7,806-7817' (88 holes), w/

101,244 gals 18 # pHaser Hybrid cross linked gel containing

248,050 # 30/50 sand. 08-06-12

CFP

Set @ 7870'. 08-04-12

Drilled out on 08-16-12

Perf'd the Codell from 8049' – 8063' @ 3 spf

Frac'd the Codell 8,049' – 8,063' (42 holes) w/ 88343 gal 22#

pHaser Hybrid cross linked gel containing 252,144 # 20/40 sand.

08-04-12

CFP

Set @ 8325' . 08-04-12

Drilled out on 08-16-12

Perf'd the J Sand @8495' - 8511' @ 3 spf

Frac'd the J-Sand 8,495' – 8,511', (48 holes)w/ 63,121 gal 18 #

pHaser Hybrid cross linked gel containing 242,600 # 20/40 Sand.

08-04-12