
PIONEER
HIGH RESOLUTION INDUCTION ELECTRICAL / COMPENSATED NEUTRON
Company: EnCana Oil & Gas (USA) Inc.
Well: Dowdy 9-2-10
Field: Wildcat
County: Uintah
State: Utah
Location: 2,000' FSL & 1,800' FEL, Sec. 2, T9S, R19E
Permanent Datum: Ground Level
Elevation: 5,000 ft
Log Measured From: KB
Drilling Measured From: KB
Elevation: KB 5,016 ft, GL 5,000 ft
Date: 10-Jul-08
Run Number: ONE
Depth Driller: 11,314 ft
Depth Logger: 11,314 ft
Bottom Logged Interval: 11,314 ft
Top Logged Interval: 2,000 ft
Casing Driller: 9.625 in @ 2,000 ft
Casing Logger: 2,000 ft
Bit Size: 8.750 in
Type Fluid in Hole: Water
Density: 8.4 lbm/gal
Viscosity: 26 s/qt
Fluid Loss: 10 cc
Source of Sample: Flowline
Rm @ Measured Temp: 0.8 @ 70 °F
Rmf @ Measured Temp: 0.6 @ 70 °F
Rmc @ Measured Temp: 1.1 @ 70 °F
Source of Rmf / Rmc: Calculated / Calculated
Rm @ BHT: 0.4 @ 200 °F
Time Since Circulation: 12 hrs
Max Recorded Temp: 200 °F
Equipment Number: 1
Location: Vernal, UT
Recorded By: Hall / Ellsworth
Witnessed By: Rich Dimmick
Run / Service Order: 1 / 08-0707-DEN-1
Run Comments: Logged with 0 psi surface pressure
Tool Name: Size / Weight / Length
Gamma Ray: 3.625 in / 30 lbs / 15.00 ft
Compensated Neutron: 3.625 in / 30 lbs / 15.00 ft
Array Induction: 3.625 in / 30 lbs / 15.00 ft
Bottom Hole Temperature: 200 °F
Logging Disclaimer
All interpretations are opinions based on inferences from electrical or other measurements and Pioneer Wireline Services, LLC cannot and does not guarantee the accuracy or correctness of any interpretations, and Pioneer Wireline Services, LLC shall not be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees.
Comments
Annular volume calculated for 4.5" casing
Ensign Drilling Rig 122
Thank you for using Pioneer Energy Services.
Database File: 11314-db
Dataset Pathname: final
Presentation Format: main
Dataset Creation: Wed Oct 8 08:05:20 2008
Charted by: Depth in Feet scaled 1:240
Density Caliper (in) 16
Gamma Ray (GAPI) 300
SP (mV) 160
HDAR (BCI)
Deep Resistivity (Ohm-m) 200.40
Medium Resistivity (Ohm-m) 200.40
Shallow Resistivity (Ohm-m) 200
RT (Ohm-m) 200
Density Porosity (pu)
Neutron Porosity (pu)
2.65 SS Matrix
Matrix Change @ 7550 ft
Pulled Tight
Opened Caliper
Closed Caliper
Caliper
Gamma Ray
SP
Logger's TD 11314
Medium Resistivity
Deep Resistivity
Shallow Resistivity
Density Porosity
Neutron Porosity