

FORM  
5A

Rev  
06/12

State of Colorado  
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

400337260

Date Received:

01/29/2013

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 10392  
2. Name of Operator: TEKTON WINDSOR LLC  
3. Address: 640 PLAZA DRIVE #290  
City: HIGHLANDS State: CO Zip: 80129  
4. Contact Name: CLAYTON DOKE  
Phone: (970) 669-7411  
Fax: (970) 669-4077

5. API Number 05-123-35324-00  
6. County: WELD  
7. Well Name: FRYE FARMS  
Well Number: 7-5-32  
8. Location: QtrQtr: SESE Section: 32 Township: 6N Range: 67W Meridian: 6  
9. Field Name: WATTENBERG Field Code: 90750

Completed Interval

FORMATION: CODELL Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 07/17/2012 End Date: 07/17/2012 Date of First Production this formation:

Perforations Top: 7420 Bottom: 7432 No. Holes: 48 Hole size: 042/100

Provide a brief summary of the formation treatment: Open Hole: ☐

167,172 gals FR water, 105,054 gals SLF, 119,598 lbs 30/50 White w/ 3,478# LC 20/40.

This formation is commingled with another formation: ☒ Yes ☐ No

Total fluid used in treatment (bbl): 6405 Max pressure during treatment (psi): 4871

Total gas used in treatment (mcf): 0 Fluid density at initial fracture (lbs/gal): 0.75

Type of gas used in treatment: Min frac gradient (psi/ft): 0.84

Total acid used in treatment (bbl): 23 Number of staged intervals: 1

Recycled water used in treatment (bbl): 0 Flowback volume recovered (bbl):

Fresh water used in treatment (bbl): 3933 Disposition method for flowback: DISPOSAL

Total proppant used (lbs): 119598 Rule 805 green completion techniques were utilized: ☐

Reason why green completion not utilized: PIPELINE

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: Hours: Bbl oil: Mcf Gas: Bbl H2O:

Calculated 24 hour rate: Bbl oil: Mcf Gas: Bbl H2O: GOR:

Test Method: Casing PSI: Tubing PSI: Choke Size:

Gas Disposition: Gas Type: Btu Gas: API Gravity Oil:

Tubing Size: Tubing Setting Depth: Tbg setting date: Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA-CODELL Status: PRODUCING Treatment Type: \_\_\_\_\_

Treatment Date: \_\_\_\_\_ End Date: \_\_\_\_\_ Date of First Production this formation: 08/21/2012

Perforations Top: 7228 Bottom: 7432 No. Holes: 140 Hole size: 039/100

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole: ☐

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_

Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): \_\_\_\_\_

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_

Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): 2921

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: \_\_\_\_\_

Total proppant used (lbs): \_\_\_\_\_ Rule 805 green completion techniques were utilized: ☐

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: 08/21/2012 Hours: 18 Bbl oil: 61 Mcf Gas: 24 Bbl H2O: 41

Calculated 24 hour rate: Bbl oil: 81 Mcf Gas: 32 Bbl H2O: 55 GOR: 393

Test Method: FLOWING Casing PSI: 950 Tubing PSI: \_\_\_\_\_ Choke Size: 012/64

Gas Disposition: SOLD Gas Type: WET Btu Gas: 1228 API Gravity Oil: 53

Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production:

Date formation Abandoned: \_\_\_\_\_ Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 07/18/2012 End Date: 07/18/2012 Date of First Production this formation: \_\_\_\_\_

Perforations Top: 7228 Bottom: 7312 No. Holes: 92 Hole size: 039/100

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole: ☐

300,942 gals FR water and acid, 204,695 gals SLF, 210,080 lbs 30/50 White.

This formation is commingled with another formation: ☒ Yes ☐ No

Total fluid used in treatment (bbl): 11874 Max pressure during treatment (psi): 5093

Total gas used in treatment (mcf): 0 Fluid density at initial fracture (lbs/gal): 0.25

Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): 0.89

Total acid used in treatment (bbl): 23 Number of staged intervals: 1

Recycled water used in treatment (bbl): 0 Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): 7057 Disposition method for flowback: DISPOSAL

Total proppant used (lbs): 210080 Rule 805 green completion techniques were utilized: ☐

Reason why green completion not utilized: PIPELINE

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: \_\_\_\_\_ Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_

Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_

Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_

Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_

Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

Comment: \_\_\_\_\_

The flowback recovery volume is from both the Niobrara and Codell formations

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Clayton Duke

Title: Consultant Date: 1/29/2013 Email: cdoke@petersonenergy.com

**Attachment Check List**

Att Doc Num	Name
400337260	FORM 5A SUBMITTED
400337272	WELLBORE DIAGRAM

Total Attach: 2 Files

**General Comments**

User Group	Comment	Comment Date

Total: 0 comment(s)