
Company: Halliburton Energy Services
Well: 1-35S-19E
Field: Wildcat
County: Labette
State: Kansas
Location: 1-35S-19E
Elevation: 1,000 ft
Date: 2024-03-15
Operator: Halliburton Energy Services
Engineer: J. Martinez
Witness: R. Thompson
Run No: 1
Depth Driller: 4,200 ft
Depth Logger: 4,198 ft
Bottom Log Interval: 4,195 ft
Top Log Interval: 3,800 ft
Casing Driller: 8.625 in @ 1,200 ft
Casing Logger: 8.625 in @ 1,198 ft
Bit Size: 7.875 in
Type Fluid in Hole: Water-based mud
Density / Viscosity: 9.2 lb/gal / 48 s
pH / Fluid Loss: 9.5 / 6.2 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Source Rmf / Rmc: Measured / Measured
Rm @ BHT: 0.12 @ 118 °F
Time Since Circ: 6 hr
Max Rec Temp: 118 °F
Equipment / Location: 1-35S-19E
Recorded By: J. Martinez
Witnessed By: R. Thompson
Run Number: 1
Depth Driller: 4,200 ft
Depth Logger: 4,198 ft
Schlumberger
Halliburton
Baker Hughes
Weatherford
Gamma Ray
Resistivity
Density
Neutron
Sonic
Caliper
Spontaneous Potential
Photoelectric Factor
Mud Weight
Viscosity
Fluid Loss
Temperature
Pressure
Flow Rate
Run 1
Run 2
Run 3
Run 4
Run 5
Run 6
Run 7
Run 8
Run 9
Run 10
Run 11
Run 12
Run 13
Run 14
Run 15
Run 16
Run 17
Run 18
Run 19
Run 20
Run

Company File: Area = 96
Company Contact: Job =
Prepared by: Date = Tue Jul 30 08:25:29 2013, Log 8:00 AM 8:00
Prepared for: Depth of Hole Logged = 748


Schlumberger
Gamma Ray (GAPI)
0
150
Caliper (in)
6
16
Resistivity (ohm.m)
0.2
2000
Neutron Porosity (dec)
0.45
-0.15
Density (g/cm3)
1.95
2.95
Photoelectric Factor (b/e)
0
10
Compensated Neutron (dec)
0.45
-0.15
Compensated Density (g/cm3)
1.95
2.95
Photoelectric Factor (b/e)
0
10