

FORM  
5A

Rev  
06/12

State of Colorado  
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

400389474

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 100185  
2. Name of Operator: ENCANA OIL & GAS (USA) INC  
3. Address: 370 17TH ST STE 1700  
City: DENVER State: CO Zip: 80202-  
4. Contact Name: Sheilla Reed-High  
Phone: (720) 876-3678  
Fax: (720) 876-4678

5. API Number 05-123-34764-00  
6. County: WELD  
7. Well Name: STELLING  
Well Number: 3A-4H  
8. Location: QtrQtr: SESW Section: 4 Township: 1N Range: 65W Meridian: 6  
9. Field Name: WATTENBERG Field Code: 90750

Completed Interval

FORMATION: NIOBRARA Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 08/08/2012 End Date: 08/12/2012 Date of First Production this formation: 11/04/2012

Perforations Top: 7555 Bottom: 11559 No. Holes: 891 Hole size: 0.38

Provide a brief summary of the formation treatment: Open Hole: ☐

Stages 1-15 treated with a total of 26,456 bbls slickwater.

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): 26456 Max pressure during treatment (psi): 7730

Total gas used in treatment (mcf): Fluid density at initial fracture (lbs/gal): 8.34

Type of gas used in treatment: Min frac gradient (psi/ft): 0.97

Total acid used in treatment (bbl): Number of staged intervals: 15

Recycled water used in treatment (bbl): 26456 Flowback volume recovered (bbl):

Fresh water used in treatment (bbl): Disposition method for flowback: RECYCLE

Total proppant used (lbs): 4777785 Rule 805 green completion techniques were utilized: ☒

Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 11/04/2012 Hours: 24 Bbl oil: 347 Mcf Gas: 391 Bbl H2O: 154

Calculated 24 hour rate: Bbl oil: 347 Mcf Gas: 391 Bbl H2O: 154 GOR: 1127

Test Method: FLOWING Casing PSI: 1755 Tubing PSI: 1411 Choke Size: 12/64

Gas Disposition: SOLD Gas Type: DRY Btu Gas: 1142 API Gravity Oil: 45

Tubing Size: 2 + 3/8 Tubing Setting Depth: 7205 Tbg setting date: 08/30/2012 Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

Comment:

--

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Sheilla Reed-High

Title: Drilling and Compl. Tech. Date: \_\_\_\_\_ Email sheilla.reedhigh@Encana.com  
:

### Attachment Check List

Att Doc Num	Name
400389475	WELLBORE DIAGRAM

Total Attach: 1 Files

### General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>

Total: 0 comment(s)