



Kubeczko - DNR, Dave <dave.kubeczko@state.co.us>

## WPX Energy Rocky Mountain LLC, Savage RWF 22-25 Pad, SENW Sec 25 T6S R94W, Garfield County, Form 2A (#400382106) Review

Kubeczko - DNR, Dave <dave.kubeczko@state.co.us>

Tue, Mar 26, 2013 at 4:53 PM

To: Dave Kubeczko - DNR <dave.kubeczko@state.co.us>

Scan No. 2106532      CORRESPONDENCE      2A#400382106

----- Forwarded message -----

From: Kubeczko - DNR, Dave <dave.kubeczko@state.co.us>

Date: Tue, Mar 26, 2013 at 4:52 PM

Subject: WPX Energy Rocky Mountain LLC, Savage RWF 22-25 Pad, SENW Sec 25 T6S R94W, Garfield County, Form 2A (#400382106) Review

To: greg.j.davis@wpxenergy.com

Greg,

I have been reviewing the Savage RWF 22-25 Pad **Form 2A** (#400382106). COGCC would like to attach the following conditions of approval (COAs) based on the information and data WPX Energy has submitted on or attached to the Form 2A prior to passing the Oil and Gas Location Assessment (OGLA) review.

**General:** The following conditions of approval (COAs) will apply:

**COA 91** - Notify the COGCC 48 hours prior to start of pad construction, rig mobilization, spud, and start of hydraulic stimulation operations using Form 42 (the appropriate COGCC individuals will automatically be email notified, including the LGD for hydraulic stimulation operations).

**COA 5** - Operator must implement best management practices to contain any unintentional release of fluids, including any fluids conveyed via temporary surface pipelines

**COA 23** - Operator must ensure 110 percent secondary containment for any volume of fluids (excluding freshwater) contained at well site during drilling and completion operations (as shown on the Construction Layout Drawings attachment); including, but not limited to, construction of a berm or diversion dike, diversion/collection trenches within and/or outside of berms/dikes, site grading, or other comparable measures (i.e., best management practices (BMPs) associated with stormwater management) sufficiently protective of nearby surface water. Any berm constructed at the well pad location will be stabilized, inspected at regular intervals (at least every 14 days), and maintained in good condition.

**COA 28** - The location is in an area of moderate run off potential; therefore the pad and access road shall be constructed to prevent any stormwater run-on and/or stormwater runoff. Standard stormwater BMPs must be implemented at this location to insure compliance with CDPHE and COGCC requirements and to prevent any stormwater run-on and /or stormwater runoff.

**COA 38** - The moisture content of any drill cuttings in a cuttings pit, trench, or pile shall be as low as practicable to prevent accumulation of liquids greater than de minimis amounts. At the time of closure, if drill cuttings are to remain/disposed of onsite, they must also meet the applicable standards of table 910-1.

**COA 25** - Flowback and stimulation fluids must be sent to tanks, separators, or other containment/filtering equipment before the fluids can be placed into any pipeline, storage vessel, or lined pit (only if an amended Form 2A has been submitted/approved and a Form 15 Earthen Pit Permitted has been submitted/approved) located on the well pad; or into tanker trucks for offsite disposal. The flowback and stimulation fluid tanks, separators, or other containment/filtering equipment must be placed on the well pad in an area with additional downgradient perimeter berming. The area where flowback fluids will be stored/reused must be constructed to be sufficiently impervious to contain any spilled or released material.

**COA 58** - Berms or other containment devices shall be constructed to be sufficiently impervious (preferably corrugated steel with poly liner) to contain any spilled or released material around crude oil, condensate, and produced water storage tanks.

**COA 48** - Operator must implement best management practices to contain any unintentional release of fluids along all portions of the surface pipeline route where temporary pumps and other necessary equipment are located.

**COA 49** - Operator must routinely inspect the entire length of the surface pipeline to ensure integrity.

**COA 54** - Operator must ensure 110 percent secondary containment for any potential volume of fluids that may be released from the surface pipeline at all stream, intermittent stream, ditch, and drainage crossings.

**COA 55** - Operator will utilize, to the extent practical, all existing access and other public roads, and/or existing pipeline right-of-ways, when placing/routing the surface pipelines. This will reduce surface disturbance and fragmentation of wildlife habitat in the area.

Based on the information provided in the Form 2A by WPX, COGCC will attach these COAs to the Form 2A permit, WPX does not need to respond, unless you have questions or concerns with details in this email. If you have any questions, please do not hesitate to call me at (970) 309-2514 (cell), or email. Thanks.

Dave

**David A. Kubeczko, PG**

**Oil and Gas Location Assessment Specialist**

Colorado Oil & Gas Conservation Commission

Northwest Area Office

796 Megan Avenue, Suite 201

Rifle, CO 81650

FAX: (970) 625-5682

Cell: (970) 309-2514

[dave.kubeczko@state.co.us](mailto:dave.kubeczko@state.co.us)



*Please consider the environment before printing this e-mail*

--  
Dave

**David A. Kubeczko, PG**  
**Oil and Gas Location Assessment Specialist**

Colorado Oil & Gas Conservation Commission  
Northwest Area Office  
796 Megan Avenue, Suite 201  
Rifle, CO 81650  
FAX: (970) 625-5682  
Cell: (970) 309-2514  
[dave.kubeczko@state.co.us](mailto:dave.kubeczko@state.co.us)

 *Please consider the environment before printing this e-mail*