



## **PICEANCE HL NAD 83**

**RG 26-01S-098W**

**RGU 42-26-198**

**RGU 432-26-198 - Slot B7**

**Wellbore #1**

**Plan: Design #1 24Jan13 kjs**

## **Standard Planning Report - Geographic**

**09 April, 2013**



**WPX Energy**  
Planning Report - Geographic

<b>Database:</b>	COMPASS-PICEANCE	<b>Local Co-ordinate Reference:</b>	Well RGU 432-26-198 - Slot B7
<b>Company:</b>	PICEANCE HL NAD 83	<b>TVD Reference:</b>	KELLY BUSHING @ 6643.00usft (Cyclone 29 (21' RKB) kjs)
<b>Project:</b>	RG 26-01S-098W	<b>MD Reference:</b>	KELLY BUSHING @ 6643.00usft (Cyclone 29 (21' RKB) kjs)
<b>Site:</b>	RGU 42-26-198	<b>North Reference:</b>	True
<b>Well:</b>	RGU 432-26-198	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1 24Jan13 kjs		

<b>Project</b>	RG 26-01S-098W, Rio Blanco County, CO		
<b>Map System:</b>	US State Plane 1983	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	North American Datum 1983		
<b>Map Zone:</b>	Colorado Central Zone		

<b>Site</b>	RGU 42-26-198			
<b>Site Position:</b>		<b>Northing:</b>	1,778,121.90 usft	<b>Latitude:</b> 39.93524
<b>From:</b> Map		<b>Easting:</b>	2,199,615.70 usft	<b>Longitude:</b> -108.35451
<b>Position Uncertainty:</b>	0.00 usft	<b>Slot Radius:</b>	13.200 in	<b>Grid Convergence:</b> -1.8003 °

<b>Well</b>	RGU 432-26-198 - Slot B7			
<b>Well Position</b>	<b>+N/-S</b>	0.00 usft	<b>Northing:</b>	1,778,097.10 usft
	<b>+E/-W</b>	0.00 usft	<b>Easting:</b>	2,199,598.80 usft
<b>Position Uncertainty</b>	0.00 usft		<b>Wellhead Elevation:</b>	
			<b>Ground Level:</b>	6,622.00 usft

<b>Wellbore</b>	Wellbore #1				
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination (°)</b>	<b>Dip Angle (°)</b>	<b>Field Strength (nT)</b>
	IGRF2010	1/24/2013	10.3617	65.9893	52,274

<b>Design</b>	Design #1 24Jan13 kjs			
<b>Audit Notes:</b>				
<b>Version:</b>	<b>Phase:</b>	PLAN	<b>Tie On Depth:</b>	0.00
<b>Vertical Section:</b>	<b>Depth From (TVD) (usft)</b>	<b>+N/-S (usft)</b>	<b>+E/-W (usft)</b>	<b>Direction (°)</b>
	0.00	0.00	0.00	278.09

<b>Plan Sections</b>										
<b>Measured Depth (usft)</b>	<b>Inclination (°)</b>	<b>Azimuth (°)</b>	<b>Vertical Depth (usft)</b>	<b>+N/-S (usft)</b>	<b>+E/-W (usft)</b>	<b>Dogleg Rate (°/100usft)</b>	<b>Build Rate (°/100usft)</b>	<b>Turn Rate (°/100usft)</b>	<b>TFO (°)</b>	<b>Target</b>
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.0000	
120.00	0.00	0.00	120.00	0.00	0.00	0.00	0.00	0.00	0.0000	
465.00	6.90	278.09	464.17	2.92	-20.54	2.00	2.00	0.00	278.0900	
3,522.98	6.90	278.09	3,500.00	54.62	-384.26	0.00	0.00	0.00	0.0000	
3,654.23	9.53	278.09	3,629.90	57.26	-402.82	2.00	2.00	0.00	0.0000	
6,991.26	9.53	278.09	6,920.92	134.95	-949.54	0.00	0.00	0.00	0.0000	
7,626.27	0.00	0.00	7,553.00	142.36	-1,001.68	1.50	-1.50	0.00	180.0000	
7,726.27	0.00	0.00	7,653.00	142.36	-1,001.68	0.00	0.00	0.00	0.0000	Mesaverde (25' Radius)
12,566.27	0.00	0.00	12,493.00	142.36	-1,001.68	0.00	0.00	0.00	0.0000	



**WPX Energy**  
Planning Report - Geographic

<b>Database:</b>	COMPASS-PICEANCE	<b>Local Co-ordinate Reference:</b>	Well RGU 432-26-198 - Slot B7
<b>Company:</b>	PICEANCE HL NAD 83	<b>TVD Reference:</b>	KELLY BUSHING @ 6643.00usft (Cyclone 29 (21' RKB) kjs)
<b>Project:</b>	RG 26-01S-098W	<b>MD Reference:</b>	KELLY BUSHING @ 6643.00usft (Cyclone 29 (21' RKB) kjs)
<b>Site:</b>	RGU 42-26-198	<b>North Reference:</b>	True
<b>Well:</b>	RGU 432-26-198	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1 24Jan13 kjs		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude	
0.00	0.00	0.00	0.00	0.00	0.00	1,778,097.10	2,199,598.80	39.93517	-108.35457	
120.00	0.00	0.00	120.00	0.00	0.00	1,778,097.10	2,199,598.80	39.93517	-108.35457	
Start Build 2.00										
465.00	6.90	278.09	464.17	2.92	-20.54	1,778,100.66	2,199,578.36	39.93518	-108.35464	
Hold 6.90 Inc, 278.09° azi										
500.00	6.90	278.09	498.91	3.51	-24.71	1,778,101.39	2,199,574.22	39.93518	-108.35466	
1,000.00	6.90	278.09	995.29	11.96	-84.18	1,778,111.70	2,199,515.04	39.93520	-108.35487	
1,234.41	6.90	278.09	1,228.00	15.93	-112.06	1,778,116.54	2,199,487.30	39.93521	-108.35497	
Green River Fm										
1,415.72	6.90	278.09	1,408.00	18.99	-133.62	1,778,120.28	2,199,465.84	39.93522	-108.35504	
A Groove										
1,500.00	6.90	278.09	1,491.67	20.42	-143.65	1,778,122.02	2,199,455.87	39.93522	-108.35508	
1,622.21	6.90	278.09	1,613.00	22.48	-158.18	1,778,124.54	2,199,441.40	39.93523	-108.35513	
B Groove										
1,909.29	6.90	278.09	1,898.00	27.34	-192.33	1,778,130.47	2,199,407.42	39.93524	-108.35525	
Dissolution Surface										
2,000.00	6.90	278.09	1,988.05	28.87	-203.12	1,778,132.34	2,199,396.69	39.93525	-108.35529	
2,500.00	6.90	278.09	2,484.43	37.32	-262.59	1,778,142.66	2,199,337.51	39.93527	-108.35550	
3,000.00	6.90	278.09	2,980.81	45.78	-322.06	1,778,152.97	2,199,278.34	39.93529	-108.35572	
3,002.21	6.90	278.09	2,983.00	45.82	-322.32	1,778,153.02	2,199,278.08	39.93529	-108.35572	
Garden Gulch										
3,183.52	6.90	278.09	3,163.00	48.88	-343.89	1,778,156.76	2,199,256.62	39.93530	-108.35579	
Orange Marker										
3,400.09	6.90	278.09	3,378.00	52.54	-369.65	1,778,161.23	2,199,230.99	39.93531	-108.35589	
Wasatch										
3,500.00	6.90	278.09	3,477.19	54.23	-381.53	1,778,163.29	2,199,219.16	39.93532	-108.35593	
3,522.98	6.90	278.09	3,500.00	54.62	-384.26	1,778,163.77	2,199,216.44	39.93532	-108.35594	
Start Build 2.00										
3,654.23	9.53	278.09	3,629.90	57.26	-402.82	1,778,166.98	2,199,197.97	39.93533	-108.35600	
Hold 9.52 Inclination										
3,905.81	9.53	278.09	3,878.00	63.11	-444.04	1,778,174.13	2,199,156.96	39.93534	-108.35615	
9 5/8"										
4,000.00	9.53	278.09	3,970.89	65.31	-459.47	1,778,176.81	2,199,141.61	39.93535	-108.35621	
4,500.00	9.53	278.09	4,464.00	76.95	-541.39	1,778,191.02	2,199,060.10	39.93538	-108.35650	
5,000.00	9.53	278.09	4,957.11	88.59	-623.30	1,778,205.23	2,198,978.59	39.93541	-108.35679	
5,500.00	9.53	278.09	5,450.21	100.23	-705.22	1,778,219.44	2,198,897.08	39.93544	-108.35708	
5,695.48	9.53	278.09	5,643.00	104.78	-737.25	1,778,224.99	2,198,865.21	39.93546	-108.35720	
Top of "G" Sand										
6,000.00	9.53	278.09	5,943.32	111.87	-787.14	1,778,233.64	2,198,815.57	39.93548	-108.35737	
6,060.51	9.53	278.09	6,003.00	113.28	-797.05	1,778,235.36	2,198,805.70	39.93548	-108.35741	
Fort Union										
6,500.00	9.53	278.09	6,436.43	123.51	-869.05	1,778,247.85	2,198,734.06	39.93551	-108.35767	
6,991.26	9.53	278.09	6,920.92	134.95	-949.54	1,778,261.81	2,198,653.97	39.93554	-108.35795	
Start Drop -1.50										
7,000.00	9.39	278.09	6,929.54	135.15	-950.96	1,778,262.06	2,198,652.55	39.93554	-108.35796	
7,456.21	2.55	278.09	7,383.00	141.83	-997.93	1,778,270.21	2,198,605.82	39.93556	-108.35813	
Ohio Creek										
7,500.00	1.89	278.09	7,426.76	142.06	-999.61	1,778,270.50	2,198,604.15	39.93556	-108.35813	
7,626.27	0.00	0.00	7,553.00	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814	
Vertical										



**WPX Energy**  
Planning Report - Geographic

<b>Database:</b>	COMPASS-PICEANCE	<b>Local Co-ordinate Reference:</b>	Well RGU 432-26-198 - Slot B7
<b>Company:</b>	PICEANCE HL NAD 83	<b>TVD Reference:</b>	KELLY BUSHING @ 6643.00usft (Cyclone 29 (21' RKB) kjs)
<b>Project:</b>	RG 26-01S-098W	<b>MD Reference:</b>	KELLY BUSHING @ 6643.00usft (Cyclone 29 (21' RKB) kjs)
<b>Site:</b>	RGU 42-26-198	<b>North Reference:</b>	True
<b>Well:</b>	RGU 432-26-198	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1 24Jan13 kjs		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
7,726.27	0.00	0.00	7,653.00	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814
<b>Mesaverde - Mesaverde</b>									
8,000.00	0.00	0.00	7,926.73	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814
8,500.00	0.00	0.00	8,426.73	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814
9,000.00	0.00	0.00	8,926.73	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814
9,136.27	0.00	0.00	9,063.00	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814
<b>Approx. Top Gas</b>									
9,500.00	0.00	0.00	9,426.73	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814
10,000.00	0.00	0.00	9,926.73	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814
10,500.00	0.00	0.00	10,426.73	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814
10,781.27	0.00	0.00	10,708.00	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814
<b>Cameo Coals</b>									
11,000.00	0.00	0.00	10,926.73	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814
11,346.27	0.00	0.00	11,273.00	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814
<b>Rollins SS</b>									
11,481.27	0.00	0.00	11,408.00	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814
<b>Cozzette</b>									
11,500.00	0.00	0.00	11,426.73	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814
11,696.27	0.00	0.00	11,623.00	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814
<b>Corcoran</b>									
12,000.00	0.00	0.00	11,926.73	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814
12,071.27	0.00	0.00	11,998.00	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814
<b>Upper Sego</b>									
12,316.27	0.00	0.00	12,243.00	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814
<b>Lower Sego</b>									
12,500.00	0.00	0.00	12,426.73	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814
12,566.27	0.00	0.00	12,493.00	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814
<b>TD at 12566.27 - TD</b>									

Design Targets									
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
Mesaverde (25' Radius) - plan hits target center - Circle (radius 25.00)	0.00	0.00	7,653.00	142.36	-1,001.68	1,778,270.86	2,198,602.09	39.93556	-108.35814

Casing Points					
Measured Depth (usft)	Vertical Depth (usft)	Name	Casing Diameter (in)	Hole Diameter (in)	
3,905.81	3,878.00	9 5/8"	9.625	13.500	



<b>Database:</b>	COMPASS-PICEANCE	<b>Local Co-ordinate Reference:</b>	Well RGU 432-26-198 - Slot B7
<b>Company:</b>	PICEANCE HL NAD 83	<b>TVD Reference:</b>	KELLY BUSHING @ 6643.00usft (Cyclone 29 (21' RKB) kjs)
<b>Project:</b>	RG 26-01S-098W	<b>MD Reference:</b>	KELLY BUSHING @ 6643.00usft (Cyclone 29 (21' RKB) kjs)
<b>Site:</b>	RGU 42-26-198	<b>North Reference:</b>	True
<b>Well:</b>	RGU 432-26-198	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1 24Jan13 kjs		

Formations						
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)	
1,234.41	1,228.00	Green River Fm				
1,415.72	1,408.00	A Groove				
1,622.21	1,613.00	B Groove				
1,909.29	1,898.00	Dissolution Surface				
3,002.21	2,983.00	Garden Gulch				
3,183.52	3,163.00	Orange Marker				
3,400.09	3,378.00	Wasatch				
5,695.48	5,643.00	Top of "G" Sand				
6,060.51	6,003.00	Fort Union				
7,456.21	7,383.00	Ohio Creek				
7,726.27	7,653.00	Mesaverde				
9,136.27	9,063.00	Approx. Top Gas				
10,781.27	10,708.00	Cameo Coals				
11,346.27	11,273.00	Rollins SS				
11,481.27	11,408.00	Cozzette				
11,696.27	11,623.00	Corcoran				
12,071.27	11,998.00	Upper Sego				
12,316.27	12,243.00	Lower Sego				
12,566.27	12,493.00	TD				

Plan Annotations					
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates			
		+N/-S (usft)	+E/-W (usft)	Comment	
120.00	120.00	0.00	0.00	Start Build 2.00	
465.00	464.17	2.92	-20.54	Hold 6.90 Inc, 278.09° azi	
3,522.98	3,500.00	54.62	-384.26	Start Build 2.00	
3,654.23	3,629.90	57.26	-402.82	Hold 9.52 Inclination	
6,991.26	6,920.92	134.95	-949.54	Start Drop -1.50	
7,626.27	7,553.00	142.36	-1,001.68	Vertical	
7,726.27	7,653.00	142.36	-1,001.68	Mesaverde	
12,566.27	12,493.00	142.36	-1,001.68	TD at 12566.27	