



## **PICEANCE HL NAD 83**

**RG 26-01S-098W**

**RGU 42-26-198**

**RGU 542-26-198 - Slot A7**

**Wellbore #1**

**Plan: Design #1 24Jan13 kjs**

## **Standard Planning Report - Geographic**

**09 April, 2013**



**WPX Energy**  
Planning Report - Geographic

<b>Database:</b>	COMPASS-PICEANCE	<b>Local Co-ordinate Reference:</b>	Well RGU 542-26-198 - Slot A7
<b>Company:</b>	PICEANCE HL NAD 83	<b>TVD Reference:</b>	KELLY BUSHING @ 6643.00usft (Cyclone 29 (21' RKB) kjs)
<b>Project:</b>	RG 26-01S-098W	<b>MD Reference:</b>	KELLY BUSHING @ 6643.00usft (Cyclone 29 (21' RKB) kjs)
<b>Site:</b>	RGU 42-26-198	<b>North Reference:</b>	True
<b>Well:</b>	RGU 542-26-198	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1 24Jan13 kjs		

<b>Project</b>	RG 26-01S-098W, Rio Blanco County, CO		
<b>Map System:</b>	US State Plane 1983	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	North American Datum 1983		
<b>Map Zone:</b>	Colorado Central Zone		

<b>Site</b>	RGU 42-26-198			
<b>Site Position:</b>		<b>Northing:</b>	1,778,121.90 usft	<b>Latitude:</b> 39.93524
<b>From:</b> Map		<b>Easting:</b>	2,199,615.70 usft	<b>Longitude:</b> -108.35451
<b>Position Uncertainty:</b>	0.00 usft	<b>Slot Radius:</b>	13.200 in	<b>Grid Convergence:</b> -1.8003 °

<b>Well</b>	RGU 542-26-198 - Slot A7			
<b>Well Position</b>	<b>+N/-S</b>	0.00 usft	<b>Northing:</b>	1,778,091.50 usft
	<b>+E/-W</b>	0.00 usft	<b>Easting:</b>	2,199,607.00 usft
<b>Position Uncertainty</b>	0.00 usft		<b>Wellhead Elevation:</b>	
			<b>Ground Level:</b>	6,622.00 usft

<b>Wellbore</b>	Wellbore #1				
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination (°)</b>	<b>Dip Angle (°)</b>	<b>Field Strength (nT)</b>
	IGRF2010	1/24/2013	10.3617	65.9893	52,274

<b>Design</b>	Design #1 24Jan13 kjs			
<b>Audit Notes:</b>				
<b>Version:</b>	<b>Phase:</b>	PLAN	<b>Tie On Depth:</b>	0.00
<b>Vertical Section:</b>	<b>Depth From (TVD) (usft)</b>	<b>+N/-S (usft)</b>	<b>+E/-W (usft)</b>	<b>Direction (°)</b>
	0.00	0.00	0.00	107.99

<b>Plan Sections</b>										
<b>Measured Depth (usft)</b>	<b>Inclination (°)</b>	<b>Azimuth (°)</b>	<b>Vertical Depth (usft)</b>	<b>+N/-S (usft)</b>	<b>+E/-W (usft)</b>	<b>Dogleg Rate (°/100usft)</b>	<b>Build Rate (°/100usft)</b>	<b>Turn Rate (°/100usft)</b>	<b>TFO (°)</b>	<b>Target</b>
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.0000	
120.00	0.00	0.00	120.00	0.00	0.00	0.00	0.00	0.00	0.0000	
226.89	2.14	107.99	226.87	-0.62	1.90	2.00	2.00	0.00	107.9918	
7,460.57	2.14	107.99	7,455.51	-83.97	258.55	0.00	0.00	0.00	0.0000	
7,603.09	0.00	0.00	7,598.00	-84.79	261.08	1.50	-1.50	0.00	180.0000	
7,703.09	0.00	0.00	7,698.00	-84.79	261.08	0.00	0.00	0.00	0.0000	Mesaverde (25' Radius
12,573.09	0.00	0.00	12,568.00	-84.79	261.08	0.00	0.00	0.00	0.0000	



**WPX Energy**  
Planning Report - Geographic

<b>Database:</b>	COMPASS-PICEANCE	<b>Local Co-ordinate Reference:</b>	Well RGU 542-26-198 - Slot A7
<b>Company:</b>	PICEANCE HL NAD 83	<b>TVD Reference:</b>	KELLY BUSHING @ 6643.00usft (Cyclone 29 (21' RKB) kjs)
<b>Project:</b>	RG 26-01S-098W	<b>MD Reference:</b>	KELLY BUSHING @ 6643.00usft (Cyclone 29 (21' RKB) kjs)
<b>Site:</b>	RGU 42-26-198	<b>North Reference:</b>	True
<b>Well:</b>	RGU 542-26-198	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1 24Jan13 kjs		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude	
0.00	0.00	0.00	0.00	0.00	0.00	1,778,091.50	2,199,607.00	39.93515	-108.35454	
120.00	0.00	0.00	120.00	0.00	0.00	1,778,091.50	2,199,607.00	39.93515	-108.35454	
<b>Start Build 2.00</b>										
226.89	2.14	107.99	226.87	-0.62	1.90	1,778,090.82	2,199,608.88	39.93515	-108.35453	
<b>Hold 2.14 Inclination</b>										
500.00	2.14	107.99	499.79	-3.76	11.59	1,778,087.37	2,199,618.46	39.93514	-108.35450	
1,000.00	2.14	107.99	999.44	-9.52	29.33	1,778,081.06	2,199,636.01	39.93513	-108.35443	
1,228.72	2.14	107.99	1,228.00	-12.16	37.44	1,778,078.17	2,199,644.04	39.93512	-108.35440	
<b>Green River Fm</b>										
1,408.85	2.14	107.99	1,408.00	-14.24	43.83	1,778,075.89	2,199,650.36	39.93511	-108.35438	
<b>A Groove</b>										
1,500.00	2.14	107.99	1,499.09	-15.29	47.07	1,778,074.74	2,199,653.56	39.93511	-108.35437	
1,613.99	2.14	107.99	1,613.00	-16.60	51.11	1,778,073.30	2,199,657.56	39.93511	-108.35436	
<b>B Groove</b>										
1,899.19	2.14	107.99	1,898.00	-19.89	61.23	1,778,069.70	2,199,667.57	39.93510	-108.35432	
<b>Dissolution Surface</b>										
2,000.00	2.14	107.99	1,998.74	-21.05	64.81	1,778,068.43	2,199,671.11	39.93510	-108.35431	
2,500.00	2.14	107.99	2,498.39	-26.81	82.55	1,778,062.11	2,199,688.66	39.93508	-108.35424	
2,984.94	2.14	107.99	2,983.00	-32.40	99.75	1,778,055.99	2,199,705.68	39.93507	-108.35418	
<b>Garden Gulch</b>										
3,000.00	2.14	107.99	2,998.05	-32.57	100.29	1,778,055.80	2,199,706.21	39.93506	-108.35418	
3,165.07	2.14	107.99	3,163.00	-34.47	106.14	1,778,053.71	2,199,712.01	39.93506	-108.35416	
<b>Orange Marker</b>										
3,380.22	2.14	107.99	3,378.00	-36.95	113.78	1,778,050.99	2,199,719.56	39.93505	-108.35413	
<b>Wasatch</b>										
3,500.00	2.14	107.99	3,497.70	-38.33	118.03	1,778,049.48	2,199,723.76	39.93505	-108.35412	
3,880.57	2.14	107.99	3,878.00	-42.72	131.53	1,778,044.67	2,199,737.12	39.93504	-108.35407	
<b>9 5/8"</b>										
4,000.00	2.14	107.99	3,997.35	-44.09	135.77	1,778,043.16	2,199,741.31	39.93503	-108.35405	
4,500.00	2.14	107.99	4,497.00	-49.85	153.51	1,778,036.85	2,199,758.86	39.93502	-108.35399	
5,000.00	2.14	107.99	4,996.65	-55.61	171.25	1,778,030.53	2,199,776.41	39.93500	-108.35393	
5,500.00	2.14	107.99	5,496.30	-61.38	188.99	1,778,024.22	2,199,793.97	39.93499	-108.35386	
5,676.82	2.14	107.99	5,673.00	-63.41	195.26	1,778,021.98	2,199,800.17	39.93498	-108.35384	
<b>Top of "G" Sand</b>										
6,000.00	2.14	107.99	5,995.96	-67.14	206.73	1,778,017.90	2,199,811.52	39.93497	-108.35380	
6,032.07	2.14	107.99	6,028.00	-67.51	207.87	1,778,017.50	2,199,812.64	39.93497	-108.35380	
<b>Fort Union</b>										
6,500.00	2.14	107.99	6,495.61	-72.90	224.47	1,778,011.59	2,199,829.07	39.93495	-108.35374	
7,000.00	2.14	107.99	6,995.26	-78.66	242.21	1,778,005.27	2,199,846.62	39.93494	-108.35367	
7,428.04	2.14	107.99	7,423.00	-83.59	257.39	1,777,999.86	2,199,861.64	39.93492	-108.35362	
<b>Ohio Creek</b>										
7,460.57	2.14	107.99	7,455.51	-83.97	258.55	1,777,999.45	2,199,862.78	39.93492	-108.35362	
<b>Start Drop -1.50</b>										
7,500.00	1.55	107.99	7,494.92	-84.36	259.75	1,777,999.02	2,199,863.98	39.93492	-108.35361	
7,603.09	0.00	0.00	7,598.00	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361	
<b>Vertical</b>										
7,703.09	0.00	0.00	7,698.00	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361	
<b>Mesaverde - Mesaverde</b>										
8,000.00	0.00	0.00	7,994.91	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361	
8,500.00	0.00	0.00	8,494.91	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361	
9,000.00	0.00	0.00	8,994.91	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361	



**WPX Energy**  
Planning Report - Geographic

<b>Database:</b>	COMPASS-PICEANCE	<b>Local Co-ordinate Reference:</b>	Well RGU 542-26-198 - Slot A7
<b>Company:</b>	PICEANCE HL NAD 83	<b>TVD Reference:</b>	KELLY BUSHING @ 6643.00usft (Cyclone 29 (21' RKB) kjs)
<b>Project:</b>	RG 26-01S-098W	<b>MD Reference:</b>	KELLY BUSHING @ 6643.00usft (Cyclone 29 (21' RKB) kjs)
<b>Site:</b>	RGU 42-26-198	<b>North Reference:</b>	True
<b>Well:</b>	RGU 542-26-198	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1 24Jan13 kjs		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
9,098.09	0.00	0.00	9,093.00	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361
<b>Approx. Top Gas</b>									
9,500.00	0.00	0.00	9,494.91	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361
10,000.00	0.00	0.00	9,994.91	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361
10,500.00	0.00	0.00	10,494.91	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361
10,788.09	0.00	0.00	10,783.00	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361
<b>Cameo Coals</b>									
11,000.00	0.00	0.00	10,994.91	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361
11,348.09	0.00	0.00	11,343.00	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361
<b>Rollins SS</b>									
11,483.09	0.00	0.00	11,478.00	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361
<b>Cozzette</b>									
11,500.00	0.00	0.00	11,494.91	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361
11,703.09	0.00	0.00	11,698.00	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361
<b>Corcoran</b>									
12,000.00	0.00	0.00	11,994.91	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361
12,068.09	0.00	0.00	12,063.00	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361
<b>Upper Sego</b>									
12,323.09	0.00	0.00	12,318.00	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361
<b>Lower Sego</b>									
12,500.00	0.00	0.00	12,494.91	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361
12,573.09	0.00	0.00	12,568.00	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361
<b>TD at 12573.09 - TD</b>									

Design Targets									
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
Mesaverde (25' Radius) - plan hits target center - Circle (radius 25.00)	0.00	0.00	7,698.00	-84.79	261.08	1,777,998.55	2,199,865.28	39.93492	-108.35361

Casing Points					
Measured Depth (usft)	Vertical Depth (usft)	Name	Casing Diameter (in)	Hole Diameter (in)	
3,880.57	3,878.00	9 5/8"	9.625	13.500	



<b>Database:</b>	COMPASS-PICEANCE	<b>Local Co-ordinate Reference:</b>	Well RGU 542-26-198 - Slot A7
<b>Company:</b>	PICEANCE HL NAD 83	<b>TVD Reference:</b>	KELLY BUSHING @ 6643.00usft (Cyclone 29 (21' RKB) kjs)
<b>Project:</b>	RG 26-01S-098W	<b>MD Reference:</b>	KELLY BUSHING @ 6643.00usft (Cyclone 29 (21' RKB) kjs)
<b>Site:</b>	RGU 42-26-198	<b>North Reference:</b>	True
<b>Well:</b>	RGU 542-26-198	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1 24Jan13 kjs		

Formations						
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)	
1,228.72	1,228.00	Green River Fm				
1,408.85	1,408.00	A Groove				
1,613.99	1,613.00	B Groove				
1,899.19	1,898.00	Dissolution Surface				
2,984.94	2,983.00	Garden Gulch				
3,165.07	3,163.00	Orange Marker				
3,380.22	3,378.00	Wasatch				
5,676.82	5,673.00	Top of "G" Sand				
6,032.07	6,028.00	Fort Union				
7,428.04	7,423.00	Ohio Creek				
7,703.09	7,698.00	Mesaverde				
9,098.09	9,093.00	Approx. Top Gas				
10,788.09	10,783.00	Cameo Coals				
11,348.09	11,343.00	Rollins SS				
11,483.09	11,478.00	Cozzette				
11,703.09	11,698.00	Corcoran				
12,068.09	12,063.00	Upper Sego				
12,323.09	12,318.00	Lower Sego				
12,573.09	12,568.00	TD				

Plan Annotations					
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates			
		+N/-S (usft)	+E/-W (usft)	Comment	
120.00	120.00	0.00	0.00	Start Build 2.00	
226.89	226.87	-0.62	1.90	Hold 2.14 Inclination	
7,460.57	7,455.51	-83.97	258.55	Start Drop -1.50	
7,603.09	7,598.00	-84.79	261.08	Vertical	
7,703.09	7,698.00	-84.79	261.08	Mesaverde	
12,573.09	12,568.00	-84.79	261.08	TD at 12573.09	