RADIOSPEC
SPECTRUM ANALYZER
Model SA-4
Serial No. 1
Frequency Range
100 kHz to 1000 MHz
Resolution Bandwidth
3 kHz to 1 MHz
Sweep Time
1 ms to 10 s
Input Impedance
50 Ω
Amplitude Range
+30 dBm to −120 dBm
Frequency Accuracy
±0.01%
Power Requirements
115 V / 230 V, 50 Hz / 60 Hz
Power Consumption
120 W
Weight
18 kg
Dimensions
430 mm × 220 mm × 360 mm
Manufactured by
RADIOSPEC INSTRUMENTS
Cambridge, England
Made in the United Kingdom
Serial No. 1
Calibrated
Certificate No. 1
Date
Signature
Frequency
Amplitude
Sweep
Trigger
Display
Markers
Memory
Interface
Options
Accessories
Manual
Warranty
Service
Repair
Calibration
Certificate



Calibration Report

Database File: ctz noble state schmidt 30-04.db
Dataset Pathname: pass3
Dataset Creation: Tue Mar 05 07:51:40 2013 by Log SCH 120400

Gamma Ray Calibration Report

Type / Serial: Probe27Sdg / 105311

Well Mon, 04 06 11:02 2011

SHOP CALIBRATION

	Counts/Sec	Gain	Offset	Jig	Units
Background	0.0				cps
Calibrator	1.0				cps
		0.7000			GAPI/cps

PRIMARY VERIFICATION

Background	0.0		cps
Calibrator	0.0		cps
Difference		0.0	GAPI

BEFORE SURVEY VERIFICATION

Background	0.0		cps
Calibrator	0.0		cps
Difference		0.0	GAPI

AFTER SURVEY VERIFICATION

Background	0.0		cps
Calibrator	0.0		cps
Difference		0.0	GAPI

Cement Bond Log Calibration Report

Serial Number:	110603		
Tool Model:	Probe27SDgMel		
Performed:	Tue Mar 05 07:40:54 2013		
Depth:	420.500	ft	
Casing Diameter:	4.5	in	

	3' Spacing	5' Spacing	
Signal Zero:	1.0	0	mV
Calibrated Amplitude:	81.1061	81.1061	mV
Reading at Signal Zero:	-0.00581055	-0.00578613	V
Reading in Free Pipe:	1.01782	1.20328	V
Gain:	52.3066	69.9809	
Offset:	1.80393	0.370202	