

Company: Chevron U.S.A. Inc.
Well: Lisa Unit 1
Field: Wildcat
County: Rio Arriba
State: New Mexico
Location: 1,850' FSL & 1,850' FWL
Sec 12 T 25 N R 3 W
Elevation: 7,000' GL
Date: 10-Jan-2008
Run No: ONE
Depth Driller: 8,000'
Depth Logger: 8,000'
Bottom Log Interval: 8,000'
Top Log Interval: 7,000'
Casing Driller: 9 5/8" @ 2,000'
Casing Logger: 2,000'
Bit Size: 8 3/4"
Type Fluid in Hole: Water Based Mud
Density: 9.2 ppg
Viscosity: 45 sec/qt
Fluid Loss: 6.0 cc
Source of Sample: Flowline
R @ Meas. Temp: 0.18 @ 120°F
R @ Meas. Temp: 0.12 @ 120°F
R @ Meas. Temp: 0.25 @ 120°F
Time Since Circ: 6 hrs
Max Rec. Temp: 120°F
Equip. Location: Farmington, NM
Recorded By: J. Smith
Witnessed By: T. Brown

Gamma Ray
Resistivity
Density
Neutron
Caliper

Chevron

CBU 8 MEASURED TO BE 1.00 FEET LEFT OF
WELL BORE AT 8,000 FEET

Chevron

CBU 8 MEASURED TO BE 1.00 FEET LEFT OF
WELL BORE AT 8,000 FEET

Company: Chevron U.S.A. Inc.
Well: Lisa Unit 1
Field: Wildcat
County: Rio Arriba
State: New Mexico
Location: 1,850' FSL & 1,850' FWL
Sec 12 T 25 N R 3 W
Elevation: 7,000' GL
Date: 10-Jan-2008
Run No: ONE
Depth Driller: 8,000'
Depth Logger: 8,000'
Bottom Log Interval: 8,000'
Top Log Interval: 7,000'
Casing Driller: 9 5/8" @ 2,000'
Casing Logger: 2,000'
Bit Size: 8 3/4"
Type Fluid in Hole: Water Based Mud
Density: 9.2 ppg
Viscosity: 45 sec/qt
Fluid Loss: 6.0 cc
Source of Sample: Flowline
R @ Meas. Temp: 0.18 @ 120°F
R @ Meas. Temp: 0.12 @ 120°F
R @ Meas. Temp: 0.25 @ 120°F
Time Since Circ: 6 hrs
Max Rec. Temp: 120°F
Equip. Location: Farmington, NM
Recorded By: J. Smith
Witnessed By: T. Brown

Gamma Ray (GR) 0 API 150
Resistivity (RT) 0.2 Ω·m 2000
Density (RHOB) 1.95 g/cm³ 2.95
Neutron (NPHI) 45 % -15
Caliper (CALI) 6 in 16



Calibration Report

Database File: cbl anadarko gregg 1.db
Dataset Pathname: pass3
Dataset Creation: Wed Apr 10 09:22:15 2013 by Log SCH 120430

Gamma Ray Calibration Report

Type / Serial: Probe275dig / 101010

SHOP CALIBRATION — Wed Feb 27 07:52:48 2013

	Counts/Sec.	Gain	Offset	Jig	Units
Background	0.0				cps
Calibrator	1.0				cps
		0.6500			GAPI/cps

PRIMARY VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference				0.0	GAPI

BEFORE SURVEY VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference				0.0	GAPI

AFTER SURVEY VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference				0.0	GAPI

Cement Bond Log Calibration Report

Serial Number:	110802		
Tool Model:	Probe27SDigital		
Performed:	Wed Apr 10 09:13:23 2013		
Depth:	2840.38	ft	
Casing Diameter:	4.5	in	
	3' Spacing	5' Spacing	
Signal Zero:	0.9	0	mV
Calibrated Amplitude:	81.1961	81.1961	mV
Reading at Signal Zero:	0.013023	0.013254	V
Reading in Free Pipe:	2.40896	2.30596	V
Gain:	32.5475	35.4192	
Offset:	0.456603	-0.479059	