

FORM  
5A

Rev  
06/12

State of Colorado  
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

400428749

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 100322  
2. Name of Operator: NOBLE ENERGY INC  
3. Address: 1625 BROADWAY STE 2200  
City: DENVER State: CO Zip: 80202  
4. Contact Name: Eileen Roberts  
Phone: (303) 2284330  
Fax: (303) 2284286

5. API Number 05-123-34418-00  
6. County: WELD  
7. Well Name: CASTOR FEDERAL LG  
Well Number: 17-62HN  
8. Location: QtrQtr: SWSW Section: 17 Township: 8N Range: 59W Meridian: 6  
9. Field Name: WATTENBERG Field Code: 90750

Completed Interval

FORMATION: NIOBRARA Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 01/28/2013 End Date: 01/28/2013 Date of First Production this formation: 02/14/2013

Perforations Top: 6616 Bottom: 10277 No. Holes: 0 Hole size:

Provide a brief summary of the formation treatment: Open Hole: ☐

Frac'd the Niobrara w/ 2308448 gals of Silverstim and Slick Water with 3534191#'s of Ottawa sand.

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): 54963 Max pressure during treatment (psi): 3845

Total gas used in treatment (mcf): 0 Fluid density at initial fracture (lbs/gal): 8.43

Type of gas used in treatment: Min frac gradient (psi/ft): 0.83

Total acid used in treatment (bbl): 0 Number of staged intervals: 22

Recycled water used in treatment (bbl): 3844 Flowback volume recovered (bbl): 9148

Fresh water used in treatment (bbl): 51118 Disposition method for flowback: RECYCLE

Total proppant used (lbs): 84147 Rule 805 green completion techniques were utilized: ☐

Reason why green completion not utilized: PIPELINE

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 02/17/2013 Hours: 24 Bbl oil: 133 Mcf Gas: 287 Bbl H2O: 577

Calculated 24 hour rate: Bbl oil: 133 Mcf Gas: 287 Bbl H2O: 577 GOR: 2157

Test Method: FLOWING Casing PSI: 1000 Tubing PSI: 525 Choke Size: 024/64

Gas Disposition: FLARED Gas Type: WET Btu Gas: 0 API Gravity Oil: 37

Tubing Size: 2 + 7/8 Tubing Setting Depth: 6388 Tbg setting date: 02/05/2013 Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

Comment:

--

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Eileen Roberts \_\_\_\_\_

Title: Regulatory Specialist Date: \_\_\_\_\_ Email: eroberts@nobleenergyinc.com  
:

### **Attachment Check List**

Att Doc Num	Name

Total Attach: 0 Files

### **General Comments**

<b><u>User Group</u></b>	<b><u>Comment</u></b>	<b><u>Comment Date</u></b>

Total: 0 comment(s)