All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or wilful negligence on our part, be liable or responsible for any loss, cost, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set forth in our current Price Schedule.

COMMENTS

RAN C.B.L. TO VERIFY CEMENT.
NOT CORROLATED.

THANK YOU FOR USING WARRIOR ENERGY SERVICES!!!!

Service	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
			GTO-Standard (STNDRD) Nutated Open Hole	0.83	1.44	1.00
			Probe	3.00	2.75	40.00
HCAOVOLT	16.20					
InTemp	14.83					
			RSO Probe (Base) Probe Rack Build That with Digital Telemetry	8.92	2.75	90.00
WVFSFT	11.58					
WVFS1	11.58					
WVFS1	11.58					
WVFS2	11.58					
WVFS3	11.58					
WVFS4	11.58					
WVFS5	11.58					
WVFS6	11.58					
WVFSFT	11.58					
WVFSB	11.58					
WVFSFT	10.58					
			Probe	3.00	2.75	40.00
CCL	3.64					
			GR-Probe (ITTI) Probe TTI	4.33	2.75	30.00
GR	0.90					

Dataset: bella federal 36-7 db: file2/swtool1/cpass3
Total Length: 20.04 ft
Total Weight: 251.00 lb
O.D: 2.75 in

Database File: bella federal 36-7 db
Dataset Pathname: pass3
Presentation Format: dfaxis
Dataset Creation: Fri Jul 26 08:26:28 2013 by Log 7.0 B1
Charted by: Depth in Feet scaled 1:240

200 TT (usec) 800 0 CCL 1.5 0 AMP (mV) 100 200 VDL 1000
0 GR (GAPI) 200 0 AMPX (mV) 20 InTemp
200 GR (GAPI) 400 (degF)



200 TT (usec) 800 0 CCL 1.5 0 AMP (mV) 100 200 VDL 1000
0 GR (GAPI) 200 0 AMPX (mV) 20 InTemp
200 GR (GAPI) 400 (degF)