

Well

Operator

Location

County

State

Field

Footages

Top of Prod Zone:

Bottom Hole:

OLIVE 13-26

EnCana Oil & Gas (USA) Inc.

NESW SEC. 26-T2N-R66W

Weld

Colorado

Wattenberg

2079' FSL & 2030' FWL

2054' FSL & 665' FWL

2050' FSL & 660' FWL

Spud Date:

03-23-2007

TD Date:

03-28-2007

Log Tops

Sussex

4958'

Niobrara

7448'

Codell

7746'

J Sand

8202'

Surface Casing and Cement

8 5/8", 24#, landed @ 1130', cemented with 540 sxs

Main Hole

7-7/8" to TD

Production Casing and Cement

4-1/2", 11.6#, landed @ 8330', cemented with 290 sxs

TOC @ 6,530'

Perf'd the Niobrara from 7516' - 7536' @ 2 spf

Frac'd the Niobrara with 115,940 gal frac fluid and 250,080# 30/50 sand. 04-08-07

Refrac Niobrara w/89,191 gal frac fluid and 251,080 # sand. 5-28-13

Perf'd the Codell from 7746' - 7764' @ 4 spf

Frac'd the Codell with 114,330 gal frac fluid and 250,080# sand. 04-08-07

Refrac Codell w/ 82,084 gal frac fluid and 250,080 # sand. 5-28-13

Perf'd the J Sand from 8202' – 8210', 8216' - 8228' @ 2 spf

Frac'd the J Sand with 151,620 gal frac fluid and 252,660# sand. 04-08-07

CIBP

Set @ 7830 on 5/20/13

Drilled out 6/1/2013

Production Tubing

2-3/8", Set @ 8169' (6/1/13)

8330'

—

PBTD

8349'

—

Driller's TD

