



STATE OF
COLORADO

Andrews - DNR, Doug <doug.andrews@state.co.us>

Form 2A review for Whiting O&G's Razor 26L Pad location - Doc #400462934

2 messages

Andrews - DNR, Doug <doug.andrews@state.co.us>

Fri, Aug 30, 2013 at 10:17 AM

To: ld_brown@bresnan.net

Larry,

I have reviewed the referenced Form 2A Oil & Gas Location Assessment and have the following comment.

In the Facilities section, per Rule 303.b.(3)C, a description of all oil, gas, and/or water pipelines is required. You have listed no production facilities at this oil and gas location and have indicated in the Operator Comments section that a separate centralized production facility will be utilized for this well, please provide me with information concerning the pipeline(s) that will go from the well pad to the centralized production facility and I will add it to the Form 2A.

Please feel free to contact me if you have any questions. Thank you.

—

Doug Andrews

Oil & Gas Location Assessment Specialist - Northeast Area
Colorado Oil & Gas Conservation Commission
1120 Lincoln St., Suite 801
Denver, CO 80203

doug.andrews@state.co.us
303-894-2100 Ext. 5180

Larry Brown <ld_brown@bresnan.net>

Wed, Sep 4, 2013 at 9:55 AM

To: "Andrews - DNR, Doug" <doug.andrews@state.co.us>

PIPELINE CONSTRUCTION:

- a) A track hoe and wheel trencher will be used to construct the pipeline right-of-way. The construction right-of-way will be 50 feet wide with a 25 feet wide permanent right-of-way. The approximate length of pipeline to be constructed is 200 feet.
- b) All displaced materials shall be placed back into the cleared route once construction is completed.
- c) Pipeline construction will not block or change the natural course of any drainage. The pipeline will be buried wherever possible. The pipeline will be buried a minimum of 30" below the surface at all locations.
- d) Pipeline trenches shall be maintained in order to correct settlement and erosion.
- e) The pipelines will be a 8" production and 6" test. All lines will be welded steel.
- f) If snow is present on the ground at the outset of construction activities, the snow will be removed before the soil is disturbed and piled downhill from the stockpile location.
- g) All equipment and vehicles will be confined to the existing roads, well locations and pipeline corridor.
- h) The disturbed areas outside of the roadbed and road ditches will be revegetated as described for the location in the Surface Reclamation Plans below.

[Quoted text hidden]



Razor 26 Exhibit B.pdf

2299K