
Schlumberger
Platform Express
Three Detector Lithology Density
Compensated Neutron
Array Induction Imager Tool
Gamma Ray
Caliper
Bit Size
Density Correction
Neutron Porosity
Photoelectric Factor
Deep Resistivity
Medium Resistivity
Shallow Resistivity
Spherically Focused Resistivity
Delta Rho
Rt/Rxo
Mud Type
Mud Density
Mud Resistivity
Mud Filtrate Resistivity
Mud Cake Resistivity
Source of Sample
Rm @ Measured Temperature
Rmf @ Measured Temperature
Rmc @ Measured Temperature
Maximum Recorded Temperature
Circulation Stopped Time
Logger on Bottom Time
Unit Number
Witnessed By
Run Number
Service Order
Location
Field
Well
Company
Schlumberger
Alaska Production
Services
Other Services
Permanent Datum
Elevation
Log Measured From
Drilling Measured From
Elevation
Kelly Bushing
Derrick Floor
Ground Level
API Serial No.
Section
Township
Range




PEAK WIRELINE SERVICES, INC.

# REPEAT SECTION

Database File: kerry.db
Dataset Pathname: 6/run1/pass1
Presentation Format: scbl02
Dataset Creation: Fri Apr 19 09:28:40 2013 by Log Std Casedhole 10071
Charted by: Depth in Feet scaled 1:240




## Calibration Report

Database File: kerry.db
Dataset Pathname: 6/run1/pass2
Dataset Creation: Fri Apr 19 09:35:55 2013 by Log Std Casedhole 10071

### Gamma Ray Calibration Report

Serial Number: 061120GR
Tool Model: PROBE
Performed: Thu Apr 18 07:11:02 2013

Calibrator Value: 1.0 GAPI

Background Reading: 0.0 cps
Calibrator Reading: 85.8 cps

Sensitivity: 1.2000 GAPI/cps

### Segmented Cement Bond Log Calibration Report

Serial Number: 4.5040904
Tool Model: Probe

Calibration Casing Diameter: 5.500 in
Calibration Depth: 4721.550 ft

Master Calibration, performed Fri Apr 19 09:42:37 2013.

| | Raw (v) | | Calibrated (mv) | | Results | |
|---|---|---|---|---|---|---|
| | Zero | Cal | Zero | Cal | Gain | Offset |
| 3' | 0.013 | 1.626 | 0.100 | 71.921 | 44.515 | -0.481 |
| CAL | 1.996 | 1.959 | | | | |
| 5' | 0.017 | 1.611 | 0.250 | 71.921 | 44.947 | -0.495 |
| SUM | | | | | | |
| S1 | 0.010 | 1.629 | 0.000 | 100.000 | 61.760 | -0.615 |
| S2 | 0.012 | 1.646 | 0.000 | 100.000 | 61.166 | -0.707 |
| S3 | 0.011 | 1.670 | 0.000 | 100.000 | 60.266 | -0.664 |
| S4 | 0.011 | 1.681 | 0.000 | 100.000 | 59.881 | -0.657 |
| S5 | 0.013 | 1.629 | 0.000 | 100.000 | 61.876 | -0.804 |
| S6 | 0.017 | 1.558 | 0.000 | 100.000 | 64.862 | -1.082 |
| S7 | 0.016 | 1.537 | 0.000 | 100.000 | 65.753 | -1.063 |
| S8 | 0.016 | 1.579 | 0.000 | 100.000 | 63.970 | -1.028 |

Internal Reference Calibration, performed Wed Dec 31 17:00:00 1969.

| | Raw (v) | | Calibrated (v) | | Results | |
|---|---|---|---|---|---|---|
| | Zero | Cal | Zero | Cal | Gain | Offset |
| CAL | 0.000 | 0.000 | 1.996 | 1.959 | 1.000 | 0.000 |

Air Zero Calibration, performed Fri Apr 19 09:02:38 2013:

| | Raw (v) | Calibrated (v) | Results |
|---|---|---|---|
| | Zero | Zero | Offset |
| 3' | 0.000 | 0.000 | 0.000 |
| 5' | 0.000 | 0.000 | 0.000 |
| SUM | | | |
| S1 | 0.000 | 0.000 | 0.000 |
| S2 | 0.000 | 0.000 | 0.000 |
| S3 | 0.000 | 0.000 | 0.000 |
| S4 | 0.000 | 0.000 | 0.000 |
| S5 | 0.000 | 0.000 | 0.000 |
| S6 | 0.000 | 0.000 | 0.000 |
| S7 | 0.000 | 0.000 | 0.000 |
| S8 | 0.000 | 0.000 | 0.000 |