
Well Name: 15/9-19 A
Field: Sleipner
Block: 15/9
Country: Norway
Drilling Contractor: Transocean Leader
Rig Name: Transocean Leader
Rig Type: Semi-Submersible
Rig Floor Elevation: 25.00 m
Water Depth: 82.00 m
Total Depth: 4,000.00 m
Spud Date: 15-Jun-2008
Completion Date: 15-Jul-2008
Operator: Statoil
Well Type: Exploration
Well Status: Abandoned
Primary Objective: Utsira Formation
Secondary Objective: Hugin Formation
Tertiary Objective: Skagerrak Formation
Hole Size: 36 in
Hole Size: 17 1/2 in
Hole Size: 12 1/4 in
Hole Size: 8 1/2 in
Casing: 30 in @ 120 m
Casing: 13 3/8 in @ 1,200 m
Casing: 9 5/8 in @ 3,500 m
Mud Type: Seawater / Bentonite
Mud Type: KCl / Polymer
Mud Type: Oil-based
Mud Weight: 1.03 SG
Mud Weight: 1.20 SG
Mud Weight: 1.45 SG
Logging Company: Schlumberger
Logging Company: Halliburton
Logging Company: Baker Hughes
Logging Company: Weatherford
Logging Company: Geoservices
Logging Company: Mudlogging Inc.
Logging Company: Sperry Sun
Logging Company: Anadrill
Logging Company: Gyrodata
Logging Company: Reeves Wireline
Logging Company: Expro
Logging Company: Wireline Specialists
Logging Company: Tuboscope



Ch1	10.0	1.00	Volts/Div
Ch2	10.0	1.00	Volts/Div
Ch3	10.0	1.00	Volts/Div
Ch4	10.0	1.00	Volts/Div

Sample Rate: 1.00 kS/s
Timebase: 1.00 s/Div
Mode: Normal
Finished Block Capture, Single
Capture Length: 10.0 s (10,000 Samples)
Measurements: All Channels

Ch1	10.0	1.00	Volts/Div
Ch2	10.0	1.00	Volts/Div
Ch3	10.0	1.00	Volts/Div
Ch4	10.0	1.00	Volts/Div



7400
7450
7500
7550
7600
7650
Line Tension
Gamma Ray
Amplified Amplitude
Collar Locator
Amplitude
Variable Density
9 Collar Locator -1
0 Gamma Ray (GAPI) 200
LTEN
0 (lb) 2000
0 Amplified Amplitude (mV) 30
0 Amplitude (mV) 100
200 Variable Density 1200