

Company: ENCANA OIL & GAS (USA) INC

Well: SGU 8512D-24 (L24 496)

Field: STORY GULCH

County: GARFIELD State: COLORADO

SLIM CEMENT MAPPING LOG
GAMMA RAY - CCL - TEMPERATUR
CBL - VDL

County: GARFIELD

Field: STORY GULCH

Location: SHL: 1596' FSL & 882' FWL

Well: SGU 8512D-24 (L24 496)

Company: ENCANA OIL & GAS (USA) INC

LOCATION	
SHL: 1596' FSL & 882' FWL BHL: 1806' FSL & 669' FWL	Elev.: K.B. 8210.00 ft G.L. 8180.00 ft D.F. 8109.00 ft
Permanent Datum: _____	GROUND LEVEL _____ Elev.: 8180.00 ft _____
Log Measured From: _____	KELLY BUSHING _____ 30.00 ft above Perm. Datum
Drilling Measured From: _____	KELLY BUSHING _____
API Serial No. 05-045-21171-0000	Section 24 Township 4S Range 96W

Logging Date	18-Mar-2013								
Run Number	1								
Depth Driller	12470 ft								
Schlumberger Depth	12327 ft								
Bottom Log Interval	12319 ft								
Top Log Interval	75 ft								
Casing Fluid Type	FRESH WATER								
Salinity									
Density	8.4 lbm/gal								
Fluid Level	75 ft								
BIT/CASING/TUBING STRING									
Bit Size	7.875 in								
From	10108 ft								
To	12470 ft								
Casing/Tubing Size	4.500 in								
Weight	13.5 lbm/ft								
Grade									
From	30 ft								
To	12445 ft								
Maximum Recorded Temperatures	288 degF								
Logger On Bottom	18-Mar-2013			15:15					
Unit Number	391	GRAND JUNCTION							
Recorded By	JASON BARRY								
Witnessed By	JOHN MILLER								

PVT DATA		Run 1	Run 2	Run
Oil Density				
Water Salinity				
Gas Gravity				
Bo				
Bw				
1/Bg				
Bubble Point Pressure				
Bubble Point Temperature				
Solution GOR				
Maximum Deviation				
CEMENTING DATA				
Primary/Squeeze		Primary		
Casing String No				
Lead Cement Type				
Volume				
Density				
Water Loss				
Additives				
Tail Cement Type				
Volume				
Density				
Water Loss				
Additives				
Expected Cement Top				
Logging Date				
Run Number				
Depth Driller				
Schlumberger Depth				
Bottom Log Interval				
Top Log Interval				
Casing Fluid Type				
Salinity				
Density				
Fluid Level				
BIT/CASING/TUBING STRING				
Bit Size				
From				
To				
Casing/Tubing Size				
Weight				
Grade				
From				
To				
Maximum Recorded Temperatures				
Logger On Bottom				
Unit Number				
Recorded By				
Witnessed By				

DEPTH SUMMARY LISTING

Date Created: 14-MAR-2013 10:41:08

Depth System Equipment

Depth Measuring Device		Tension Device		Logging Cable	
Type:	IDW-B	Type:	CMTD-B/A	Type:	1-25ZT
Serial Number:	6214	Serial Number:	3421	Serial Number:	112136
Calibration Date:	24-APR-2012	Calibration Date:	20-FEB-2011	Length:	19500 FT
Calibrator Serial Number:		Calibrator Serial Number:	174878	Conveyance Method:	Wireline
Calibration Cable Type:	1-25ZT	Number of Calibration Points:	10	Rig Type:	LAND
Wheel Correction 1:	-3	Calibration RMS:	4		
Wheel Correction 2:	-4	Calibration Peak Error:	8		

Depth Control Parameters

Log Sequence:	First Log In the Well
Rig Up Length At Surface:	0.00 FT
Rig Up Length At Bottom:	0.00 FT
Rig Up Length Correction:	0.00 FT
Stretch Correction:	
Tool Zero Check At Surface:	

Depth Control Remarks


1. ALL SCHLUMBERGER DEPTH CONTROL POLICIES APPLIED
2. IDW USED AS PRIMARY DEPTH REFERENCE
3. SWPT DRUM COUNTER USED AS SECONDARY DEPTH REFERENCE
- 4.
- 5.
- 6.

DISCLAIMER

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

OTHER SERVICES1	OTHER SERVICES2
OS1: RESERVOIR SATURATION	OS1:
OS2: LOG	OS2:
OS3: SIGMA MODE	OS3:
OS4: GAMMA RAY - CCL	OS4:
OS5:	OS5:
REMARKS: RUN NUMBER 1	REMARKS: RUN NUMBER 2
FIRST RUN IN HOLE	
TOOL RAN AS PER TOOL SKETCH	
MAX RECORDED TEMPERATURE: 288 DEGF	
MAX RECORDED PRESSURE: 5199 PSI	
SHORT JOINTS: 10871 FT & 7684 FT	

ENTRANCE TIME: 14:30					
TIME ON BOTTOM: 15:15					
EXIT TIME: 18:45					
MAIN PASS LOGGED UNDER ZERO SURFACE PRESSURE					
EXPECTED CBL AMP IN FREE PIPE = 0 MV					
CREW: J BARRY, B CUPP, J MANN, W AZIZ, K JOHNS					
THANK YOU FOR CHOOSING E&P WIRELINE, A SCHLUMBERGER COMPANY					
RUN 1			RUN 2		
SERVICE ORDER #: C920-00054			SERVICE ORDER #:		
PROGRAM VERSION: 19C0-187			PROGRAM VERSION:		
FLUID LEVEL: 75 ft			FLUID LEVEL:		
LOGGED INTERVAL	START	STOP	LOGGED INTERVAL	START	STOP
EQUIPMENT DESCRIPTION					
RUN 1			RUN 2		
SURFACE EQUIPMENT					
WITM-A PSC_16MHZ					
DOWNHOLE EQUIPMENT					
MH-22 MH-22		33.2			
Detail MT TelStatus CTEM					
AH-38		31.6			
HBMS-B		31.3			
PSC-A 2880					
HUDH-A 2880					
HSTC-A					
HBMC-A					
GR					
CCL					
HBMC					
HTPS-A 2880					
HCQG_E_Mano	GR	26.4			
RTD_Thermometer					
	CCL	24.0			
	HSTC Aux.				
	HBMC Aux.	22.5			
	CQG Manom				
	Well_Temp	21.1			
SCMT-CB		20.2			
SCMC-CA 8120					
SECH-CA					
CMIR-AG					
SCMS-CB 8179					
SCMX-CA					



MAIN PASS CBL VDL


MAXIS Field Log


Company: ENCANA OIL & GAS (USA) INC Well: SGU 8512D-24 (L24 496)


Input DLIS Files						
DEFAULT	SCMT_HBMS_011LUP	FN:10	PRODUCER	18-Mar-2013 15:17	12342.5 FT	51.5 FT
Output DLIS Files						
DEFAULT	SCMT_HBMS_015PUP	FN:14	PRODUCER	18-Mar-2013 18:54	12342.5 FT	20.0 FT


OP System Version: 19C0-187			
SCMT-CB	SRPC-5214-H2-2012-OP1	HBMS-B	SRPC-5214-H2-2012-OP1


PIP SUMMARY

















































































































































































First Reading GR 12301 FT

Total Depth 12327 FT

First Reading CBL 12319 FT

Gamma Ray (GR)	Tension (TENS)	CBL Amplitude (CBL)	Min	Amplitude	Max
(GAPI)	(LBF)	(MV)			
0	0	0			
150	2000	100			
				VDL VariableDensity (VDL)	
			200	(US)	1200
Transit Time (TT)	Discriminat	CBL Amplitude (CBL)			
(US)	ed CCL	(MV)			
260	(CCLD)	0			
160	3 (V) -1	10			

PIP SUMMARY	
-------------	--

 Time Mark Every 60 S

Format: CBL_VDL Vertical Scale: 5" per 100' Graphics File Created: 18-Mar-2013 18:54

OP System Version: 19C0-187

SCMT-CB	SRPC-5214-H2-2012-OP15	HBMS-B	SRPC-5214-H2-2012-OP15
---------	------------------------	--------	------------------------

<<<SCMT Cement Evaluation Information Summary>>>

Sonde Serial Number	SCMS-CB 8179		
Current Casing Size	4.50000 IN		
Casing Weight	13.5000 LB/F		
Expected CBL Amplitude in Free Pipe Section	81 MV	Minimum Sonic Amplitude	1.28673 MV (100% Cement)
			2.94636 MV (80% Cement)
		MAP Minimum Sonic Amplitude	7.12449 MV (100% Cement)
			12.0838 MV (80% Cement)
Master Calibration (Normalization)		Before Calibration (Adjustment)	
Date of Master Calibration	6-MAR-2012		
CBL Correction Factor	0.0704263	CBL Adjustment Factor (CBAF)	0.800000
MAP 1 Correction Factor	0.0993191	MAP Adjustment Factor (MPAF)	1.0
MAP 2 Correction Factor	0.0941329		
MAP 3 Correction Factor	0.101552		
MAP 4 Correction Factor	0.114415		
MAP 5 Correction Factor	0.127992		
MAP 6 Correction Factor	0.121190		
MAP 7 Correction Factor	0.112867		
MAP 8 Correction Factor	0.102913		

Parameters	
------------	--

DLIS Name	Description	Value	
SCMT-CB: Slim Cement Mapping Tool, 1-11/16 OD			
BILI	Bond Index Level for Zone Isolation	0.8	
CB3D	SCMT CBL 3 ft Peak Detection Mode	PEAK	
CB3G	SCMT CBL 3 ft Peak Detection T0_Delay and Noise Gate	223.206	US
CB3T	SCMT CBL 3 ft Fixed Threshold Level	20	MV
CB5D	SCMT CBL 5 ft Peak Detection Mode	PEAK	
CB5G	SCMT CBL 5 ft Peak Detection T0_Delay and Noise Gate	337.206	US
CB5T	SCMT CBL 5 ft Fixed Threshold Level	20	MV
CBLG	CBL Gate Width	40	US
CBRA	CBL LQC Reference Amplitude in Free Pipe	81	MV
CMCF	CBL Cement Type Compensation Factor	1	
CMTc	SCMT Slow Channel Multiplexer Mode	SCAN	
CMTM	SCMT Operating Mode	LOG	
CSCS	SCMT Slow Channel Index	VCC	
CTHI	Casing Thickness	0.300677	IN
DTF	Delta-T Fluid	189	US/F
FATT	Acoustic Attenuation due to Fluid	0	DB/F
FCF	CBL Fluid Compensation Factor	0.924277	
GOBO	Good Bond	2.94636	MV
MAPD	SCMT MAP Peak Detection Mode	PEAK	
MAPG	SCMT MAP Peak Detection T0_Delay and Noise Gate	166.206	US
MAPT	SCMT MAP Fixed Threshold Level	30	MV
MATT	Maximum Attenuation	11.0005	DB/F

MAT	Maximum Attenuation	14.0905	DB/F
MCCF	MAP Cement Type Compensation Factor	1	
MCI	Minimum Cemented Interval for Isolation	1.25	FT
MMSA	MAP Minimum Sonic Amplitude	7.12449	MV
MSA	Minimum Sonic Amplitude	1.28673	MV
PEDE	Peak Detection On/Off Switch in Playback	OFF	
VDLG	VDL Manual Gain	5	
ZCMT	Acoustic Impedance of Cement	6.8	MRAY
System and Miscellaneous			
CSIZ	Current Casing Size	4.500	IN
CWEI	Casing Weight	13.50	LB/F
DFD	Drilling Fluid Density	8.40	LB/G
DO	Depth Offset for Playback	0.0	FT
PP	Playback Processing	RECOMPUTE	
TD	Total Depth	12327	FT

Input DLIS Files

DEFAULT	SCMT_HBMS_011LUP	FN:10	PRODUCER	18-Mar-2013 15:17	12342.5 FT	51.5 FT
---------	------------------	-------	----------	-------------------	------------	---------

Output DLIS Files

DEFAULT	SCMT_HBMS_015PUP	FN:14	PRODUCER	18-Mar-2013 18:54
---------	------------------	-------	----------	-------------------

Schlumberger

REPEAT ANALYSIS CBL VDL

MAXIS Field Log

Company: ENCANA OIL & GAS (USA) INC	Well: SGU 8512D-24 (L24 496)
-------------------------------------	------------------------------

Input DLIS Files

DEFAULT	SCMT_HBMS_010LUP	FN:9	PRODUCER	18-Mar-2013 14:56	7817.0 FT	7508.5 FT
DEFAULT	SCMT_HBMS_015PUP	FN:14	PRODUCER	18-Mar-2013 18:54	12342.5 FT	20.0 FT

Output DLIS Files


DEFAULT	SCMT_HBMS_016PUP	FN:15	PRODUCER	18-Mar-2013 19:06	7816.0 FT	7476.0 FT
---------	------------------	-------	----------	-------------------	-----------	-----------


OP System Version: 19C0-187



SCMT-CB	SRPC-5214-H2-2012-OP1:	HBMS-B	SRPC-5214-H2-2012-OP1:
---------	------------------------	--------	------------------------

PIP SUMMARY

Time Mark Every 60 S







PIP SUMMARY

Time Mark Every 60 S

Format: CBL_VDL_REP Vertical Scale: 5" per 100'

Graphics File Created: 18-Mar-2013 19:06

OP System Version: 19C0-187

SCMT-CB SRPC-5214-H2-2012-OP1 HBMS-B SRPC-5214-H2-2012-OP1

<<<SCMT Cement Evaluation Information Summary>>>

Sonde Serial Number SCMS-CB 8179

Current Casing Size 4.50000 IN

Casing Weight 13.5000 LB/F

Expected CBL Amplitude
in Free Pipe Section 81 MV

Minimum Sonic Amplitude 1.28673 MV (100% Cement)
2.94636 MV (80% Cement)
MAP Minimum Sonic Amplitude 7.12449 MV (100% Cement)
12.0838 MV (80% Cement)

Master Calibration (Normalization)

Before Calibration (Adjustment)

CBL Correction Factor	0.0704263	CBL Adjustment Factor (CBAF)	0.800000
MAP 1 Correction Factor	0.0993191	MAP Adjustment Factor (MPAF)	1.0
MAP 2 Correction Factor	0.0941329		
MAP 3 Correction Factor	0.101552		
MAP 4 Correction Factor	0.114415		
MAP 5 Correction Factor	0.127992		
MAP 6 Correction Factor	0.121190		
MAP 7 Correction Factor	0.112867		
MAP 8 Correction Factor	0.102913		

Parameters

DLIS Name	Description	Value	
SCMT-CB: Slim Cement Mapping Tool, 1-11/16 OD			
BILI	Bond Index Level for Zone Isolation	0.8	
CB3D	SCMT CBL 3 ft Peak Detection Mode	PEAK	
CB3G	SCMT CBL 3 ft Peak Detection T0_Delay and Noise Gate	223.206	US
CB3T	SCMT CBL 3 ft Fixed Threshold Level	20	MV
CB5D	SCMT CBL 5 ft Peak Detection Mode	PEAK	
CB5G	SCMT CBL 5 ft Peak Detection T0_Delay and Noise Gate	337.206	US
CB5T	SCMT CBL 5 ft Fixed Threshold Level	20	MV
CBLG	CBL Gate Width	40	US
CBRA	CBL LQC Reference Amplitude in Free Pipe	81	MV
CMCF	CBL Cement Type Compensation Factor	1	
CMTC	SCMT Slow Channel Multiplexer Mode	SCAN	
CMTM	SCMT Operating Mode	LOG	
CSCS	SCMT Slow Channel Index	VCC	
CTHI	Casing Thickness	0.300677	IN
DTF	Delta-T Fluid	189	US/F
FATT	Acoustic Attenuation due to Fluid	0	DB/F
FCF	CBL Fluid Compensation Factor	0.924277	
GOBO	Good Bond	2.94636	MV
MAPD	SCMT MAP Peak Detection Mode	PEAK	
MAPG	SCMT MAP Peak Detection T0_Delay and Noise Gate	166.206	US
MAPT	SCMT MAP Fixed Threshold Level	30	MV
MATT	Maximum Attenuation	14.0905	DB/F
MCCF	MAP Cement Type Compensation Factor	1	
MCI	Minimum Cemented Interval for Isolation	1.25	FT
MMSA	MAP Minimum Sonic Amplitude	7.12449	MV
MSA	Minimum Sonic Amplitude	1.28673	MV
PEDE	Peak Detection On/Off Switch in Playback	OFF	
VDLG	VDL Manual Gain	5	
ZCMT	Acoustic Impedance of Cement	6.8	MRAY
System and Miscellaneous			
CSIZ	Current Casing Size	4.500	IN
CWEI	Casing Weight	13.50	LB/F
DFD	Drilling Fluid Density	8.40	LB/G
DO	Depth Offset for Playback	-1.0	FT
DORL	Depth Offset for Repeat Analysis	0.0	FT
PP	Playback Processing	RECOMPUTE	
TD	Total Depth	12327	FT


Input DLIS Files

DEFAULT	SCMT_HBMS_010LUP	FN:9	PRODUCER	18-Mar-2013 14:56	7817.0 FT	7508.5 FT
DEFAULT	SCMT_HBMS_015PUP	FN:14	PRODUCER	18-Mar-2013 18:54	12342.5 FT	20.0 FT

Output DLIS Files

DEFAULT	SCMT_HBMS_016PUP	FN:15	PRODUCER	18-Mar-2013 19:06
---------	------------------	-------	----------	-------------------

Index: 12342.5 - 20.0 FT



19961 Points Plotted

18-MAR-2013 19:04

Schlumberger

PBMS COEFFICIENTS

MAXIS Field Log

Client: ENCANA OIL & GAS (USA) INC

Field: STORY GULCH

Well: SGU 8512D-24 (L24 496)

Run date: 18-Mar-2013

Tool: PSP

Sub Type: PBMS

Sensor: GR

PBMS Gamma Ray

Sonde Serial NB

Sensor Serial NB

Calib Date ddmmyy

Matrix Size

Coeff CRC

RESISTORS FOR GR SENSOR N.34384,TOOL HBMS-BA2880. SENSOR S/N:

34384

160206

12

D8B5

GR HV Rt

	Rt**0	Rt**1
Rt**0	+.200000000000e+04	+.173000000000e+04

Client: ENCANA OIL & GAS (USA) INC

Field: STORY GULCH

Well: SGU 8512D-24 (L24 496)

Run date: 18-Mar-2013

Tool: PSP

Sub Type: PBMS

Sensor: WellTemp RTD

PBMS RTD Well Thermometer

Sonde Serial NB

Sensor Serial NB

Calib Date ddmmyy

Matrix Size

Coeff CRC

COEFFICIENTS FOR RTD THERMOMETER PBMS-B.2880 S/N:

2880

260408

16

A3AF

WTemp Coeff

	Tt**0	Tt**1	Tt**2
Tt**0	-.104337336008E+04	+.798824971753E+03	-.251944021281E+03
	Tt**3	Tt**4	Tt**5
Tt**0	+.406192777109E+02	-.240958437264E+01	0.0

Client: ENCANA OIL & GAS (USA) INC

Field: STORY GULCH

Well: SGU 8512D-24 (L24 496)

Run date: 18-Mar-2013

Tool: PSP

Sub Type: PBMS

Sensor: CQG

PBMS Quartz Gauge type F

Sonde Serial NB

Sensor Serial NB

Calib Date ddmmyy

Matrix Size

Coeff CRC

COEFFICIENTS FOR CQG PBMS-B.2880 S/N:

2880

260408

66

66B8

Pres Coeff

	Fb**0	Fb**1	Fb**2
Fc**0	+.694668499013E+04	+.138137467574E-01	-.206148488488E-06
Fc**1	-.104285125976E+01	-.125721589078E-04	-.971577899959E-10
Fc**2	+.101045175546E-05	+.480801816357E-10	+.889110474366E-15
Fc**3	+.127326781620E-11	+.130693902354E-15	0.0
Fc**4	0.0	0.0	0.0
Fc**5	0.0	0.0	0.0

	Fb**3	Fb**4	Fb**5
Fc**0	-.802395356069E-10	-.148392899370E-14	-.162952476494E-19
Fc**1	+.114970383999E-15	+.186330526680E-19	0.0
Fc**2	0.0	0.0	0.0
Fc**3	0.0	0.0	0.0
Fc**4	0.0	0.0	0.0
Fc**5	0.0	0.0	0.0

PBMS Quartz Gauge type F

Sonde Serial NB

Sensor Serial NB

Calib Date ddmmyy

:

2880

260408

Matrix Size 66
Coeff CRC 3690

Temp Coeff

	Fc**0	Fc**1	Fc**2
Fb**0	+.114978632240E+03	-.318843725686E-03	+.651766172344E-08
Fb**1	-.590205352250E-02	+.168686572404E-07	+.162345150354E-12
Fb**2	-.362996279263E-07	+.407654559315E-12	+.452411391342E-17
Fb**3	-.276281361281E-12	+.871817059405E-17	0.0
Fb**4	0.0	0.0	0.0
Fb**5	0.0	0.0	0.0

	Fc**3	Fc**4	Fc**5
Fb**0	+.199118144093E-13	-.260997933236E-18	+.618908211390E-21
Fb**1	+.250084591851E-17	+.455070709200E-21	0.0
Fb**2	0.0	0.0	0.0
Fb**3	0.0	0.0	0.0
Fb**4	0.0	0.0	0.0
Fb**5	0.0	0.0	0.0

PBMS Quartz Gauge type F

Sonde Serial NB :
Sensor Serial NB 2880
Calib Date ddmmyy 260408
Matrix Size 16
Coeff CRC 71B5

Clock Freq Coeff

	(Fb'-Fc')**0	(Fb'-Fc')**1	(Fb'-Fc')**2
(Fb'-Fc')**0	+.310736316923E+05	+.273670214709E-02	+.731815197856E-06

	(Fb'-Fc')**3	(Fb'-Fc')**4	(Fb'-Fc')**5
(Fb'-Fc')**0	-.654219198492E-10	-.150585137208E-15	-.117697151708E-19

PBMS Quartz Gauge type F

Sonde Serial NB :
Sensor Serial NB 2880
Calib Date ddmmyy 260408
Matrix Size 16
Coeff CRC ECB5

Clock Temp Coeff

(Fb'-Fc')**0	(Fb'-Fc')**1	(Fb'-Fc')**2

(Fb'-Fc')**0	+.116053417872E+03	-.554118045908E-02	-.348241454518E-07
	(Fb'-Fc')**3	(Fb'-Fc')**4	(Fb'-Fc')**5
(Fb'-Fc')**0	+.207992675474E-12	-.353168788938E-17	-.345142848607E-21

Schlumberger

MASTER CALIBRATION

MAXIS Field Log

Slim Cement Mapping Tool, 1-11/16 OD / Equipment Identification

Primary Equipment:

Slim Cement Mapping Xmitter Electronics
Slim Cement Mapping Sonde
Slim Cement Mapping Cartridge

SCMX - CA 8179
SCMS - CB 8120
SCMC - CA










Auxiliary Equipment:

Slim Electronics Cartridge Housing

SECH - CA

Slim Cement Mapping Tool, 1-11/16 OD Master Calibration

SCMT CBL and MAP Amplitude Normalization in SFT-155/-255

Phase	MAP 1 Amplitude Plus MV	Value	Phase	MAP 2 Amplitude Plus MV	Value
Master		1158	Master		1232
	500.0 (Minimum) 1075 (Nominal) 1650 (Maximum)			500.0 (Minimum) 1075 (Nominal) 1650 (Maximum)	
Phase	MAP 3 Amplitude Plus MV	Value	Phase	MAP 4 Amplitude Plus MV	Value
Master		1237	Master		1118
	500.0 (Minimum) 1075 (Nominal) 1650 (Maximum)			500.0 (Minimum) 1075 (Nominal) 1650 (Maximum)	
Phase	MAP 5 Amplitude Plus MV	Value	Phase	MAP 6 Amplitude Plus MV	Value
Master		1061	Master		1299
	500.0 (Minimum) 1075 (Nominal) 1650 (Maximum)			500.0 (Minimum) 1075 (Nominal) 1650 (Maximum)	
Phase	MAP 7 Amplitude Plus MV	Value	Phase	MAP 8 Amplitude Plus MV	Value
Master		1258	Master		1267
	500.0 (Minimum) 1075 (Nominal) 1650 (Maximum)			500.0 (Minimum) 1075 (Nominal) 1650 (Maximum)	
Phase	CBL Amplitude Plus MV	Value			
Master		1351			
	1000 (Minimum) 1350 (Nominal) 1700 (Maximum)				

Master: 2-Jan-2013 15:55

Company: **ENCANA OIL & GAS (USA) INC**

Schlumberger

Well: **SGU 8512D-24 (L24 496)**

Field: **STORY GULCH**

County: **GARFIELD**

State: **COLORADO**

SLIM CEMENT MAPPING LOG
GAMMA RAY - CCL - TEMPERATUR
CBL - VDL