Company: ANADARKO PETROLEUM CORP
Well: VIVIANE #12A
Field: WATTENBERG
State: COLORADO
County: WELD
Field: WATTENBERG
Location: SEC 34 T3N R67W 6TH PM
Company: ANADARKO PETROLEUM CORP
Well: VIVIANE #12A
State: COLORADO
County: WELD
Field: WATTENBERG
Location: SEC 34 T3N R67W 6TH PM

CEMENT BOND COLLAR LOG

Comments

BOTTOM CEMENT@5140

Transmitter	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
			CENTR (1)	5.00	1.69	10.00
CCL	14.00		CCL-CTBasic (2.75TEC1) 1.75 TEC CL Axial Freq	1.46	2.75	20.00
GR	11.40		GR-ALPHA (EDT)	2.92	1.69	30.00
WVP1	7.14					
WVP2	6.24		CBL_TJ (SYC)	7.21	2.44	127.00
			CENTR (2)	5.00	1.69	10.00

Cutaway
Total Length: 57.71 ft
Max Diameter: 2.44 in
O.D: 1.72 in

Database File: anadarko.db
Dataset Pathname: pass1
Presentation Format: cbl
Dataset Creation: Wed Oct 09 20:23:14 2013 by Log SCH 111116
Charted by: Depth in Feet scaled 1:240

HL	CCL	+0.250	TT	Amplitude (mV)	500	Variable Density	1250
100	TT1 (usec)	200		Amplitude Amplitude (mV)	0		

Top of Cement

3600
4000
4100
4200
4300
4400
4500
4600
4700
4800
4900
5000
5100
5140 TOP OF BOTTOM
5200
5300

HL	CCL	-0.250	TT	Amplitude (mV)	500	Variable Density	1250
100	TT1 (usec)	200		Amplitude Amplitude (mV)	0		

Database File: anadarko.db
Dataset Pathname: pass1
Dataset Creation: Wed Oct 09 20:23:14 2013 by Log SCH 111116

Calibration Report

Cement Bond Log Calibration Report

Serial Number	501		
Tool Model	SLIM		
Calibration Date	Wed Oct 09 20:10:00 2013		
Depth	1936.76	ft	
Casing Diameter	4.5	in	
	T Spacing	T Spacing	
Digital Zero	2	2	mV
Calibrated Amplitude	61.583	61.583	mV
Reading at Zero Amplitude	0.5	0.5	mV
Reading at Peak Pips	2.5	2.5	V
Gain	31.2764	31.2764	
Offset	2	2	

Gamma Ray Calibration Report

Serial Number	501	
Tool Model	SLIMGR	
Calibration Date	Wed Oct 10 14:32:25 1962	
Calibrator Value	7.0	GAPI
Background Reading	0.0	cps
Calibrator Reading	0.0	cps
Sensitivity	1.0000	GAPI/cps