

FORM 5A

Rev 06/12

State of Colorado Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



Table with columns DE, ET, OE, ES

Document Number: 400505032

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 100322
2. Name of Operator: NOBLE ENERGY INC
3. Address: 1625 BROADWAY STE 2200
City: DENVER State: CO Zip: 80202
4. Contact Name: Kathleen Mills
Phone: (720) 587-2226
Fax: (303) 228-4286

5. API Number 05-123-36299-00
6. County: WELD
7. Well Name: TREBOR B
Well Number: 11-67-1HN
8. Location: QtrQtr: SWNW Section: 11 Township: 5N Range: 64W Meridian: 6
9. Field Name: WATTENBERG Field Code: 90750

Completed Interval

FORMATION: NIOBRARA Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 09/26/2013 End Date: 09/26/2013 Date of First Production this formation: 10/14/2013

Perforations Top: 7179 Bottom: 10957 No. Holes: 0 Hole size:

Provide a brief summary of the formation treatment: Open Hole: []

FRAC'D W/3184367 GAL PERMSTIM AND SLICK WATER AND 4237031# OTTAWA SAND

This formation is commingled with another formation: [] Yes [X] No

Total fluid used in treatment (bbl): 75818 Max pressure during treatment (psi): 6035
Total gas used in treatment (mcf): Fluid density at initial fracture (lbs/gal): 8.43
Type of gas used in treatment: Min frac gradient (psi/ft): 0.89
Total acid used in treatment (bbl): Number of staged intervals: 18
Recycled water used in treatment (bbl): 4531 Flowback volume recovered (bbl): 2010
Fresh water used in treatment (bbl): 71287 Disposition method for flowback: RECYCLE
Total proppant used (lbs): 4237031 Rule 805 green completion techniques were utilized: [X]

Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 10/17/2013 Hours: 24 Bbl oil: 239 Mcf Gas: 326 Bbl H2O: 232
Calculated 24 hour rate: Bbl oil: 239 Mcf Gas: 326 Bbl H2O: 232 GOR: 1364
Test Method: FLOWING Casing PSI: 1490 Tubing PSI: 1480 Choke Size: 16/64
Gas Disposition: SOLD Gas Type: WET Btu Gas: 1108 API Gravity Oil: 38
Tubing Size: 22 + 7/8 Tubing Setting Depth: 6855 Tbg setting date: 10/10/2013 Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: [] Yes [] No If yes, number of sacks cmt

** Bridge Plug Depth: ** Sacks cement on top: ** Wireline and Cement Job Summary must be attached.

Comment:

--

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Kathleen Mills
Title: Regulatory Analyst Date: _____ Email: kmills@nobleenergyinc.com
:

Attachment Check List

Att Doc Num **Name**

--	--

Total Attach: 0 Files

General Comments

User Group **Comment** **Comment Date**

--	--	--

Total: 0 comment(s)