

Light, Cheryl

From: Light, Cheryl
Sent: Monday, November 11, 2013 3:56 PM
To: Light, Cheryl
Subject: FW: KUNZMAN FEDERAL 30N-5HZ Drill & Abandon?
Attachments: Kunzman Federal 30N-5HZ PROPOSED WBD.xlsx; Kunzman Federal 30N-5HZHZ PROCEDURE.docx

From: Schmiegelt, Mike
Sent: Monday, October 14, 2013 8:28 AM
To: Frantz, Sabrina
Cc: McManus, Todd
Subject: RE: KUNZMAN FEDERAL 30N-5HZ Drill & Abandon?

This well currently has surface casing set and has been cemented on the backside, the issue was we could not circulate through the shoe track so we needed to perforate above the float collar to circulate cement. It should be cemented from 787' back to surface. There is currently a 60' cement plug inside casing with fresh water above it. It will need to be P&A'd by your group pumping cement inside casing, we are going to re-drill this surface hole (Kunzman Federal 30N-5HZR) to drill the well.

All of this was approved by Dianna Burn at the COGCC.

Please call me with any further questions.

Mike Schmiegelt | Drilling Engineer – Rockies | **Anadarko Petroleum Corporation**
mike.schmiegelt@anadarko.com | Office (720) 929-6834 | Cell (720) 880-8738