



Company: **ENCANA OIL & GAS (USA) INC**

Well: **SHIDELER 19-16CC (O19EB)**

Field: **MAMM CREEK**

County: **GARFIELD**

State: **COLORADO**

**RESERVOIR SATURATION LOG
SIGMA MODE
GR-CCL**

County: **GARFIELD**
Field: **MAMM CREEK**
Location: **SHL: 624 FSL & 1607 FEL**
Well: **SHIDELER 19-16CC (O19EB)**
Company: **ENCANA OIL & GAS (USA) INC**

LOCATION		SHL: 624 FSL & 1607 FEL	Elev.:	K.B. 6631.00 ft
		BHL: 69 FSL & 652 FEL	G.L. 6509.00 ft	D.F. 6630.00 ft
Permanent Datum:	GROUND LEVEL	Elev.: 6609.00 ft		
Log Measured From:	KELLY BUSHING	22.00 ft	above Perm. Datum	
Drilling Measured From:	KELLY BUSHING			
API Serial No.	Section 19	Township 7S	Range 92W	
05-045-21842-000C				

Logging Date	27-Apr-2013		
Run Number	1		
Depth Driller	7634 ft		
Schlumberger Depth	7545 ft		
Bottom Log Interval	7511 ft		
Top Log Interval	2000 ft		
Casing Fluid Type	FRESH WATER		
Salinity			
Density	8.4 lbm/gal		
Fluid Level	60 ft		
BIT/CASING/TUBING STRING			
Bit Size	7.875 in		
From	6525 ft		
To	7634 ft		
Casing/Tubing Size	4.500 in		
Weight	11.6 lbm/ft		
Grade			
From	22 ft		
To	7615 ft		
Maximum Recorded Temperatures	222 degF		
Logger On Bottom	27-Apr-2013	18:30	
Unit Number	391	GRAND JUNCTION	
Recorded By	KIRSTIE BUNTING		
Witnessed By	BILLY MYERS		

	Run 1	Run 2	Run
PVT DATA			
Oil Density			
Water Salinity			
Gas Gravity			
Bo			
Bw			
1/Bg			
Bubble Point Pressure			
Bubble Point Temperature			
Solution GOR			
Maximum Deviation			
CEMENTING DATA			
Primary/Squeeze	Primary		
Casing String No			
Lead Cement Type			
Volume			
Density			
Water Loss			
Additives			
Tail Cement Type			
Volume			
Density			
Water Loss			
Additives			
Expected Cement Top			
Logging Date			
Run Number			
Depth Driller			
Schlumberger Depth			
Bottom Log Interval			
Top Log Interval			
Casing Fluid Type			
Salinity			
Density			
Fluid Level			
BIT/CASING/TUBING STRING			
Bit Size			
From			
To			
Casing/Tubing Size			
Weight			
Grade			
From			
To			
Maximum Recorded Temperatures			
Logger On Bottom			
Unit Number			
Recorded By			
Witnessed By			

DEPTH SUMMARY LISTING

Date Created: 14-MAR-2013 10:41:08

Depth System Equipment

Depth Measuring Device	Tension Device	Logging Cable
Type: IDW-B Serial Number: 6214 Calibration Date: 24-APR-2012 Calibrator Serial Number: Calibration Cable Type: 1-25ZT Wheel Correction 1: -3 Wheel Correction 2: -4	Type: CMTD-B/A Serial Number: 3421 Calibration Date: 20-FEB-2011 Calibrator Serial Number: 174878 Number of Calibration Points: 10 Calibration RMS: 4 Calibration Peak Error: 8	Type: 1-25ZT Serial Number: 112136 Length: 19500 FT Conveyance Method: Wireline Rig Type: LAND

Depth Control Parameters

Log Sequence: First Log In the Well
Rig Up Length At Surface: 0.00 FT
Rig Up Length At Bottom: 0.00 FT
Rig Up Length Correction: 0.00 FT
Stretch Correction:
Tool Zero Check At Surface:

Depth Control Remarks

<ol style="list-style-type: none"> 1. ALL SCHLUMBERGER DEPTH CONTROL POLICIES APPLIED 2. IDW USED AS PRIMARY DEPTH REFERENCE 3. SWPT DRUM COUNTER USED AS SECONDARY DEPTH REFERENCE 4. 5. 6.
--

DISCLAIMER

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

OTHER SERVICES1	OTHER SERVICES2
OS1: SLIM CEMENT MAPPING	OS1:
OS2: LOG	OS2:
OS3: CBL-VDL	OS3:
OS4:	OS4:
OS5:	OS5:
REMARKS: RUN NUMBER 1	REMARKS: RUN NUMBER 2
FIRST RUN IN HOLE CORRELATED TO DOWN LOG	
TOOL RAN AS PER TOOL SKETCH	
MAXIMUM RECORDED TEMPERATURE= 222 DEGF	
MAXIMUM RECORDED PRESSURE= 3153 PSIA	
ENTRANCE TIME= 18:00	

TIME ON BOTTOM= 18:30
EXIT TIME= 20:30
SHORT JOINTS: 5101 FT & 6093 FT
SANDSTONE MATRIX USED
THANK YOU FOR CHOOSING E&P WIRELINE, A SCHLUMBERGR COMPANY
CREW: KBUNTING JBARRY KJOHNS JMANN


RUN 1			RUN 2		
SERVICE ORDER #:	CGF9-00056		SERVICE ORDER #:		
PROGRAM VERSION:	19C0-187		PROGRAM VERSION:		
FLUID LEVEL:	60 ft		FLUID LEVEL:		
LOGGED INTERVAL	START	STOP	LOGGED INTERVAL	START	STOP

EQUIPMENT DESCRIPTION

RUN 1 RUN 2


SURFACE EQUIPMENT

WITM-A
PSC_16MHZ



SCMT-CB
 SCMC-CA 8120
 SECH-CA
 CMIR-AG
 SCMS-CB 8303
 SCMX-CA

20.3



AH-YYY

Tension SCMT HV
 TOOL ZERO 0.0

0.2

MAXIMUM STRING DIAMETER 1.72 IN
 MEASUREMENTS RELATIVE TO TOOL ZERO
 ALL LENGTHS IN FEET



MAIN PASS RST SIGMA

MAXIS Field Log

Input DLIS Files

DEFAULT	SCMT_RST_PSP_026LUP	FN:24	PRODUCER	27-Apr-2013 18:32	7551.5 FT	-29.8 FT
---------	---------------------	-------	----------	-------------------	-----------	----------

Output DLIS Files

DEFAULT	SCMT_RST_PSP_030PUP	FN:28	PRODUCER	27-Apr-2013 20:40	7554.5 FT	-71.0 FT
---------	---------------------	-------	----------	-------------------	-----------	----------

OP System Version: 19C0-187

SCMT-CB PSPT	SRPC-5214-H2-2012-OP1! SRPC-5214-H2-2012-OP1!	RST-C	SRPC-5214-H2-2012-OP1!
-----------------	--	-------	------------------------

Changed Parameter Summary

DLIS Name	New Value	Previous Value	Depth & Time
BS	7.875 IN 8.750 IN	7.875 IN 7.875 IN	7554.5 20:40:14 6525.0 20:42:43

PIP SUMMARY

Time Mark Every 60 S

Crossover in sand
 From RST_CIRF_FIL to RST_CIRN_FIL

WINR Gas Flag

RST Weighted Inelastic Ratio (WINR_RST)

0.4 (----) 0

Minitron Arc Detection (MARC)

RST Porosity (TPHI) (V/V)

RST Capture to Inelastic Ratio Far (CIRF_FIL)

0.5 (----) 0 7 (----) 0

RST Borehole Salinity (BSAL)

Discriminated CCL (CCLD)

RST Sigma (SIGM)

450 (PPK) -50 60 (CU) 0


Gamma Ray (GR) (GAPI)


Tension (TENS) (LBF)

RST Inelastic Ratio (IRAT_FIL)

RST Capture to Inelastic Ratio Near (CIRN_FIL)

0 150 0.75 (----) 0 2.5 (----) 0





100

200

300


TENS

BSAL

GR

MARC

CCLD



400

TENS


500


BSAL


GR


MARC


CCLD














1700

TENS


BSAL


GR


CCLD


MARC


1800








































































First Reading GR 7498 FT

First Reading RST 7511 FT

Total Depth 7545 FT



450	RST Borehole Salinity (BSAL) (PPK)	-50	Discriminat ed CCL (CCLD)	60	RST Sigma (SIGM) (CU)	0
			3 (V) -1			
			Minitron Arc Detection (MARC)	0.5	RST Porosity (TPHI) (V/V)	0
			0 (---- 5)		RST Capture to Inelastic Ratio Far (CIRF_FIL)	0
				0.4	RST Weighted Inelastic Ratio (WINR_RST)	0
					WINR Gas Flag From WINR to RST_CIRF_FIL	
					Crossover in sand From RST_CIRF_FIL to RST_CIRN_FIL	

PIP SUMMARY

Time Mark Every 60 S

Parameters

DLIS Name	Description	Value
SCMT-CB: Slim Cement Mapping Tool, 1-11/16 OD		
BILI	Bond Index Level for Zone Isolation	0.8
BISS	Bond Index Source Selection for BIQL	BI
CB3D	SCMT CBL 3 ft Peak Detection Mode	PEAK
CB3G	SCMT CBL 3 ft Peak Detection T0_Delay and Noise Gate	224.559 US
CB3T	SCMT CBL 3 ft Fixed Threshold Level	20 MV
CB5D	SCMT CBL 5 ft Peak Detection Mode	PEAK
CB5G	SCMT CBL 5 ft Peak Detection T0_Delay and Noise Gate	338.559 US
CB5T	SCMT CBL 5 ft Fixed Threshold Level	20 MV
CBLG	CBL Gate Width	45 US
CBRA	CBL LQC Reference Amplitude in Free Pipe	80 MV
CMCF	CBL Cement Type Compensation Factor	1
CMTC	SCMT Slow Channel Multiplexer Mode	SCAN
CMTM	SCMT Operating Mode	LOG
CMTF	SCMT Tool position on CAN	5
CSCS	SCMT Slow Channel Index	VCC
CTHI	Casing Thickness	0.255617 IN
DTF	Delta-T Fluid	189 US/F
FATT	Acoustic Attenuation due to Fluid	0 DB/F
FCF	CBL Fluid Compensation Factor	0.924277
GOBO	Good Bond	1.55185 MV
MAPD	SCMT MAP Peak Detection Mode	PEAK
MAPG	SCMT MAP Peak Detection T0_Delay and Noise Gate	167.559 US
MAPT	SCMT MAP Fixed Threshold Level	30 MV
MATT	Maximum Attenuation	16.5449 DB/F
MCCF	MAP Cement Type Compensation Factor	1
MCI	Minimum Cemented Interval for Isolation	1.25 FT
MMSA	MAP Minimum Sonic Amplitude	4.32284 MV
MSA	Minimum Sonic Amplitude	0.579149 MV
PEDE	Peak Detection On/Off Switch in Playback	OFF
RBC	Relative Bearing Correction Allow/Disallow	ALLOW
VDLG	VDL Manual Gain	5
ZCMT	Acoustic Impedance of Cement	6.8 MRAY
RST-C: Reservoir Saturation Pro Tool C		
AIRB	Tractor Available in Tool String	NO
BHS	RST Air Borehole	No
BHT	Borehole Status	CASED
BSALOPT	Bottom Hole Temperature (used in calculations)	212 DEG F
BSFL	RST Borehole Salinity Option	Unknown
CSID	RST Borehole Salinity Filter Length	51
DFPC	Casing Size I.D.	4 IN
DFPC_TDTL	RST Depth Filter Processing Constant	One
GCSE	RST Depth Filter Processing Constant (TDT-like)	Two
GDEV	Generalized Caliper Selection	BS
GRDR	Average Angular Deviation of Borehole from Normal	0 DEG
GRSE	Geothermal Gradient	0.01 DF/F
GTSE	Generalized Mud Resistivity Selection	CHART_GEN_9
ISSBAR	Generalized Temperature Selection	LINEAR_ESTIMATE
MATR	Barite Mud Switch	NOBARITE
NORM_IPAT_RST	Rock Matrix for Neutron Porosity Corrections	SANDSTONE
	RST Normalized Inelastic Ratio	0.48

NORM_RATIO_RST	RST Normalized Ratio	0.48	
NORM_SIGM_RST	RST Normalized Sigma	30	CU
PTIER	RST Tiered Presentation Selection	0_Customer	
PVL_PSNT_PRST	PVL Peak Signal/Noise Threshold	3	
RGAI	Near/Far Gain Calibration Ratio	1	
SHT	Surface Hole Temperature	68	DEGF
TIER_IC	RST IC Acquisition Mode	0_CO_Yield_and_Spectrolith	
TIER_SIGM	RST Sigma Acquisition Mode	0_RST_Sigma	
WOFSL_PRST	RST WFL-Off Subcycle Length	0	
WONSL_PRST	RST WFL-On Subcycle Length	0	
WSCOM_PRST	RST Station Log Comment		
PSPT: Production Services Logging Platform			
BHS	Borehole Status	CASED	
BHT	Bottom Hole Temperature (used in calculations)	212	DEGF
CSID	Casing Size I.D.	4	IN
GCSE	Generalized Caliper Selection	BS	
GDEV	Average Angular Deviation of Borehole from Normal	0	DEG
GGRD	Geothermal Gradient	0.01	DF/F
GRSE	Generalized Mud Resistivity Selection	CHART_GEN_9	
GTSE	Generalized Temperature Selection	LINEAR_ESTIMATE	
ISSBAR	Barite Mud Switch	NOBARITE	
MATR	Rock Matrix for Neutron Porosity Corrections	SANDSTONE	
PBPO	PBMS Tool position on CAN	2	
PCCG	PBMS CCL Gain	DB0	
PSTP	PSTC Tool Position on CAN Bus	1	
SHT	Surface Hole Temperature	68	DEGF
System and Miscellaneous			
ALTDPCCHAN	Name of alternate depth channel	SpeedCorrectedDepth	
BS	Bit Size	7.875	IN
BSAL	Borehole Salinity	-50000.00	PPM
CSIZ	Current Casing Size	4.500	IN
CWEI	Casing Weight	11.60	LB/F
DFD	Drilling Fluid Density	8.40	LB/G
DO	Depth Offset for Playback	3.0	FT
FLEV	Fluid Level	60.00	FT
MST	Mud Sample Temperature	-50000.00	DEGF
PBVSADP	Use alternate depth channel for playback	NO	
PP	Playback Processing	RECOMPUTE	
RMFS	Resistivity of Mud Filtrate Sample	-50000.0000	OHMM
RW	Resistivity of Connate Water	1.0000	OHMM
TD	Total Depth	7545	FT
TDD	Total Depth - Driller	7634.00	FT
TDL	Total Depth - Logger	7545.00	FT
TWS	Temperature of Connate Water Sample	100.00	DEGF

Format: RST_SIGMA_S5 Vertical Scale: 5" per 100' Graphics File Created: 27-Apr-2013 20:40

OP System Version: 19C0-187

SCMT-CB	SRPC-5214-H2-2012-OP1!	RST-C	SRPC-5214-H2-2012-OP1!
PSPT	SRPC-5214-H2-2012-OP1!		

Input DLIS Files

DEFAULT	SCMT_RST_PSP_026LUP	FN:24	PRODUCER	27-Apr-2013 18:32	7551.5 FT	-29.8 FT
---------	---------------------	-------	----------	-------------------	-----------	----------

Output DLIS Files

DEFAULT	SCMT_RST_PSP_030PUP	FN:28	PRODUCER	27-Apr-2013 20:40		
---------	---------------------	-------	----------	-------------------	--	--



REPEAT ANALYSIS RST SIGMA

MAXIS Field Log

Input DLIS Files

DEFAULT	SCMT_RST_PSP_024LUP	FN:22	PRODUCER	27-Apr-2013 18:19	5335.5 FT	5031.5 FT
---------	---------------------	-------	----------	-------------------	-----------	-----------

Output DLIS Files

DEFAULT SCMT_RST_PSP_032PUP FN:30 PRODUCER 27-Apr-2013 20:47 5335.5 FT 4987.0 FT

OP System Version: 19C0-187



SCMT-CB SRPC-5214-H2-2012-OP1; RST-C SRPC-5214-H2-2012-OP1;
 PSPT SRPC-5214-H2-2012-OP1;


Changed Parameter Summary


DLIS Name	New Value	Previous Value	Depth & Time
BS	8.750 IN	8.750 IN	5335.5 20:47:16

PIP SUMMARY

Time Mark Every 60 S







PIP SUMMARY

Time Mark Every 60 S

Parameters

DLIS Name	Description	Value
SCMT-CB: Slim Cement Mapping Tool, 1-11/16 OD		
BILI	Bond Index Level for Zone Isolation	0.8
BISS	Bond Index Source Selection for BIQL	BI
CB3D	SCMT CBL 3 ft Peak Detection Mode	PEAK
CB3G	SCMT CBL 3 ft Peak Detection T0_Delay and Noise Gate	224.559 US
CB3T	SCMT CBL 3 ft Fixed Threshold Level	20 MV
CB5D	SCMT CBL 5 ft Peak Detection Mode	PEAK
CB5G	SCMT CBL 5 ft Peak Detection T0_Delay and Noise Gate	338.559 US
CB5T	SCMT CBL 5 ft Fixed Threshold Level	20 MV
CBLG	CBL Gate Width	45 US
CBRA	CBL LQC Reference Amplitude in Free Pipe	80 MV
CMCF	CBL Cement Type Compensation Factor	1
CMTC	SCMT Slow Channel Multiplexer Mode	SCAN
CMTM	SCMT Operating Mode	LOG
CMTF	SCMT Tool position on CAN	5
CSCS	SCMT Slow Channel Index	VCC
CTHI	Casing Thickness	0.255617 IN
DTF	Delta-T Fluid	189 US/F
FATT	Acoustic Attenuation due to Fluid	0 DB/F
FCF	CBL Fluid Compensation Factor	0.924277
GOBO	Good Bond	1.55185 MV
MAPD	SCMT MAP Peak Detection Mode	PEAK
MAPG	SCMT MAP Peak Detection T0_Delay and Noise Gate	167.559 US
MAPT	SCMT MAP Fixed Threshold Level	30 MV
MATT	Maximum Attenuation	16.5449 DB/F
MCCF	MAP Cement Type Compensation Factor	1
MCI	Minimum Cemented Interval for Isolation	1.25 FT
MMSA	MAP Minimum Sonic Amplitude	4.32284 MV
MSA	Minimum Sonic Amplitude	0.579149 MV
PEDE	Peak Detection On/Off Switch in Playback	OFF
RBC	Relative Bearing Correction Allow/Disallow	ALLOW
VDLG	VDL Manual Gain	5
ZCMT	Acoustic Impedance of Cement	6.8 MRAY
RST-C: Reservoir Saturation Pro Tool C		
AIRB	Tractor Available in Tool String	NO
RUC	RST Air Borehole	NO
CASER	Reservoir Saturation	CASER

BHS	Borehole Status	CASED	
BHT	Bottom Hole Temperature (used in calculations)	212	DEGF
BSALOPT	RST Borehole Salinity Option	Unknown	
BSFL	RST Borehole Salinity Filter Length	51	
CSID	Casing Size I.D.	4	IN
DFPC	RST Depth Filter Processing Constant	One	
DFPC_TDTL	RST Depth Filter Processing Constant (TDT-like)	Two	
GCSE	Generalized Caliper Selection	BS	
GDEV	Average Angular Deviation of Borehole from Normal	0	DEG
GGRD	Geothermal Gradient	0.01	DF/F
GRSE	Generalized Mud Resistivity Selection	CHART_GEN_9	
GTSE	Generalized Temperature Selection	LINEAR_ESTIMATE	
ISSBAR	Barite Mud Switch	NOBARITE	
MATR	Rock Matrix for Neutron Porosity Corrections	SANDSTONE	
NORM_IRAT_RST	RST Normalized Inelastic Ratio	0.48	
NORM_SIGM_RST	RST Normalized Sigma	30	CU
PTIER	RST Tiered Presentation Selection	0_Customer	
PVL_PSNT_PRST	PVL Peak Signal/Noise Threshold	3	
RGAI	Near/Far Gain Calibration Ratio	1	
SHT	Surface Hole Temperature	68	DEGF
TIER_IC	RST IC Acquisition Mode	0_CO_Yield_and_Spectrolith	
TIER_SIGM	RST Sigma Acquisition Mode	0_RST_Sigma	
WOFSL_PRST	RST WFL-Off Subcycle Length	0	
WONSL_PRST	RST WFL-On Subcycle Length	0	
WSCOM_PRST	RST Station Log Comment		

PSPT: Production Services Logging Platform

BHS	Borehole Status	CASED	
BHT	Bottom Hole Temperature (used in calculations)	212	DEGF
CSID	Casing Size I.D.	4	IN
GCSE	Generalized Caliper Selection	BS	
GDEV	Average Angular Deviation of Borehole from Normal	0	DEG
GGRD	Geothermal Gradient	0.01	DF/F
GRSE	Generalized Mud Resistivity Selection	CHART_GEN_9	
GTSE	Generalized Temperature Selection	LINEAR_ESTIMATE	
ISSBAR	Barite Mud Switch	NOBARITE	
MATR	Rock Matrix for Neutron Porosity Corrections	SANDSTONE	
PBPO	PBMS Tool position on CAN	2	
PCCG	PBMS CCL Gain	DB0	
PSTP	PSTC Tool Position on CAN Bus	1	
SHT	Surface Hole Temperature	68	DEGF

System and Miscellaneous

ALTDPCCHAN	Name of alternate depth channel	SpeedCorrectedDepth	
BS	Bit Size	8.750	IN
BSAL	Borehole Salinity	-50000.00	PPM
CSIZ	Current Casing Size	4.500	IN
CWEI	Casing Weight	11.60	LB/F
DFD	Drilling Fluid Density	8.40	LB/G
DO	Depth Offset for Playback	0.0	FT
DORL	Depth Offset for Repeat Analysis	0.0	FT
FLEV	Fluid Level	60.00	FT
MST	Mud Sample Temperature	-50000.00	DEGF
PBVSADP	Use alternate depth channel for playback	NO	
PP	Playback Processing	RECOMPUTE	
RMFS	Resistivity of Mud Filtrate Sample	-50000.0000	OHMM
RW	Resistivity of Connate Water	1.0000	OHMM
TD	Total Depth	7545	FT
TDD	Total Depth - Driller	7634.00	FT
TDL	Total Depth - Logger	7545.00	FT
TWS	Temperature of Connate Water Sample	100.00	DEGF

Format: RST_SIGMA_S5_REP Vertical Scale: 5" per 100' Graphics File Created: 27-Apr-2013 20:47

OP System Version: 19C0-187

SCMT-CB SRPC-5214-H2-2012-OP1! RST-C SRPC-5214-H2-2012-OP1!
 PSPT SRPC-5214-H2-2012-OP1!

Input DLIS Files

DEFAULT	SCMT_RST_PSP_024LUP	FN:22	PRODUCER	27-Apr-2013 18:19	5335.5 FT	5031.5 FT
DEFAULT	SCMT_RST_PSP_030PUP	FN:28	PRODUCER	27-Apr-2013 20:40	7554.5 FT	-71.0 FT

Output DLIS Files

DEFAULT	SCMT_RST_PSP_032PUP	FN:30	PRODUCER	27-Apr-2013 20:47		
---------	---------------------	-------	----------	-------------------	--	--

MAXIS Field Log

Client: ENCANA OIL & GAS (USA) INC
 Field: MAMM CREEK
 Well: SHIDELER 19-16CC (O19EB)
 Run date: 27-Apr-2013

Tool: PSP
 Sub Type: PBMS
 Sensor: GR

PBMS Gamma Ray

Sonde Serial NB RESISTORS FOR GR SENSOR N.33223,TOOL PBMS-BA0928. SENSOR S/N:
 Sensor Serial NB 33223
 Calib Date ddmmyy 090800
 Matrix Size 12
 Coeff CRC CFE2

GR HV Rt

Rt**0

Rt**1

Rt**0

+.182000000000e+04

+.332000000000e+04

Client: ENCANA OIL & GAS (USA) INC
 Field: MAMM CREEK
 Well: SHIDELER 19-16CC (O19EB)
 Run date: 27-Apr-2013

Tool: PSP
 Sub Type: PBMS
 Sensor: WellTemp RTD

PBMS RTD Well Thermometer

Sonde Serial NB COEFFICIENTS FOR RTD THERMOMETER PBMS-B.928 S/N:
 Sensor Serial NB 928
 Calib Date ddmmyy 280612
 Matrix Size 16
 Coeff CRC A24E

WTemp Coeff

	Tt**0	Tt**1	Tt**2
Tt**0	-.391987973189E+03	+.191346892512E+03	-.440920753451E+02
	Tt**3	Tt**4	Tt**5
Tt**0	+.957191300908E+01	-.711421725686E+00	0.0

Client: ENCANA OIL & GAS (USA) INC
 Field: MAMM CREEK
 Well: SHIDELER 19-16CC (O19EB)
 Run date: 27-Apr-2013

Tool: PSP
 Sub Type: PBMS
 Sensor: CQG

PBMS Quartz Gauge type F

Sonde Serial NB
 Sensor Serial NB
 Calib Date ddmmyy
 Matrix Size
 Coeff CRC

COEFFICIENTS FOR CQG PBMS-B.928 S/N:
 928
 280612
 66
 9DC3

Pres Coeff

	Fb**0	Fb**1	Fb**2
Fc**0	+.714463802232E+04	+.183434658655E-01	-.156620073569E-06
Fc**1	-.100638308957E+01	-.119899563644E-04	-.912155899025E-10
Fc**2	+.936268101283E-06	+.423898071451E-10	+.958076371919E-15
Fc**3	+.185123362373E-11	+.203107925433E-15	0.0
Fc**4	0.0	0.0	0.0
Fc**5	0.0	0.0	0.0

	Fb**3	Fb**4	Fb**5
Fc**0	-.746577997611E-10	-.588773826860E-15	-.622250441458E-19
Fc**1	-.120636521092E-15	+.400325894750E-19	0.0
Fc**2	0.0	0.0	0.0
Fc**3	0.0	0.0	0.0
Fc**4	0.0	0.0	0.0
Fc**5	0.0	0.0	0.0

PBMS Quartz Gauge type F

Sonde Serial NB :
 Sensor Serial NB 928
 Calib Date ddmmyy 280612
 Matrix Size 66
 Coeff CRC 283B

Temp Coeff

	Fc**0	Fc**1	Fc**2
Fb**0	+1.117016867873E+03	-.284359629614E-03	+6.04391180345E-08
Fb**1	-.598309140812E-02	+1.82731130848E-07	+1.60166486172E-12
Fb**2	-.307621454576E-07	+3.00601550309E-12	+3.11233548560E-17
Fb**3	-.419658736767E-12	+1.117473708647E-16	0.0
Fb**4	0.0	0.0	0.0
Fb**5	0.0	0.0	0.0
	Fc**3	Fc**4	Fc**5
Fb**0	+1.114322792679E-12	+1.53807711176E-17	-.736714260866E-21
Fb**1	-.528037875456E-18	-.220337637519E-21	0.0
Fb**2	0.0	0.0	0.0
Fb**3	0.0	0.0	0.0
Fb**4	0.0	0.0	0.0
Fb**5	0.0	0.0	0.0

PBMS Quartz Gauge type F

Sonde Serial NB :
 Sensor Serial NB 928
 Calib Date ddmmyy 280612
 Matrix Size 16
 Coeff CRC 093F

Clock Freq Coeff

	(Fb'-Fc')**0	(Fb'-Fc')**1	(Fb'-Fc')**2
(Fb'-Fc')**0	+3.10874009898E+05	+2.88920923041E-02	+6.97940727038E-06
	(Fb'-Fc')**3	(Fb'-Fc')**4	(Fb'-Fc')**5
(Fb'-Fc')**0	-.657432344763E-10	-.412920638782E-15	+2.13369826099E-20

Sonde Serial NB :
Sensor Serial NB 928
Calib Date ddmmyy 280612
Matrix Size 16
Coeff CRC 8419

Clock Temp Coeff

	(Fb'-Fc')**0	(Fb'-Fc')**1	(Fb'-Fc')**2
(Fb'-Fc')**0	+1.115369519827E+03	-.565338877075E-02	-.333717531829E-07
	(Fb'-Fc')**3	(Fb'-Fc')**4	(Fb'-Fc')**5
(Fb'-Fc')**0	-.124387135327E-12	+7.13102327208E-16	-.316084316842E-20

Company: **ENCANA OIL & GAS (USA) INC**

Schlumberger

Well: **SHIDELER 19-16CC (O19EB)**
Field: **MAMM CREEK**
County: **GARFIELD**
State: **COLORADO**

RESERVOIR SATURATION LOG
SIGMA MODE
GR-CCL