



Liner Information		
4-1/2" 11.60# HCP-110		
Burst=	10,690	psi
Collapse=	7,580	psi
Capacity=	0.01554	bbbls/ft

Displacements	BBLs	GALS
2.500" SLV	269.25	11,309
2.375" SLV	272.64	11,451
2.250" SLV	275.41	11,567
2.125" SLV	278.66	11,704
2.000" SLV	282.06	11,847
1.875" SLV	285.47	11,990
1.750" SLV	288.86	12,132
1.625" SLV	292.15	12,270
1.500 + "P" SLV	295.43	12,408
BALL SEAT	296.78	12,465
Float Shoe	297.45	12,493

TD	Float Shoe
10,735.00	10,725.00

17	Zone 16	Zone 15	Zone 14	Zone 13	Zone 12	Zone 11	Zone 10	Zone 9	Zone 8	Zone 7	Zone 6	Zone 5	Zone 4	Zone 3	Zone 2	Zone 1	1.250"
SLV	3.375" SLV	3.250" SLV	3.125" SLV	3.000" SLV	2.875" SLV	2.750" SLV	2.625" SLV	2.500" SLV	2.375" SLV	2.250" SLV	2.125" SLV	2.000" SLV	1.875" SLV	1.750" SLV	1.625" SLV	1.500 + "P" SLV	BALL SEAT
84	7,429.35	7,656.49	7,832.43	8,049.34	8,258.84	8,476.66	8,692.53	8,910.53	9,128.76	9,306.82	9,516.05	9,734.88	9,954.38	10,172.65	10,383.87	10,595.00	10682.19
86	(6) 2286	(6) 2286	(6) 2286	(6) 2286	(6) 2286	(6) 2286	(6) 2286	(6) 2286	(6) 2286	(6) 2286	(6) 2286	(6) 2286	(6) 2286	(6) 2286	(6) 2286	(5) 4025	
	100	100	100	100	100	100	100	100	100	100	100	90	70	60	50	50	

Baker Oil Tools



Sleeve Shift PSI:
Max Rate **Thru** Sleeve:

7.5.1-1F4 Frac-Point Space Out Diagram