Company: ANADARKO PETROLEUM CORP
Well: SHUTT FEDERAL 16-16A
Field: WATTENBERG
County: WELD
State: COLORADO

Company: ANADARKO PETROLEUM CORP
Well: SHUTT FEDERAL 16-16A
Field: WATTENBERG
County: WELD
State: COLORADO

CEMENT BOND GAMMA RAY COLLAR LOG

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or wilful negligence on our part be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
			CENT-A (1)	3.00	1.69	10.00
CCL	14.06		CCL_CTSHeavy (2 TITEX CCL) 1 in Tbl CCL Each Way	1.96	2.75	28.00
GR	11.40		GR_a_6001 (6001)	2.52	1.69	30.00
WVF5	7.34					
WVF3	6.34		CBL_5_5 (001)	7.23	2.44	127.00
			CENT-B (2)	3.00	1.69	10.00

Dataset: shutt federal 16-16a db: fieldvertmain1-pass1
Total Length: 17.71 ft
Total Weight: 197.00 lb
O.D: 2.75 in

Database File: shutt federal 16-16a.db
Dataset Pathname: pass1
Presentation Format: cbl
Dataset Creation: Thu Dec 05 15:36:34 2013 by Log SCH 111116
Charted by: Depth in Feet scaled 1:240

0	Gamma Ray_(GAPI)	150	0	T Amplitude (mV)	100 200 Variable Density 1200
-10	CCL	-0.25	0	Amplified Amplitude (mV)	30
300	TT1 (usec)	200			

Top of Cement

CCL

Travel Time

Gamma Ray

START OF CEMENT

Variable Density

T Amplitude

Amplified Amplitude

0	Gamma Ray_(GAPI)	150	0	T Amplitude (mV)	100 200 Variable Density 1200
-10	CCL	-0.25	0	Amplified Amplitude (mV)	30
300	TT1 (usec)	200			

Calibration Report

Database File: shutt federal 16-16a.db
Dataset Pathname: pass1
Dataset Creation: Thu Dec 05 15:36:34 2013 by Log SCH 111116

Cement Bond Log Calibration Report

Serial Number:	005	
Tool Model:	3.5	
Performed:	Thu Dec 05 19:24:10 2013	
Depth:	548.65	ft
Casing Diameter:	4.5	in
	T Spacing	T Spacing
Signal Zero:	3	3 mV
Calibrated Amplitude:	81.1061	81.1061 mV
Reading in Free Pipe:	2.5	2.5 V
Reading in Free Pipe:	2.5	2.29919 V
Gain:	31.2784	34.0102
Offset:	3	3

Gamma Ray Calibration Report

Serial Number:	6001	
Tool Model:	GR-A	
Performed:	Sun Jun 13 14:30:21 1993	
Calibrator Value:	1.0	GAPI
Background Reading:	0.0	cps
Calibration Reading:	1.0	cps
Sensitivity:	1.0000	GAPI/cps