
Schlumberger
Platform Express
Three Detector Lithology Density
Compensated Neutron
Array Induction Imager Tool
Gamma Ray
Caliper
Bit Size
Mud Type
Density
Viscosity
PH
Fluid Loss
Source
Rm @ Measured Temperature
Rmf @ Measured Temperature
Rmc @ Measured Temperature
Source of Rmf and Rmc
Rm @ BHT
Time Since Circulation
Max Recorded Temperature
Equipment Number
Location
Recorded By
Witnessed By
Run Number
Depth Driller
Depth Logger
Bottom Logged Interval
Top Log Interval
Casing Driller
Casing Logger
BHT
Logging Disk
Logging Date
Logging Unit Number
Logging Engineer
Witness
Run 1
Run 2
Run 3
Run 4
Run 5
Run 6
Run 7
Run 8
Run 9
Run 10
Run 11
Run 12
Run 13
Run 14
Run 15
Run 16
Run 17
Run 18
Run 19
Run 20
Run



PEAK WIRELINE SERVICES, INC.

REPEAT SECTION

Database File:	hanavan1.db
Dataset Pathname:	pass1
Presentation Format:	cbldig
Dataset Creation:	Thu Nov 14 13:22:08 2013 by Log Std Casedhole 10071
Charted by:	Depth in Feet scaled 1:240



Calibration Report

Database File:	hanavan1.db
Dataset Pathname:	pass2
Dataset Creation:	Thu Nov 14 13:29:27 2013 by Log Std Casedhole 10071

Gamma Ray Calibration Report

Serial Number:	061120GR	
Tool Model:	PROBE	
Performed:	Mon Nov 11 11:12:24 2013	
Calibrator Value:	1.0	GAPI
Background Reading:	0.0	cps
Calibrator Reading:	1.0	cps
Sensitivity:	0.8000	GAPI/cps

Cement Bond Log Calibration Report

Serial Number:	5.5dig040201		
Tool Model:	Probe275Digital		
Performed:	Thu Nov 14 13:14:13 2013		
Depth:	11	ft	
Casing Diameter:	5.5	in	
	3' Spacing	5' Spacing	
Signal Zero:	0.25	0	mV
Calibrated Amplitude:	71.921	71.921	mV
Reading at Signal Zero:	0.00905762	0.0149902	V
Reading in Free Pipe:	2.32	2.32632	V
Gain:	31.0138	31.1167	
Offset:	-0.0309113	-0.466447	