



Company: US ROCKIES REGION
 Project: COLORADO-WELD-NAD83-UTM13

Site: REYNOLDS 3-24 PAD
 Common Well Name: REYNOLDS 3-24

API No: 0512321820
 Latitude: 40.217177°
 Longitude: -104.953664°

Datum: RKB
 KB: 4,931.0usft
 Ground Level: 4,920.0usft

Section: 24
 Township: 3 N
 Range: 68 W

Div of Quarter Section: NE
 Div of Section: NW
 MD BH: 7,436.0usft

Casing Information	Casing Depths	Schematic (1/2/2014)	Cement Depths	Cement Fluid (sacks)	Hole Depths	TVD / PBMD	Perforation Intervals (usft)
Casing, 8.625in,	11.0usft	Hole Size 12.250 -----	11usft (TOC)	-NEAT ; ; 3% CACL2 1/4 #/sk Flocel ; 525	11.0usft		
	749.0usft		749usft		755.0usft		
			3660usft (TOC)				
Casing, 4.500in,	11.0usft		4900usft				
			5520usft (TOC)				
			5700usft				
		Hole Size 7.875 -----					
			6537usft (TOC)	-LITE ; ; 12.2#/GAL ; 190			
			6550usft (TOC)	-LITE ; ; 10.6#/GAL ; 100			
			6970usft	-50/50 POZ-MIX ; ; 14.6#/GAL ; 160			
				-FRESH WATER ; LEAD ; 50/50 POZ-MIX ; 25			
							7,028 - 7,028 - NIOBRARA 7,026 - 7,038 - NIOBRARA 7,036 - 7,036 - NIOBRARA 7,039 - 7,039 - NIOBRARA 7,039 - 7,039 - NIOBRARA 7,083 - 7,085 - NIOBRARA 7,084 - 7,096 - NIOBRARA 7,091 - 7,091 - NIOBRARA 7,136 - 7,148 - NIOBRARA 7,280 - 7,292 - CODELL 7,278 - 7,292 - CODELL
Casing Float Collar, 4.500in,	7391.0us						
Casing, 4.500in,	7392.0us						
Casing Guide Shoe, 4.500in,	7434.0us						
	7435.0us						
			7435usft		7436.0usft	TVD 7,436usft, PBMD 7,391usft	