

**PCGC - Pressure Case Gamma**  
**PCDC - Pressure Case Directional**



1 : 240

[illegible]

## WELL INFORMATION

MWD Run Number	100				
Date run completed	16-Oct-13				
Rig Bit Number	100				
Bit Size (in)	8.750				
Tool Nominal OD (in)	6.750				
Log Start Depth (MD, ft)	992.00				
Log End Depth (MD, ft)	7,948.00				
Drill or Wipe	Drill				
Drill/Wipe Start Date and Time	13-Oct-13 17:53				
Drill/Wipe End Date and Time	16-Oct-13 17:53				
Min Inc (deg) @ Depth (MD, ft)	0.34 @ 6,900.00				
Max Inc (deg) @ Depth (MD, ft)	86.11 @ 7,900.00				
Bit TFA(in2) / Bit Type	PDC / 1.04				
Flow Rate (gpm)	574.08				
Max AV (fpm) / CV (fpm) @ MWD	N/A / N/A				
Fluid Type	Native/Spud Mud				
Density (ppg) / Viscosity (spqt)	8.30 / 27.00				
Filtrate CL (ppm)	1,200.00				
pH / Fluid Loss (mptm)	8.90 / 0				
PV (cP) / YP (lbf2)	15 / 1.00				
% Solids / % Sand	1.5 / .03				
% Oil / Oil:Water Ratio	1.5 / 91				
Rm @ Measured Temp (degF)	N/A @ N/A				
Rmf @ Measured Temp (degF)	N/A @ N/A				
Rmc @ Measured Temp (degF)	N/A @ N/A				
Max Tool Temp (deg F)	177.04 / 329				

Max Tool Temp (degF) / Source	177.64 / PCM				
Rm @ Max Tool Temp (degF)	N/A @ 177.64				
Lead MWD Engineer	Reuben Edgington				
Customer Representative	Dave Cornett				

## SENSOR INFORMATION

### Directional Sensor Information

Tool Type	PCDC				
Distance From Bit (ft)	48.00				
Software Version	6.21				
Sub Serial Number	11404261				
Sonde Serial Number	11297555				
Sensor ID Number	N/A				
Toolface Offset (deg)	207.01				

### Gamma Ray Sensor Information

Tool Type	PCG				
Distance From Bit (ft)	51.18				
Recorded Sample Period (sec)	10				
Software Version	8.15				
Sub Serial Number	11404261				
Insert/Sonde Serial Number	12035849				

### Pulser Controller Sensor Information

Tool Type	PCM				
Software Version	5.76				
PIC Software Version	1.40				
Sub/HOC Serial Number	11404261				
Insert/Probe/Module SN	11400901				
Battery Serial Number	N/A				
Valve Insert SN	N/A				
DC Insert Serial Number	N/A				
Choke Size (32nd)	N/A				
Driver Current (amps)	N/A				
Driver SMI Current (amps)	N/A				
Boot Strap Version	4,130.00				

## REMARKS

1. All depths are true vertical bit depths, referenced to the Driller's pipe tally and are measured from the drill floor, unless otherwise specified.
- 2.No Depth correction have been made for pipe stretch or compression.
- 3.Critical annular velocities are calculated using the "power law" model for water based fluides.
4. Run 100 were drilled with directional data only.
5. All data presented is recorded data unless otherwise specified.
6. The following smoothing parameters have been applied to the data:

PCGR (Corrected Gamma Ray):  
Interval Resolution: 0.5 ft  
Interval Distance: 0.6 ft  
Gap Fill: 3.0 ft


Insite version: 8.0.0


WARRANTY


HALLIBURTON WILL USE ITS BEST EFFORTS TO FURNISH CUSTOMERS WITH ACCURATE INFORMATION AND INTERPRETATIONS THAT ARE PART OF, AND INCIDENT TO, THE SERVICES PROVIDED. HOWEVER, HALLIBURTON CANNOT AND DOES NOT WARRANT THE ACCURACY OR CORRECTNESS OF SUCH INFORMATION AND INTERPRETATIONS. UNDER NO CIRCUMSTANCES SHOULD ANY SUCH INFORMATION OR INTERPRETATION BE RELIED UPON AS THE SOLE BASIS FOR ANY DRILLING, COMPLETION, PRODUCTION, OR FINANCIAL DECISION OR ANY PROCEDURE INVOLVING ANY RISK TO THE SAFETY OF ANY DRILLING VENTURE, DRILLING RIG OR ITS CREW OR ANY OTHER THIRD PARTY. THE CUSTOMER HAS FULL RESPONSIBILITY FOR ALL DRILLING, COMPLETION AND PRODUCTION OPERATION. HALLIBURTON MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, WITH RESPECT TO THE SERVICES RENDERED. IN NO EVENT WILL HALLIBURTON BE LIABLE FOR FAILURE TO OBTAIN ANY PARTICULAR RESULTS OR FOR ANY DAMAGES, INCLUDING, BUT NOT LIMITED TO, INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES, RESULTING FROM THE USE OF ANY INFORMATION OR INTERPRETATION PROVIDED BY HALLIBURTON.


HALLIBURTON  
 Sperry Drilling Services  
 TVD Detail Log 1:240


Anadarko  
 Butterball 29C-15HZ  
 Xtreme 22  
 T2N-R67W





































Pason lost tracking


3450	3472	9.79	273.13	3446.48	-2.14
3500					
3550	3558	11.36	268.74	3531.02	-2.40
3600					
	3643	10.56	265.55	3614.47	-1.65
















































Kick off Build @ 6955' MD









926.00	0.46	258.52	925.99	1.34 N	1.58 W	-1.34	TIE-IN
1083.00	0.82	273.74	1082.98	1.29 N	3.32 W	-1.29	0.25
1174.00	0.99	274.28	1173.97	1.39 N	4.75 W	-1.39	0.19
1266.00	1.10	275.98	1265.95	1.54 N	6.42 W	-1.54	0.12
1359.00	1.13	206.94	1358.94	0.82 N	7.73 W	-0.82	1.36
1444.00	1.44	210.49	1443.92	0.85 S	8.65 W	0.85	0.38
1530.00	1.74	249.13	1529.89	2.25 S	10.42 W	2.25	1.27
1615.00	3.02	272.56	1614.81	2.61 S	13.86 W	2.61	1.86
1701.00	4.87	283.10	1700.61	1.68 S	19.68 W	1.68	2.30
1860.00	7.86	279.89	1858.61	1.72 N	36.97 W	-1.72	1.89
1952.00	9.51	284.07	1949.55	4.65 N	50.54 W	-4.65	1.92
2044.00	10.36	278.13	2040.17	7.66 N	66.10 W	-7.66	1.45
2137.00	11.07	266.86	2131.56	8.36 N	83.29 W	-8.36	2.37
2228.00	10.67	265.23	2220.93	7.18 N	100.41 W	-7.18	0.55
2320.00	10.36	267.13	2311.39	6.06 N	117.16 W	-6.06	0.51
2413.00	9.85	267.79	2402.94	5.33 N	133.46 W	-5.33	0.56
2505.00	9.18	267.13	2493.68	4.66 N	148.66 W	-4.66	0.74
2597.00	10.07	267.01	2584.38	3.87 N	164.02 W	-3.87	0.97
2689.00	9.84	268.66	2675.00	3.27 N	179.91 W	-3.27	0.40
2781.00	9.90	269.38	2765.63	3.00 N	195.68 W	-3.00	0.15
2873.00	9.83	270.30	2856.27	2.96 N	211.44 W	-2.96	0.19
2959.00	9.37	270.25	2941.07	3.02 N	225.78 W	-3.02	0.53
3045.00	10.20	266.55	3025.82	2.60 N	240.38 W	-2.60	1.21
3130.00	9.69	265.99	3109.54	1.64 N	255.03 W	-1.64	0.61
3215.00	9.97	269.53	3193.29	1.08 N	269.52 W	-1.08	0.78
3301.00	10.25	270.92	3277.96	1.15 N	284.62 W	-1.15	0.43
3387.00	9.50	271.86	3362.68	1.50 N	299.36 W	-1.50	0.89
3472.00	9.79	273.28	3446.48	2.14 N	313.59 W	-2.14	0.44
3558.00	11.36	268.90	3531.02	2.40 N	329.36 W	-2.40	2.05
3643.00	10.56	265.70	3614.47	1.65 N	345.50 W	-1.65	1.18
3729.00	9.66	264.63	3699.13	0.38 N	360.54 W	-0.38	1.07
3815.00	9.42	270.42	3783.95	0.24 S	374.76 W	0.24	1.15
3900.00	10.14	277.53	3867.71	0.79 N	389.13 W	-0.79	1.65
3986.00	9.23	277.86	3952.49	2.73 N	403.47 W	-2.73	1.06
4071.00	10.04	274.28	4036.29	4.21 N	417.61 W	-4.21	1.18
4157.00	9.83	273.57	4121.00	5.23 N	432.42 W	-5.23	0.28
4243.00	9.51	273.16	4205.78	6.08 N	446.84 W	-6.08	0.38
4329.00	8.53	273.30	4290.71	6.84 N	460.30 W	-6.84	1.14
4414.00	9.02	273.10	4374.72	7.56 N	473.24 W	-7.56	0.58
4500.00	9.83	274.76	4459.55	8.53 N	487.29 W	-8.53	0.99
4586.00	10.87	273.78	4544.15	9.68 N	502.70 W	-9.68	1.23
4671.00	10.60	273.99	4627.67	10.75 N	518.50 W	-10.75	0.32
4757.00	10.70	273.72	4712.19	11.82 N	534.35 W	-11.82	0.13
4843.00	10.07	273.25	4796.78	12.76 N	549.83 W	-12.76	0.74
4928.00	9.79	274.81	4880.50	13.79 N	564.45 W	-13.79	0.46
5014.00	10.40	269.50	4965.17	14.34 N	579.50 W	-14.34	1.29
5100.00	10.45	268.82	5049.75	14.11 N	595.06 W	-14.11	0.15
5186.00	9.89	268.16	5134.40	13.71 N	610.24 W	-13.71	0.67
5271.00	8.94	268.38	5218.26	13.29 N	624.13 W	-13.29	1.12
5357.00	8.82	265.67	5303.23	12.60 N	637.39 W	-12.60	0.51
5443.00	9.59	266.01	5388.12	11.60 N	651.11 W	-11.61	0.90
5528.00	10.35	265.73	5471.83	10.54 N	665.79 W	-10.54	0.90
5614.00	8.95	264.35	5556.61	9.31 N	680.15 W	-9.31	1.65
5700.00	9.47	266.51	5641.51	8.22 N	693.87 W	-8.22	0.73
5785.00	10.58	268.72	5725.21	7.62 N	708.65 W	-7.62	1.38
5871.00	9.43	265.67	5809.90	6.91 N	723.57 W	-6.91	1.47
5957.00	10.08	262.97	5894.65	5.46 N	738.06 W	-5.46	0.92
6042.00	9.33	268.83	5978.44	4.41 N	752.33 W	-4.41	1.46
6128.00	9.39	272.03	6063.29	4.51 N	766.32 W	-4.51	0.61
6214.00	9.24	272.40	6148.16	5.05 N	780.22 W	-5.05	0.19
6300.00	7.89	272.02	6233.20	5.55 N	793.02 W	-5.55	1.57
6386.00	6.75	270.53	6318.50	5.80 N	803.98 W	-5.80	1.34
6471.00	5.66	268.86	6403.00	5.77 N	813.16 W	-5.77	1.30
6557.00	5.01	281.75	6488.63	6.45 N	821.08 W	-6.45	1.58
6643.00	4.39	281.91	6574.34	7.89 N	827.98 W	-7.89	0.72
6728.00	3.22	275.11	6659.15	8.78 N	833.54 W	-8.78	1.47
6814.00	1.85	261.38	6745.06	8.78 N	837.32 W	-8.78	1.73
6900.00	0.34	229.51	6831.05	8.41 N	838.88 W	-8.41	1.83
6943.00	0.52	194.51	6874.05	8.14 N	839.03 W	-8.14	0.72
6986.00	4.32	181.17	6917.00	6.33 N	839.11 W	-6.33	8.87
7029.00	8.14	186.99	6959.74	1.69 N	839.51 W	-1.69	8.99
7072.00	12.06	185.25	7002.06	5.81 S	840.30 W	5.81	9.14

7072.00	12.00	183.23	7002.00	3.81 S	848.30 W	3.81	9.14
7114.00	15.92	188.20	7042.81	15.89 S	841.52 W	15.89	9.34
7157.00	20.27	184.37	7083.68	29.16 S	842.93 W	29.16	10.48
7200.00	25.30	180.43	7123.31	45.78 S	843.57 W	45.78	12.22
7243.00	27.49	177.27	7161.83	64.89 S	843.16 W	64.89	6.05
7286.00	31.04	178.09	7199.33	85.89 S	842.32 W	85.89	8.31
7329.00	35.69	181.55	7235.24	109.52 S	842.29 W	109.52	11.68
7371.00	40.07	183.96	7268.38	135.27 S	843.55 W	135.27	11.01
7414.00	45.31	184.03	7299.98	164.34 S	845.59 W	164.34	12.19
7457.00	49.58	183.24	7329.05	195.95 S	847.59 W	195.95	10.02
7500.00	51.54	181.26	7356.37	229.13 S	848.88 W	229.13	5.78
7543.00	52.56	179.24	7382.82	263.03 S	849.03 W	263.03	4.40
7586.00	57.47	178.31	7407.46	298.24 S	848.26 W	298.24	11.56
7629.00	61.62	180.10	7429.25	335.29 S	847.76 W	335.29	10.30
7672.00	65.51	181.10	7448.39	373.79 S	848.17 W	373.79	9.28
7714.00	69.47	180.51	7464.47	412.58 S	848.71 W	412.57	9.52
7757.00	73.34	179.65	7478.18	453.32 S	848.77 W	453.32	9.20
7800.00	77.98	179.20	7488.83	494.97 S	848.35 W	494.97	10.84
7843.00	82.98	178.87	7495.94	537.36 S	847.63 W	537.36	11.65
7900.00	86.11	178.58	7501.35	594.08 S	846.37 W	594.08	5.51

CALCULATION BASED ON MINIMUM CURVATURE METHOD  
 SURVEY COORDINATES RELATIVE TO WELL SYSTEM REFERENCE POINT  
 TVD VALUES GIVEN RELATIVE TO DRILLING MEASUREMENT POINT  
 VERTICAL SECTION RELATIVE TO WELL HEAD  
 VERTICAL SECTION IS COMPUTED ALONG A DIRECTION OF 180.00 DEGREES (TRUE)  
 A TOTAL CORRECTION OF 8.63 DEG FROM MAGNETIC NORTH TO TRUE NORTH HAS BEEN APPLIED  
 HORIZONTAL DISPLACEMENT IS RELATIVE TO THE WELL HEAD.  
 HORIZONTAL DISPLACEMENT(CLOSURE) AT 7900.00 FEET  
 IS 1034.05 FEET ALONG 234.93 DEGREES (TRUE)