

Company: ENCANA OIL & GAS (USA) INC

Well: HAGEN FEDERAL 22-4D (PC22)

Field: SOUTH PARACHUTE

County: GARFIELD State: COLORADO

SLIM CEMENT MAPPING LOG  
CBL-VDL  
GAMMA RAY-CCL

County: GARFIELD

Field: SOUTH PARACHUTE

Location: SHL: 607 FNL & 1762 FWL

Well: HAGEN FEDERAL 22-4D (PC22)

Company: ENCANA OIL & GAS (USA) INC

| LOCATION                 |               |                            |       |
|--------------------------|---------------|----------------------------|-------|
| SHL: 607 FNL & 1762 FWL  | Elev.: K.B.   | 6543.00 ft                 |       |
| BHL: 1187 FNL & 1123 FWL | G.L.          | 6521.00 ft                 |       |
|                          | D.F.          | 6542.00 ft                 |       |
| Permanent Datum:         | GROUND LEVEL  | Elev.: 6521.00 ft          |       |
| Log Measured From:       | KELLY BUSHING | 22.00 ft above Perm. Datum |       |
| Drilling Measured From:  | KELLY BUSHING |                            |       |
| API Serial No.           | Section       | Township                   | Range |
| 05-04522013-00           | 22            | 7S                         | 95W   |

|                               |                 |  |  |       |  |  |  |  |  |
|-------------------------------|-----------------|--|--|-------|--|--|--|--|--|
| Logging Date                  | 13-Sep-2013     |  |  |       |  |  |  |  |  |
| Run Number                    | 1               |  |  |       |  |  |  |  |  |
| Depth Driller                 | 7822 ft         |  |  |       |  |  |  |  |  |
| Schlumberger Depth            | 7725 ft         |  |  |       |  |  |  |  |  |
| Bottom Log Interval           | 7716 ft         |  |  |       |  |  |  |  |  |
| Top Log Interval              | 50 ft           |  |  |       |  |  |  |  |  |
| Casing Fluid Type             | FRESH WATER     |  |  |       |  |  |  |  |  |
| Salinity                      |                 |  |  |       |  |  |  |  |  |
| Density                       | 8.4 lbm/gal     |  |  |       |  |  |  |  |  |
| Fluid Level                   | 50 ft           |  |  |       |  |  |  |  |  |
| BIT/CASING/TUBING STRING      |                 |  |  |       |  |  |  |  |  |
| Bit Size                      | 8.750 in        |  |  |       |  |  |  |  |  |
| From                          | 22 ft           |  |  |       |  |  |  |  |  |
| To                            | 7822 ft         |  |  |       |  |  |  |  |  |
| Casing/Tubing Size            | 4.500 in        |  |  |       |  |  |  |  |  |
| Weight                        | 11.6 lbm/ft     |  |  |       |  |  |  |  |  |
| Grade                         | S-80            |  |  |       |  |  |  |  |  |
| From                          | 22 ft           |  |  |       |  |  |  |  |  |
| To                            | 7790 ft         |  |  |       |  |  |  |  |  |
| Maximum Recorded Temperatures | 218 degF        |  |  |       |  |  |  |  |  |
| Logger On Bottom              | 13-Sep-2013     |  |  | 18:00 |  |  |  |  |  |
| Unit Number                   | Location        |  |  |       |  |  |  |  |  |
| Recorded By                   | KIRSTIE BUNTING |  |  |       |  |  |  |  |  |
| Witnessed By                  | JIM DYKEMAN     |  |  |       |  |  |  |  |  |

| PVT DATA                      |  |  |  | Run 1   | Run 2 | Run 3 |
|-------------------------------|--|--|--|---------|-------|-------|
| Oil Density                   |  |  |  |         |       |       |
| Water Salinity                |  |  |  |         |       |       |
| Gas Gravity                   |  |  |  |         |       |       |
| Bo                            |  |  |  |         |       |       |
| Bw                            |  |  |  |         |       |       |
| 1/Bg                          |  |  |  |         |       |       |
| Bubble Point Pressure         |  |  |  |         |       |       |
| Bubble Point Temperature      |  |  |  |         |       |       |
| Solution GOR                  |  |  |  |         |       |       |
| Maximum Deviation             |  |  |  |         |       |       |
| CEMENTING DATA                |  |  |  |         |       |       |
| Primary/Squeeze               |  |  |  | Primary |       |       |
| Casing String No              |  |  |  |         |       |       |
| Lead Cement Type              |  |  |  |         |       |       |
| Volume                        |  |  |  |         |       |       |
| Density                       |  |  |  |         |       |       |
| Water Loss                    |  |  |  |         |       |       |
| Additives                     |  |  |  |         |       |       |
| Tail Cement Type              |  |  |  |         |       |       |
| Volume                        |  |  |  |         |       |       |
| Density                       |  |  |  |         |       |       |
| Water Loss                    |  |  |  |         |       |       |
| Additives                     |  |  |  |         |       |       |
| Expected Cement Top           |  |  |  |         |       |       |
| Logging Date                  |  |  |  |         |       |       |
| Run Number                    |  |  |  |         |       |       |
| Depth Driller                 |  |  |  |         |       |       |
| Schlumberger Depth            |  |  |  |         |       |       |
| Bottom Log Interval           |  |  |  |         |       |       |
| Top Log Interval              |  |  |  |         |       |       |
| Casing Fluid Type             |  |  |  |         |       |       |
| Salinity                      |  |  |  |         |       |       |
| Density                       |  |  |  |         |       |       |
| Fluid Level                   |  |  |  |         |       |       |
| BIT/CASING/TUBING STRING      |  |  |  |         |       |       |
| Bit Size                      |  |  |  |         |       |       |
| From                          |  |  |  |         |       |       |
| To                            |  |  |  |         |       |       |
| Casing/Tubing Size            |  |  |  |         |       |       |
| Weight                        |  |  |  |         |       |       |
| Grade                         |  |  |  |         |       |       |
| From                          |  |  |  |         |       |       |
| To                            |  |  |  |         |       |       |
| Maximum Recorded Temperatures |  |  |  |         |       |       |
| Logger On Bottom              |  |  |  |         |       |       |
| Unit Number                   |  |  |  |         |       |       |
| Recorded By                   |  |  |  |         |       |       |
| Witnessed By                  |  |  |  |         |       |       |

## DEPTH SUMMARY LISTING

Date Created: 14-AUG-2013 11:54:57

## Depth System Equipment

| Depth Measuring Device    |           | Tension Device                |            | Logging Cable  |          |
|---------------------------|-----------|-------------------------------|------------|--|----------|
| Type:                     | IDW-JB    | Type:                         | CMTD-B/A   | Type:  | 1-25ZT   |
| Serial Number:            | 6349      | Serial Number:                | 3421       | Serial Number:   | 112136   |
| Calibration Date:         | 7-31-2013 | Calibration Date:             | 14-AUG-201 | Length:  | 19000 FT |
| Calibrator Serial Number: |           | Calibrator Serial Number:     | 174878     | <div>Conveyance Method: Wireline</div> <div>Rig Type: LAND</div> |          |
| Calibration Cable Type:   | 1-25ZT    | Number of Calibration Points: | 10         |  |          |
| Wheel Correction 1:       | -5        | Calibration RMS:              | 3          |  |          |
| Wheel Correction 2:       | -4        | Calibration Peak Error:       | 8          |  |          |

## Depth Control Parameters

|                             |                       |
|-----------------------------|-----------------------|
| Log Sequence:               | First Log In the Well |
| Rig Up Length At Surface:   | 0.00 FT               |
| Rig Up Length At Bottom:    | 0.00 FT               |
| Rig Up Length Correction:   | 0.00 FT               |
| Stretch Correction:         |                       |
| Tool Zero Check At Surface: |                       |

## Depth Control Remarks

1. ALL SCHLUMBERGER DEPTH CONTROL PROCEDURES USED
2. IDW USED AS PRIMARY DEPTH REFERENCE
3. SPWT DRUM COUNTER USED AS SECONDARY DEPTH REFERENCE
- 4.
- 5.
- 6.

## DISCLAIMER

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

|  |                       |
|--|-----------------------|
| OTHER SERVICES1                          | OTHER SERVICES2       |
| OS1: RESERVOIR SATURATION                | OS1:                  |
| OS2: LOG                                 | OS2:                  |
| OS3: SIGMA MODE                          | OS3:                  |
| OS4:                                     | OS4:                  |
| OS5:                                     | OS5:                  |
| REMARKS: RUN NUMBER 1                    | REMARKS: RUN NUMBER 2 |
| FIRST RUN IN HOLE CORRELATED TO DOWN LOG |                       |
| TOOL RAN AS PER TOOL SKETCH              |                       |
|  |                       |
| ENTRANCE: 17:00                          |                       |
| TIME ON BOTTOM: 18:00                    |                       |
| EXIT: 20:00                              |                       |
|  |                       |

|   |  |
|---|--|
| MAXIMUM RECORDED TEMPERATURE: 218 DEGF                      |  |
| MAXIMUM RECORDED PRESSURE: 3254 PSIA                        |  |
|   |  |
| SHORT JOINTS: 5412 FT & 6398 FT                             |  |
|   |  |
| MAIN PASS LOGGED UNDER ZERO SURFACE PRESSURE                |  |
| EXPECTED CBL AMPLITUDE IN FREE PIPE IS 80MV                 |  |
|   |  |
| CREW: KBUNTING, KJOHNS, JMANN                               |  |
| THANK YOU FOR CHOOSING E&P WIRELINE, A SCHLUMBERGER COMPANY |  |


|   |       |      |   |       |      |
|---|-------|------|---|-------|------|
| RUN 1<br>SERVICE ORDER #:<br>PROGRAM VERSION:<br>FLUID LEVEL: |       |      | RUN 2<br>SERVICE ORDER #:<br>PROGRAM VERSION:<br>FLUID LEVEL: |       |      |
|   |       |      |   |       |      |
| LOGGED INTERVAL   | START | STOP | LOGGED INTERVAL   | START | STOP |
|   |       |      |   |       |      |
|   |       |      |   |       |      |
|   |       |      |   |       |      |
|   |       |      |   |       |      |


| EQUIPMENT | DESCRIPTION |
|-----------|-------------|
|           |             |

|     | RUN 1 | RUN 2 |
|-----|-------|-------|
| 1   | 1     | 1     |
| 2   | 1     | 1     |
| 3   | 1     | 1     |
| 4   | 1     | 1     |
| 5   | 1     | 1     |
| 6   | 1     | 1     |
| 7   | 1     | 1     |
| 8   | 1     | 1     |
| 9   | 1     | 1     |
| 10  | 1     | 1     |
| 11  | 1     | 1     |
| 12  | 1     | 1     |
| 13  | 1     | 1     |
| 14  | 1     | 1     |
| 15  | 1     | 1     |
| 16  | 1     | 1     |
| 17  | 1     | 1     |
| 18  | 1     | 1     |
| 19  | 1     | 1     |
| 20  | 1     | 1     |
| 21  | 1     | 1     |
| 22  | 1     | 1     |
| 23  | 1     | 1     |
| 24  | 1     | 1     |
| 25  | 1     | 1     |
| 26  | 1     | 1     |
| 27  | 1     | 1     |
| 28  | 1     | 1     |
| 29  | 1     | 1     |
| 30  | 1     | 1     |
| 31  | 1     | 1     |
| 32  | 1     | 1     |
| 33  | 1     | 1     |
| 34  | 1     | 1     |
| 35  | 1     | 1     |
| 36  | 1     | 1     |
| 37  | 1     | 1     |
| 38  | 1     | 1     |
| 39  | 1     | 1     |
| 40  | 1     | 1     |
| 41  | 1     | 1     |
| 42  | 1     | 1     |
| 43  | 1     | 1     |
| 44  | 1     | 1     |
| 45  | 1     | 1     |
| 46  | 1     | 1     |
| 47  | 1     | 1     |
| 48  | 1     | 1     |
| 49  | 1     | 1     |
| 50  | 1     | 1     |
| 51  | 1     | 1     |
| 52  | 1     | 1     |
| 53  | 1     | 1     |
| 54  | 1     | 1     |
| 55  | 1     | 1     |
| 56  | 1     | 1     |
| 57  | 1     | 1     |
| 58  | 1     | 1     |
| 59  | 1     | 1     |
| 60  | 1     | 1     |
| 61  | 1     | 1     |
| 62  | 1     | 1     |
| 63  | 1     | 1     |
| 64  | 1     | 1     |
| 65  | 1     | 1     |
| 66  | 1     | 1     |
| 67  | 1     | 1     |
| 68  | 1     | 1     |
| 69  | 1     | 1     |
| 70  | 1     | 1     |
| 71  | 1     | 1     |
| 72  | 1     | 1     |
| 73  | 1     | 1     |
| 74  | 1     | 1     |
| 75  | 1     | 1     |
| 76  | 1     | 1     |
| 77  | 1     | 1     |
| 78  | 1     | 1     |
| 79  | 1     | 1     |
| 80  | 1     | 1     |
| 81  | 1     | 1     |
| 82  | 1     | 1     |
| 83  | 1     | 1     |
| 84  | 1     | 1     |
| 85  | 1     | 1     |
| 86  | 1     | 1     |
| 87  | 1     | 1     |
| 88  | 1     | 1     |
| 89  | 1     | 1     |
| 90  | 1     | 1     |
| 91  | 1     | 1     |
| 92  | 1     | 1     |
| 93  | 1     | 1     |
| 94  | 1     | 1     |
| 95  | 1     | 1     |
| 96  | 1     | 1     |
| 97  | 1     | 1     |
| 98  | 1     | 1     |
| 99  | 1     | 1     |
| 100 | 1     | 1     |


|                   |  |  |
|-------------------|--|--|
| SURFACE EQUIPMENT |  |  |
| WITM-A            |  |  |
| PSC_16MHZ         |  |  |


## DOWNHOLE EQUIPMENT




































































































SHORT JOINT




































Date of Master Calibration 6-MAR-2012

CBL Correction Factor 0.0704263

CBL Adjustment Factor (CBAF) 1.0

MAP 1 Correction Factor 0.0993191

MAP Adjustment Factor (MPAF) 1.0

MAP 2 Correction Factor 0.0941329

MAP 3 Correction Factor 0.101552

MAP 4 Correction Factor 0.114415

MAP 5 Correction Factor 0.127992

MAP 6 Correction Factor 0.121190

MAP 7 Correction Factor 0.112867

MAP 8 Correction Factor 0.102913

## Parameters

| DLIS Name                                     | Description  | Value     |      |
|---|--|-----------|------|
| SCMT-CB: Slim Cement Mapping Tool, 1-11/16 OD |  |           |      |
| BILI  | Bond Index Level for Zone Isolation                  | 0.8       |      |
| CB3D  | SCMT CBL 3 ft Peak Detection Mode                    | PEAK      |      |
| CB3G  | SCMT CBL 3 ft Peak Detection T0_Delay and Noise Gate | 224.559   | US   |
| CB3T  | SCMT CBL 3 ft Fixed Threshold Level                  | 20        | MV   |
| CB5D  | SCMT CBL 5 ft Peak Detection Mode                    | PEAK      |      |
| CB5G  | SCMT CBL 5 ft Peak Detection T0_Delay and Noise Gate | 338.559   | US   |
| CB5T  | SCMT CBL 5 ft Fixed Threshold Level                  | 20        | MV   |
| CBLG  | CBL Gate Width                                       | 45        | US   |
| CBRA  | CBL LQC Reference Amplitude in Free Pipe             | 80        | MV   |
| CMCF  | CBL Cement Type Compensation Factor                  | 1         |      |
| CMT C   | SCMT Slow Channel Multiplexer Mode                   | SCAN      |      |
| CMTM  | SCMT Operating Mode                                  | LOG       |      |
| CSCS  | SCMT Slow Channel Index                              | VCC       |      |
| CTHI  | Casing Thickness                                     | 0.255617  | IN   |
| DTF   | Delta-T Fluid  | 189       | US/F |
| FATT  | Acoustic Attenuation due to Fluid                    | 0         | DB/F |
| FCF   | CBL Fluid Compensation Factor                        | 0.924277  |      |
| GOBO  | Good Bond  | 1.55185   | MV   |
| MAPD  | SCMT MAP Peak Detection Mode                         | PEAK      |      |
| MAPG  | SCMT MAP Peak Detection T0_Delay and Noise Gate      | 167.559   | US   |
| MAPT  | SCMT MAP Fixed Threshold Level                       | 30        | MV   |
| MATT  | Maximum Attenuation                                  | 16.5449   | DB/F |
| MCCF  | MAP Cement Type Compensation Factor                  | 1         |      |
| MCI   | Minimum Cemented Interval for Isolation              | 1.25      | FT   |
| MMSA  | MAP Minimum Sonic Amplitude                          | 4.32284   | MV   |
| MSA   | Minimum Sonic Amplitude                              | 0.579149  | MV   |
| PEDE  | Peak Detection On/Off Switch in Playback             | OFF       |      |
| VDLG  | VDL Manual Gain                                      | 5         |      |
| ZCMT  | Acoustic Impedance of Cement                         | 6.8       | MRAY |
| System and Miscellaneous                      |  |           |      |
| CSIZ  | Current Casing Size                                  | 4.500     | IN   |
| CWEI  | Casing Weight  | 11.60     | LB/F |
| DFD   | Drilling Fluid Density                               | 8.40      | LB/G |
| DO  | Depth Offset for Playback                            | 2.0       | FT   |
| PP  | Playback Processing                                  | RECOMPUTE |      |
| TD  | Total Depth  | 7725      | FT   |

## Input DLIS Files

|         |                            |      |          |                   |           |          |
|---------|----------------------------|------|----------|-------------------|-----------|----------|
| DEFAULT | Splice_SCMT_RST_PSP_031CUP | FN:1 | PRODUCER | 13-Sep-2013 20:14 | 7731.5 FT | -36.4 FT |
|---------|----------------------------|------|----------|-------------------|-----------|----------|

## Output DLIS Files

|         |                     |       |          |                   |
|---------|---------------------|-------|----------|-------------------|
| DEFAULT | SCMT_RST_PSP_032PUP | FN:30 | PRODUCER | 13-Sep-2013 20:16 |
|---------|---------------------|-------|----------|-------------------|



REPEAT ANALYSIS CBL VDL

Input DLIS Files

|         |                     |       |          |                   |           |           |
|---------|---------------------|-------|----------|-------------------|-----------|-----------|
| DEFAULT | SCMT_RST_PSP_025LUP | FN:24 | PRODUCER | 13-Sep-2013 17:40 | 5766.5 FT | 5357.0 FT |
| DEFAULT | SCMT_RST_PSP_032PUP | FN:30 | PRODUCER | 13-Sep-2013 20:16 | 7733.5 FT | -85.5 FT  |

Output DLIS Files


|         |                     |       |          |                   |           |           |
|---------|---------------------|-------|----------|-------------------|-----------|-----------|
| DEFAULT | SCMT_RST_PSP_033PUP | FN:31 | PRODUCER | 13-Sep-2013 20:21 | 5766.5 FT | 5305.5 FT |
|---------|---------------------|-------|----------|-------------------|-----------|-----------|


OP System Version: 19C0-187

|         |          |       |          |
|---------|----------|-------|----------|
| SCMT-CB | 19C0-187 | RST-C | 19C0-187 |
| PSPT    | 19C0-187 |       |          |



PIP SUMMARY

Time Mark Every 60 S









PIP SUMMARY

Time Mark Every 60 S

Format: CBL\_VDL\_REP Vertical Scale: 5" per 100'

Graphics File Created: 13-Sep-2013 20:21

OP System Version: 19C0-187

|         |          |       |          |
|---------|----------|-------|----------|
| SCMT-CB | 19C0-187 | RST-C | 19C0-187 |
| PSPT    | 19C0-187 |       |          |

<<<SCMT Cement Evaluation Information Summary>>>

|                     |              |
|---------------------|--------------|
| Sonde Serial Number | SCMS-CB 8179 |
| Current Casing Size | 4.50000 IN   |
| Casing Weight       | 11.6000 LB/F |


|  |  |            |                                 |  |                           |  |
|--|--|------------|---------------------------------|--|---------------------------|--|
| Expected CBL Amplitude<br>in Free Pipe Section |  | 80 MV      | Minimum Sonic Amplitude         |  | 0.579149 MV (100% Cement) |  |
|  |  |            | MAP Minimum Sonic Amplitude     |  | 1.55185 MV (80% Cement)   |  |
|  |  |            |                                 |  | 4.32284 MV (100% Cement)  |  |
|  |  |            |                                 |  | 8.10244 MV (80% Cement)   |  |
| Master Calibration (Normalization)             |  |            | Before Calibration (Adjustment) |  |                           |  |
| Date of Master Calibration                     |  | 6–MAR–2012 |                                 |  |                           |  |
| CBL Correction Factor                          |  | 0.0704263  | CBL Adjustment Factor (CBAF)    |  | 1.0                       |  |
| MAP 1 Correction Factor                        |  | 0.0993191  | MAP Adjustment Factor (MPAF)    |  | 1.0                       |  |
| MAP 2 Correction Factor                        |  | 0.0941329  |                                 |  |                           |  |
| MAP 3 Correction Factor                        |  | 0.101552   |                                 |  |                           |  |
| MAP 4 Correction Factor                        |  | 0.114415   |                                 |  |                           |  |
| MAP 5 Correction Factor                        |  | 0.127992   |                                 |  |                           |  |
| MAP 6 Correction Factor                        |  | 0.121190   |                                 |  |                           |  |
| MAP 7 Correction Factor                        |  | 0.112867   |                                 |  |                           |  |
| MAP 8 Correction Factor                        |  | 0.102913   |                                 |  |                           |  |

| Parameters                                    |  |           |      |
|---|--|-----------|------|
| DLIS Name                                     | Description  | Value     |      |
| SCMT–CB: Slim Cement Mapping Tool, 1–11/16 OD |  |           |      |
| BILI  | Bond Index Level for Zone Isolation                  | 0.8       |      |
| CB3D  | SCMT CBL 3 ft Peak Detection Mode                    | PEAK      |      |
| CB3G  | SCMT CBL 3 ft Peak Detection T0_Delay and Noise Gate | 224.559   | US   |
| CB3T  | SCMT CBL 3 ft Fixed Threshold Level                  | 20        | MV   |
| CB5D  | SCMT CBL 5 ft Peak Detection Mode                    | PEAK      |      |
| CB5G  | SCMT CBL 5 ft Peak Detection T0_Delay and Noise Gate | 338.559   | US   |
| CB5T  | SCMT CBL 5 ft Fixed Threshold Level                  | 20        | MV   |
| CBLG  | CBL Gate Width                                       | 45        | US   |
| CBRA  | CBL LQC Reference Amplitude in Free Pipe             | 80        | MV   |
| CMCF  | CBL Cement Type Compensation Factor                  | 1         |      |
| CMTC  | SCMT Slow Channel Multiplexer Mode                   | SCAN      |      |
| CMTM  | SCMT Operating Mode                                  | LOG       |      |
| CSCS  | SCMT Slow Channel Index                              | VCC       |      |
| CTHI  | Casing Thickness                                     | 0.255617  | IN   |
| DTF   | Delta–T Fluid  | 189       | US/F |
| FATT  | Acoustic Attenuation due to Fluid                    | 0         | DB/F |
| FCF   | CBL Fluid Compensation Factor                        | 0.924277  |      |
| GOBO  | Good Bond  | 1.55185   | MV   |
| MAPD  | SCMT MAP Peak Detection Mode                         | PEAK      |      |
| MAPG  | SCMT MAP Peak Detection T0_Delay and Noise Gate      | 167.559   | US   |
| MAPT  | SCMT MAP Fixed Threshold Level                       | 30        | MV   |
| MATT  | Maximum Attenuation                                  | 16.5449   | DB/F |
| MCCF  | MAP Cement Type Compensation Factor                  | 1         |      |
| MCI   | Minimum Cemented Interval for Isolation              | 1.25      | FT   |
| MMSA  | MAP Minimum Sonic Amplitude                          | 4.32284   | MV   |
| MSA   | Minimum Sonic Amplitude                              | 0.579149  | MV   |
| PEDE  | Peak Detection On/Off Switch in Playback             | OFF       |      |
| VDLG  | VDL Manual Gain                                      | 5         |      |
| ZCMT  | Acoustic Impedance of Cement                         | 6.8       | MRAY |
| System and Miscellaneous                      |  |           |      |
| CSIZ  | Current Casing Size                                  | 4.500     | IN   |
| CWEI  | Casing Weight  | 11.60     | LB/F |
| DFD   | Drilling Fluid Density                               | 8.40      | LB/G |
| DO  | Depth Offset for Playback                            | 0.0       | FT   |
| DORL  | Depth Offset for Repeat Analysis                     | 0.0       | FT   |
| PP  | Playback Processing                                  | RECOMPUTE |      |
| TD  | Total Depth  | 7725      | FT   |

| Input DLIS Files  |                     |       |          |                   |           |           |
|-------------------|---------------------|-------|----------|-------------------|-----------|-----------|
| DEFAULT           | SCMT_RST_PSP_025LUP | FN:24 | PRODUCER | 13–Sep–2013 17:40 | 5766.5 FT | 5357.0 FT |
| DEFAULT           | SCMT_RST_PSP_032PUP | FN:30 | PRODUCER | 13–Sep–2013 20:16 | 7733.5 FT | –85.5 FT  |
| Output DLIS Files |                     |       |          |                   |           |           |
| DEFAULT           | SCMT_RST_PSP_033PUP | FN:31 | PRODUCER | 13–Sep–2013 20:21 |           |           |

MAXIS Field Log

Index: 7733.5 – -85.5 FT



15468 Points Plotted

13-SEP-2013 20:20

Client: ENCANA OIL & GAS (USA) INC

Field: SOUTH PARACHUTE

Well: HAGEN FEDERAL 22-4D (PC22)

Run date: 13-Sep-2013

Tool: PSP

Sub Type: PBMS

Sensor: GR

PBMS Gamma Ray

Sonde Serial NB

Sensor Serial NB

Calib Date ddmmyy

Matrix Size

Coeff CRC

RESISTORS FOR GR SENSOR N.33223,TOOL PBMS-BA0928. SENSOR S/N:

33223

090800

12

CFE2

GR HV Rt

Rt\*\*0

Rt\*\*1

Rt\*\*0

+.182000000000e+04

+.332000000000e+04

Client: ENCANA OIL & GAS (USA) INC

Field: SOUTH PARACHUTE

Well: HAGEN FEDERAL 22-4D (PC22)

Run date: 13-Sep-2013

Tool: PSP

Sub Type: PBMS

Sensor: WellTemp RTD

PBMS RTD Well Thermometer

Sonde Serial NB

Sensor Serial NB

Calib Date ddmmyy

Matrix Size

Coeff CRC

COEFFICIENTS FOR RTD THERMOMETER PBMS-B.928 S/N:

928

280612

16

A24E

WTemp Coeff

Tt\*\*0

Tt\*\*1

Tt\*\*2



|       |                     |                     |                    |
|-------|---------------------|---------------------|--------------------|
| Tt**0 | −.391987973189E+03  | + .191346892512E+03 | −.440920753451E+02 |
|       | Tt**3               | Tt**4               | Tt**5              |
| Tt**0 | + .957191300908E+01 | −.711421725686E+00  | 0.0                |

|           |                            |           |      |
|-----------|----------------------------|-----------|------|
| Client:   | ENCANA OIL & GAS (USA) INC | Tool:     | PSP  |
| Field:    | SOUTH PARACHUTE            | Sub Type: | PBMS |
| Well:     | HAGEN FEDERAL 22–4D (PC22) | Sensor:   | CQG  |
| Run date: | 13–Sep–2013                |           |      |

PBMS Quartz Gauge type F

Sonde Serial NB

Sensor Serial NB

Calib Date ddmmyy

Matrix Size

Coeff CRC

COEFFICIENTS FOR CQG PBMS–B.928 S/N:

928

280612

66

9DC3

Pres Coeff

|       |                     |                     |                     |
|-------|---------------------|---------------------|---------------------|
|       | Fb**0               | Fb**1               | Fb**2               |
| Fc**0 | + .714463802232E+04 | + .183434658655E–01 | −.156620073569E–06  |
| Fc**1 | −.100638308957E+01  | −.119899563644E–04  | −.912155899025E–10  |
| Fc**2 | + .936268101283E–06 | + .423898071451E–10 | + .958076371919E–15 |
| Fc**3 | + .185123362373E–11 | + .203107925433E–15 | 0.0                 |
| Fc**4 | 0.0                 | 0.0                 | 0.0                 |
| Fc**5 | 0.0                 | 0.0                 | 0.0                 |

|       |                    |                     |                    |
|-------|--------------------|---------------------|--------------------|
|       | Fb**3              | Fb**4               | Fb**5              |
| Fc**0 | −.746577997611E–10 | −.588773826860E–15  | −.622250441458E–19 |
| Fc**1 | −.120636521092E–15 | + .400325894750E–19 | 0.0                |
| Fc**2 | 0.0                | 0.0                 | 0.0                |
| Fc**3 | 0.0                | 0.0                 | 0.0                |
| Fc**4 | 0.0                | 0.0                 | 0.0                |
| Fc**5 | 0.0                | 0.0                 | 0.0                |

PBMS Quartz Gauge type F

Sonde Serial NB :  
Sensor Serial NB 928  
Calib Date ddmmyy 280612  
Matrix Size 66  
Coeff CRC 283B

Temp Coeff

|       | Fc**0              | Fc**1              | Fc**2              |
|-------|--------------------|--------------------|--------------------|
| Fb**0 | +.117016867873E+03 | -.284359629614E-03 | +.604391180345E-08 |
| Fb**1 | -.598309140812E-02 | +.182731130848E-07 | +.160166486172E-12 |
| Fb**2 | -.307621454576E-07 | +.300601550309E-12 | +.311233548560E-17 |
| Fb**3 | -.419658736767E-12 | +.117473708647E-16 | 0.0                |
| Fb**4 | 0.0                | 0.0                | 0.0                |
| Fb**5 | 0.0                | 0.0                | 0.0                |
|       | Fc**3              | Fc**4              | Fc**5              |
| Fb**0 | +.114322792679E-12 | +.153807711176E-17 | -.736714260866E-21 |
| Fb**1 | -.528037875456E-18 | -.220337637519E-21 | 0.0                |
| Fb**2 | 0.0                | 0.0                | 0.0                |
| Fb**3 | 0.0                | 0.0                | 0.0                |
| Fb**4 | 0.0                | 0.0                | 0.0                |
| Fb**5 | 0.0                | 0.0                | 0.0                |

PBMS Quartz Gauge type F

Sonde Serial NB :  
Sensor Serial NB 928  
Calib Date ddmmyy 280612  
Matrix Size 16  
Coeff CRC 093F

Clock Freq Coeff

|              | (Fb'-Fc')**0       | (Fb'-Fc')**1       | (Fb'-Fc')**2       |
|--------------|--------------------|--------------------|--------------------|
| (Fb'-Fc')**0 | +.310874009898E+05 | +.288920923041E-02 | +.697940727038E-06 |
|              | (Fb'-Fc')**3       | (Fb'-Fc')**4       | (Fb'-Fc')**5       |
| (Fb'-Fc')**0 | -.657432344763E-10 | -.412920638782E-15 | +.213369826099E-20 |

PBMS Quartz Gauge type F

Sonde Serial NB :  
Sensor Serial NB 928  
Calib Date ddmmyy 280612



Company: ENCANA OIL & GAS (USA) INC

Schlumberger

Well: HAGEN FEDERAL 22-4D (PC22)

Field: SOUTH PARACHUTE

County: GARFIELD

State: COLORADO

SLIM CEMENT MAPPING LOG

CBL-VDL

GAMMA RAY-CCL