



SUMMARY OF ROUTINE CORE ANALYSES RESULTS

Vacuum Oven Dried at 180° F Net Confining Stress: 1,665 psi

Whiting Oil and Gas Corporation
Wildhorse 16-13L Well
Undisclosed Field

Weld County, Colorado
File No.: CO-65139
Date: 8/30/2013

Core Number	Sample Number	Sample Depth, feet	Permeability, millidarcys		Porosity, percent		Grain Density, gm/cc	Fluid Saturations, percent		
			to Air	Klinkenberg	Ambient	NCS		Water	Oil	Total
1	1-13	6,162.70	0.0027	0.0009	12.5	12.3	2.70	12.4	53.0	65.4
1	1-22	6,171.45	0.0018	0.0005	9.7	9.5	2.71	11.3	54.4	65.7
1	1-36c	6,185.20	+		12.0		2.71	28.4	45.7	74.2
1	1-52(F)	6,201.10	+		8.6		2.65	28.8	48.9	77.8
1	1-55c	6,204.85	+		7.8		2.62	26.2	66.4	92.6
1	1-84c	6,233.50	+		12.0		2.67	12.0	61.0	73.1
1	1-90(F)	6,239.50	+		7.4		2.58	21.2	67.9	89.0
1	1-109	6,258.60	0.0013	0.0003	11.6	11.5	2.67	22.2	53.5	75.6
1	1-119c	6,268.75	+		13.7		2.68	4.2	60.6	64.8
3	3-1(F)	7,525.30	+		4.2		2.71	86.5	4.5	91.0
3	3-2	7,526.70	<0.0001		5.1	5.0	2.71	83.1	15.6	98.7
3	3-3	7,527.50	0.0009	0.0002	2.6	2.5	2.81	68.1	30.7	98.8
3	3-4	7,528.30	0.0030	0.0010	3.8	3.7	2.68	67.0	20.5	87.5
3	3-5	7,529.50	0.0081	0.0034	1.1	1.0	2.92			**
3	3-6(F)	7,530.50	+		4.7		2.69	94.1	0.0	94.1
3	3-7	7,531.50	0.0008	0.0002	0.3	0.3	2.96			**
3	3-8	7,532.50	0.026	0.014	1.5	1.5	2.73			**
3	3-9	7,533.50	0.016	0.0077	1.9	1.8	2.72			**
3	3-10	7,534.70	0.946	0.690	8.0	7.9	2.66	36.9	12.5	49.3
3	3-11	7,535.50	0.169	0.119	11.3	11.1	2.67	60.1	4.8	64.8
3	3-12	7,536.50	0.069	0.044	9.8	9.7	2.66	57.1	2.6	59.6
3	3-13	7,537.50	0.0006	0.0001	3.6	3.6	2.69	83.9	13.8	97.7
3	3-14	7,538.50	0.0059	0.0023	7.9	7.8	2.66	85.7	1.4	87.0
3	3-15	7,539.50	0.0070	0.0029	8.0	7.9	2.67	76.2	5.2	81.5
3	3-16	7,540.50	30.6	25.9	18.4	18.2	2.66	60.3	2.9	63.3
3	3-17	7,541.70	192.	175.	16.3	16.1	2.69	58.2	8.4	66.6
3	3-18	7,542.50	0.958	0.733	8.2	8.1	2.71	59.9	4.0	63.9
3	3-19	7,543.40	2.28	1.80	10.1	9.9	2.71	59.4	5.6	65.0
3	3-20c	7,544.70	153.	139.	22.4		2.67	79.3	5.2	84.5
3	3-21	7,545.30	50.4	43.5	15.1	14.9	2.69	74.9	3.4	78.4
3	3-22	7,546.50	26.4	22.2	13.6	13.4	2.70	63.8	3.9	67.6
3	3-23	7,547.20	93.4	82.6	21.0	20.8	2.68	61.3	5.2	66.5
3	3-24	7,548.70	144.	130.	23.5	23.3	2.65	84.3	1.4	85.7
3	3-25(F)	7,549.50	+		22.8		2.66	69.0	5.1	74.2
3	3-26	7,550.50	64.1	55.7	21.3	21.1	2.66	61.9	1.9	63.8
3	3-28	7,552.40	40.2	34.5	13.2	13.0	2.69	59.9	2.9	62.8
3	3-32	7,556.80	8.38	6.86	13.6	13.4	2.67	61.1	1.3	62.4
3	3-33	7,557.50	60.9	52.9	17.2	17.0	2.65	56.3	1.2	57.5
3	3-34	7,558.50	38.7	32.9	18.0	17.8	2.65	57.4	2.1	59.5
3	3-35	7,559.40	80.8	71.3	19.3	19.1	2.65	56.8	1.9	58.6
3	3-36	7,560.70	6.75	5.44	15.1	14.9	2.66	59.0	0.5	59.5
3	3-37	7,561.50	8.36	6.80	15.3	15.1	2.65	64.5	3.0	67.5
3	3-38	7,562.50	55.8	48.5	16.8	16.6	2.65	60.8	2.4	63.2
3	3-39	7,563.50	6.78	5.50	10.1	10.0	2.69	58.9	0.2	59.1



SUMMARY OF ROUTINE CORE ANALYSES RESULTS

Vacuum Oven Dried at 180° F Net Confining Stress: 1,665 psi

Whiting Oil and Gas Corporation
 Wildhorse 16-13L Well
 Undisclosed Field

Weld County, Colorado
 File No.: CO-65139
 Date: 8/30/2013

Core Number	Sample Number	Sample Depth, feet	Permeability, millidarcys		Porosity, percent		Grain Density, gm/cc	Fluid Saturations, percent		
			to Air	Klinkenberg	Ambient	NCS		Water	Oil	Total
3	3-40	7,564.50	25.1	21.1	17.2	17.0	2.66	62.8	1.2	64.0
3	3-41	7,565.50	48.9	42.3	19.7	19.5	2.65	54.8	1.5	56.3
3	3-42	7,566.50	60.3	52.6	19.5	19.3	2.66	53.4	1.4	54.8
3	3-43	7,567.50	31.8	27.0	19.7	19.5	2.65	63.3	1.5	64.8
3	3-44	7,568.50	13.1	10.8	16.4	16.2	2.65	59.3	1.4	60.7
3	3-45	7,569.50	25.2	21.3	17.6	17.4	2.66	67.2	0.9	68.1
3	3-46	7,570.50	24.1	20.3	19.2	19.0	2.66	62.6	1.8	64.4
3	3-47	7,571.50	18.9	15.8	18.4	18.2	2.67	63.2	0.6	63.8
3	3-48	7,572.50	24.7	20.8	17.9	17.7	2.66	60.5	0.4	60.9
3	3-49	7,573.50	22.0	18.5	18.1	17.9	2.66	65.8	0.0	65.8
3	3-50	7,574.50	60.9	53.2	19.7	19.5	2.66	62.0	1.0	63.0
3	3-51	7,575.50	9.23	7.23	16.5	16.3	2.66	62.2	2.5	64.7
3	3-52	7,576.50	11.1	9.12	15.3	15.1	2.67	64.3	0.3	64.6
3	3-53	7,577.50	28.7	24.3	17.9	17.7	2.66	62.4	0.5	62.8
3	3-54	7,578.50	10.2	8.30	17.1	16.9	2.66	56.9	2.1	59.0
3	3-55	7,579.50	67.2	58.9	19.9	19.7	2.66	50.8	1.5	52.4
3	3-56	7,580.30	28.3	24.0	18.7	18.5	2.66	62.7	1.0	63.7
3	3-61	7,585.50	26.3	22.2	18.5	18.3	2.67	55.4	7.6	62.9
4	4-1	8,150.30	2.94	2.28	10.0	9.9	2.64	36.3	9.5	45.7
4	4-2	8,151.80	1.35	1.06	3.8	3.8	2.69	31.4	2.2	33.7
4	4-3	8,152.40	0.020	0.010	4.4	4.3	2.68	36.3	2.6	38.9
4	4-4	8,153.50	0.040	0.023	3.3	3.3	2.70			**
4	4-5	8,154.60	0.030	0.017	3.7	3.6	2.69			**
4	4-6	8,155.50	0.029	0.016	7.7	7.5	2.64			**
4	4-7(f)	8,156.40	1.57	1.17	8.7	8.6	2.65	39.5	2.5	42.0
4	4-8	8,157.70	0.027	0.014	5.3	5.2	2.68			**
4	4-9(F)	8,158.50		+	3.3		2.70			**
4	4-10	8,159.50	0.012	0.0055	1.8	1.7	2.72			**
4	4-11	8,160.50	0.017	0.0084	1.5	1.4	2.73			**
4	4-12	8,161.50	0.011	0.0049	1.4	1.3	2.75			**
4	4-13	8,162.30	0.021	0.011	1.3	1.2	2.74			**
4	4-14	8,163.60	6.16	4.95	6.8	6.7	2.65	70.2	6.7	77.0
4	4-15	8,164.50	0.041	0.024	7.1	7.0	2.65	63.2	8.0	71.2
4	4-16	8,165.70	5.82	4.59	8.2	8.1	2.67	61.2	9.9	71.1
4	4-17	8,166.30	0.026	0.014	3.1	3.0	2.70	37.0	4.8	41.8
4	4-18	8,167.70	0.072	0.046	5.6	5.5	2.67	62.8	1.2	64.0
4	4-19	8,168.50	0.0070	0.0029	5.4	5.3	2.67	62.6	14.4	77.0
4	4-20	8,169.50	0.054	0.033	5.9	5.8	2.68	62.1	2.3	64.4
4	4-21	8,170.30	0.209	0.151	7.0	6.8	2.66	49.2	6.9	56.2
4	4-22	8,171.50	0.326	0.245	5.5	5.4	2.67	46.4	2.0	48.3
4	4-23	8,172.40	0.152	0.106	3.7	3.6	2.71	43.1	2.2	45.4
4	4-24	8,173.70	1.89	1.49	6.7	6.6	2.68	54.7	2.0	56.7
4	4-25	8,174.30	0.276	0.205	4.9	4.8	2.69	38.4	8.4	46.7
4	4-26(F)	8,175.30		+	9.8		2.66	50.9	2.6	53.5



SUMMARY OF ROUTINE CORE ANALYSES RESULTS

Vacuum Oven Dried at 180° F Net Confining Stress: 1,665 psi

Whiting Oil and Gas Corporation
 Wildhorse 16-13L Well
 Undisclosed Field

Weld County, Colorado
 File No.: CO-65139
 Date: 8/30/2013

Core Number	Sample Number	Sample Depth, feet	Permeability, millidarcys		Porosity, percent		Grain Density, gm/cc	Fluid Saturations, percent		
			to Air	Klinkenberg	Ambient	NCS		Water	Oil	Total
4	4-27	8,176.40	0.033	0.019	2.7	2.6	2.74	36.1	12.4	48.5
4	4-28c	8,177.30		+	6.7		2.66	63.8	2.4	66.2
4	4-29	8,178.20	2.85	2.23	5.7	5.6	2.69	53.9	6.0	59.9
4	4-30	8,179.80	4.99	3.96	6.9	6.8	2.65	50.9	0.0	50.9
4	4-32	8,181.40	0.021	0.011	2.2	2.2	2.74			**
4	4-33	8,182.50	0.017	0.0084	1.7	1.6	2.74			**
4	4-34	8,183.70	0.0041	0.0015	1.8	1.8	2.67			**
4	4-35	8,184.70	0.0007	0.0001	3.3	3.2	2.67	87.8	4.3	92.1
4	4-36	8,185.50	0.0015	0.0004	4.3	4.2	2.67	67.5	10.6	78.1
4	4-37	8,186.50	0.0012	0.0003	4.5	4.4	2.67	75.3	3.2	78.5
4	4-38	8,187.50	0.0016	0.0004	3.5	3.4	2.68	75.1	1.0	76.1
4	4-39	8,188.50	0.0023	0.0007	5.1	5.0	2.68	79.9	2.6	82.6
4	4-40	8,189.50	0.0020	0.0006	4.5	4.4	2.69	65.7	22.3	87.9
4	4-41	8,190.50	0.0023	0.0007	4.8	4.7	2.68	70.5	10.3	80.9
4	4-42	8,191.40	0.0023	0.0007	5.1	5.0	2.69	70.3	9.6	79.9
4	4-43	8,192.50	0.0015	0.0004	3.8	3.7	2.68	73.6	5.4	79.0
4	4-44(F)	8,193.50		+	7.0		2.70	66.0	1.6	67.6
4	4-45	8,194.50		<0.0001	3.1	3.0	2.71	94.1	3.9	98.0
4	4-46	8,195.50	0.0005	0.0001	3.5	3.4	2.70	86.0	12.9	98.9
4	4-47	8,196.50	0.0014	0.0004	4.1	4.0	2.70	89.7	7.2	96.9
4	4-48	8,197.50	0.0032	0.0011	4.7	4.6	2.69	59.6	22.3	81.8
4	4-49	8,198.50	0.0038	0.0013	5.0	4.9	2.68	74.0	13.4	87.4
4	4-50	8,199.50	0.0011	0.0003	3.4	3.3	2.69	80.5	18.2	98.7
4	4-51	8,200.50	0.0028	0.0009	5.1	5.0	2.68	82.2	1.1	83.3
4	4-52	8,201.50	0.0012	0.0003	4.6	4.5	2.68	79.9	5.7	85.5
4	4-53c	8,202.50		+	4.6		2.67	58.2	0.0	58.3
4	4-54	8,203.50	0.216	0.156	7.0	6.9	2.66	42.3	4.8	47.1
4	4-55	8,204.40	0.025	0.013	5.5	5.4	2.67	67.2	0.0	67.3
4	4-56	8,205.50	5.48	4.38	8.8	8.7	2.65	41.7	3.8	45.5
4	4-57	8,206.50	12.4	10.2	12.3	12.1	2.65	61.6	0.9	62.5
4	4-58	8,207.50	9.18	7.49	9.0	8.8	2.66	46.2	0.5	46.7
4	4-59	8,208.50	5.70	4.57	12.1	11.9	2.65	59.7	4.3	64.0
4	4-60	8,209.50	6.53	5.25	10.0	9.8	2.66	25.4	0.0	25.5
4	4-61	8,210.50	1.04	0.797	10.1	9.9	2.66	39.1	0.0	39.1
4	4-63	8,212.20	10.3	8.41	9.5	9.3	2.66	41.8	0.0	41.9
4	4-64	8,213.40	1.23	0.962	10.5	10.3	2.65	34.3	0.0	34.3
4	4-65	8,214.50	0.437	0.337	10.5	10.3	2.66	41.8	0.0	41.8
4	4-66	8,215.50	0.0086	0.0037	5.2	5.1	2.71	45.8	2.0	47.8
4	4-67	8,216.50	0.0048	0.0018	3.5	3.4	2.73	41.1	0.0	41.2
4	4-68	8,217.50	0.0017	0.0005	3.1	3.0	2.72	68.2	1.5	69.7
4	4-69	8,218.50	7.29	5.88	8.5	8.4	2.69	29.9	6.5	36.4
4	4-70	8,219.50	42.4	36.5	13.8	13.6	2.66	49.5	3.5	53.0
4	4-71	8,220.50	52.0	45.1	14.3	14.1	2.66	51.4	5.0	56.4
4	4-72	8,221.40	26.1	22.0	14.5	14.3	2.65	68.4	0.0	68.4



SUMMARY OF ROUTINE CORE ANALYSES RESULTS

Vacuum Oven Dried at 180° F Net Confining Stress: 1,665 psi

Whiting Oil and Gas Corporation
Wildhorse 16-13L Well
Undisclosed Field

Weld County, Colorado
File No.: CO-65139
Date: 8/30/2013

Core Number	Sample Number	Sample Depth, feet	Permeability, millidarcys		Porosity, percent		Grain Density, gm/cc	Fluid Saturations, percent		
			to Air	Klinkenberg	Ambient	NCS		Water	Oil	Total
4	4-73	8,222.50	38.5	33.0	14.5	14.3	2.66	66.8	0.0	66.9
4	4-74	8,223.50	41.5	35.6	14.3	14.1	2.65	57.0	3.0	60.0
4	4-75	8,224.50	34.5	29.5	14.7	14.5	2.66	65.3	3.6	69.0
4	4-76	8,225.50	21.8	18.3	14.8	14.6	2.65	69.6	0.0	69.6
4	4-77c	8,226.50	12.3	10.1	12.5		2.68	56.2	0.0	56.3
4	4-78	8,227.50	13.3	11.0	12.3	12.1	2.65	48.7	3.2	52.0
4	4-79	8,228.50	5.21	4.18	8.3	8.2	2.69	55.1	0.0	55.1
4	4-80	8,229.50	3.55	2.81	8.1	8.0	2.69	51.1	2.7	53.9
4	4-81	8,230.50	0.121	0.082	4.5	4.4	2.72	48.9	6.1	55.0
4	4-82(F)	8,231.50	0.0044	0.0016	2.0		2.74			**
4	4-83	8,232.50	0.0053	0.0020	1.9	1.8	2.74			**
4	4-84(F)	8,233.50	0.0073	0.0030	1.4		2.77			**
4	4-85	8,234.55	0.0010	0.0002	4.5	4.4	2.76	95.8	3.5	99.3
4	4-86	8,235.50		<0.0001	4.4	4.3	2.77	89.0	0.1	89.1
4	4-87	8,236.60	0.0004	0.0001	1.1	1.0	2.76			**
4	4-88(F)	8,237.70		+	4.4		2.73	96.4	0.2	96.6
4	4-89(F)	8,238.60		+	2.3		2.73			**
4	4-90(F)	8,239.90		+	6.4		2.79	73.1	0.1	73.2
4	4-91(F)	8,240.30		+	3.4		2.73	81.2	0.1	81.3
4	4-92(f)	8,241.30	0.0084	0.0036	2.3	2.2	2.78	96.6	0.1	96.7
4	4-93	8,242.30		<0.0001	2.6	2.5	2.75	79.0	14.7	93.8
5	5-2c	9,351.50		+	11.0		2.84	62.3	1.3	63.7
5	5-4(f)	9,353.30	10.1	8.11	18.2	18.0	2.83	65.7	4.9	70.6
6	6-5	9,363.50		<0.0001	0.2	0.2	2.67			**
6	6-7(F)	9,365.50		+	1.7		2.71			**
7	7-2	9,369.90		<0.0001	2.3	2.2	2.67			**
7	7-4	9,371.85		<0.0001	2.1	2.1	2.66			**
7	7-6	9,373.30		<0.0001	1.8	1.7	2.68			**
7	7-7c	9,374.45		<0.0001	0.6		2.68			**
7	7-9	9,376.50	0.033	0.018	13.8	13.6	2.81	25.4	47.9	73.3
7	7-13	9,380.55	0.049	0.029	7.9	7.8	2.82	65.4	14.3	79.8
7	7-15	9,382.50	0.074	0.047	18.4	18.2	2.79	33.0	34.5	67.5
7	7-17c	9,384.30		<0.0001	0.7		2.70			**
8	8-2(F)	9,401.65		+	1.5		2.69			**
8	8-4c	9,403.00		<0.0001	1.2		2.71			**
8	8-6(F)	9,405.00		+	2.9		2.74			**
8	8-8c	9,407.05		+	2.9		2.73			**
8	8-10	9,409.50		<0.0001	0.6	0.6	2.72			**
8	8-12	9,411.75	0.0004	0.0001	4.1	4.0	2.75	77.6	17.6	95.2
8	8-15(F)	9,414.60		+	5.2		2.76	85.9	0.0	85.9
8	8-18-A	9,417.65		<0.0001	4.4	4.3	2.69	94.9	3.1	97.9
8	8-20(F)	9,419.05		+	4.5		2.68	73.7	2.9	76.6
8	8-21c	9,420.30		+	0.4		2.63			**
8	8-24c	9,423.05		+	4.9		2.74	95.5	0.1	95.6



SUMMARY OF ROUTINE CORE ANALYSES RESULTS

Vacuum Oven Dried at 180° F Net Confining Stress: 1,665 psi

Whiting Oil and Gas Corporation
 Wildhorse 16-13L Well
 Undisclosed Field

Weld County, Colorado
 File No.: CO-65139
 Date: 8/30/2013

Core Number	Sample Number	Sample Depth, feet	Permeability, millidarcys		Porosity, percent		Grain Density, gm/cc	Fluid Saturations, percent		
			to Air	Klinkenberg	Ambient	NCS		Water	Oil	Total
8	8-26	9,425.05	0.0015	0.0004	5.0	4.9	2.77	86.0	0.1	86.1
8	8-28	9,427.60	<0.0001		2.9	2.8	2.76	94.3	0.3	94.6
8	8-29(F)	9,428.50	+		3.4	3.3	2.74	85.8	0.5	86.3
8	8-31	9,430.50	0.0014	0.0004	4.8	4.7	2.71			**
8	8-33	9,432.50	0.0033	0.0011	12.9	12.8	2.80	91.3	0.0	91.3
8	8-38c	9,437.80	<0.0001		0.9		2.70			**
8	8-40	9,439.50	0.0041	0.0015	6.8	6.7	2.77	91.7	0.1	91.8
8	8-42	9,441.50	0.0019	0.0005	5.7	5.6	2.78	84.8	0.0	84.8
8	8-44	9,443.50	<0.0001		1.8	1.8	2.74			**
9	9-6(F)	9,449.50	+		1.0		2.72			**
9	9-12	9,455.50	<0.0001		1.0	0.9	2.67			**
9	9-14c(f)	9,457.50	0.027	0.015	3.6		2.70	88.1	0.1	88.2
9	9-20c	9,463.50	+		0.3		2.63			**
9	9-24c	9,467.60	+		4.9		2.71	38.7	3.2	41.9
9	9-32(F)	9,475.50	+		1.2		2.72			**
10	10-2(F)	9,480.70	+		2.5		2.74	75.6	0.0	75.6
10	10-6	9,484.50	<0.0001		1.6	1.6	2.74			**
10	10-26(F)	9,504.40	+		6.0		2.72	78.2	0.5	78.7
11	11-5	9,544.50	0.024	0.013	3.9	3.9	2.75	83.8	0.1	83.9
11	11-6(F)	9,545.05	+		2.0		2.71			**
11	11-9	9,548.30	<0.0001		1.6	1.5	2.77			**
11	11-11(F)	9,550.10	+		1.2		2.72			**
11	11-15(f)	9,554.30	0.011	0.0051	4.3	4.2	2.75	92.9	0.0	93.0
11	11-17(F)	9,556.70	+		1.0		2.70			**
11	11-20(f)	9,559.50	0.075	0.048	1.0	1.0	2.71			**
11	11-23(F)	9,562.50	+		3.9		2.78	74.1	0.1	74.2
11	11-26(F)	9,565.50	+		3.2		2.75	95.7	0.1	95.8
11	11-28	9,567.30	0.0006	0.0001	2.0	1.9	2.72			**
11	11-32(F)	9,571.30	+		2.1		2.74			**
11	11-34c	9,573.20	0.0012	0.0003	1.0		2.71			**
11	11-37(F)	9,578.60	+		2.5		2.76			**
11	11-39(F)	9,578.60	+		1.4		2.73			**
11	11-41(F)	9,580.80	+		1.4		2.72			**
11	11-44(F)	9,583.30	+		0.8		2.70			**
11	11-50(F)	9,589.60	+		2.2		2.71			**
11	11-52	9,591.60	<0.0001		1.1	1.0	2.72			**
11	11-59(F)	9,598.85	+		5.2		2.71	98.4	0.2	98.6
11	11-68(F)	9,607.35	+		2.1		2.72			**
11	11-80c	9,619.90	+		0.4		2.71			**
11	11-82(F)	9,621.60	+		0.5		2.71			**
11	11-89(F)	9,628.60	+		2.6		2.72			**
11	11-93c	9,632.50	+		0.9		2.71			**
12	12-6c	9,638.30	+		0.6		2.71			**
12	12-9c	9,641.20	+		1.2		2.70			**



SUMMARY OF ROUTINE CORE ANALYSES RESULTS

Vacuum Oven Dried at 180° F Net Confining Stress: 1,665 psi

Whiting Oil and Gas Corporation
 Wildhorse 16-13L Well
 Undisclosed Field

Weld County, Colorado
 File No.: CO-65139
 Date: 8/30/2013

Core Number	Sample Number	Sample Depth, feet	Permeability, millidarcys		Porosity, percent		Grain Density, gm/cc	Fluid Saturations, percent			
			to Air	Klinkenberg	Ambient	NCS		Water	Oil	Total	
12	12-14(F)	9,646.30		+		2.2		2.70			**
13	13-1(F)	9,655.90		+		3.2		2.73			**
13	13-26(F)	9,680.20		+		1.3		2.71			**
13	13-28(F)	9,682.50		+		2.1		2.71			**
13	13-38c	9,692.30		+		3.3		2.80	96.3	2.4	98.6
13	13-42c	9,696.50		+		1.7		2.71			**
14	14-4(F)	9,721.80		+		1.0		2.55			**
14	14-12(F)	9,729.10		+		1.3		2.72			**
14	14-28c	9,745.10		+		0.8		2.71			**
14	14-48c	9,765.40		+		0.9		2.71			**
14	14-50(F)	9,767.20		+		2.0		2.72			**
15	15-24c	9,798.90	0.0008		0.0002	0.4		2.69			**
15	15-25	9,799.50	0.0016		0.0004	0.5	0.5	2.69			**
15	15-26c	9,800.50		+		0.6		2.71			**
15	15-27	9,801.40	0.0089		0.0039	1.8	1.7	2.69			**
16	16-3	9,812.50	0.0067		0.0027	1.1	1.1	2.68			**
16	16-6(f)	9,815.60	3.32		2.61	1.2	1.2	2.69			**
16	16-7	9,816.40		<0.0001		1.3	1.2	2.72			**
16	16-8	9,817.80	0.0007		0.0002	1.4	1.4	2.69			**
16	16-10	9,819.50	0.0071		0.0029	1.3	1.2	2.69			**
16	16-11c	9,820.50		+		1.4		2.71			**
16	16-11-A	9,820.90	0.0005		0.0001	0.9	0.9	2.65			**
16	16-26c	9,835.20		+		1.7		2.70			**
16	16-28(F)	9,837.10		+		1.1		2.67			**
16	16-44	9,853.60	0.0050		0.0019	4.9	4.8	2.80	72.8	2.7	75.5
16	16-50c	9,859.10		+		2.3		2.66			**
17	17-7c	9,866.50		+		4.3		2.72	50.9	0.6	51.5
19	19-3(F)	9,889.60		+		10.7		2.81	62.8	6.7	69.5
Average values:			12.8		11.1	6.7	8.0	2.70	62.2	7.4	69.6

- + Indicates the sample is unsuitable for this type of measurement
- ** Indicates pore volume / water out was insufficient to report saturations
- (f) Indicates the sample has a visible fracture or lamination that may affect permeability
- (F) Indicates the sample is fractured into multiple pieces
- c Indicates the sample is chipped