

	measured depth (ft)	Inclination (")	azimuth (")	true vertical depth (ft)	northing +N/-S (ft)	easting +E/-W (ft)
Header Information						
Operator Name	0	0.00	0.00	0	0	0
Dejour Energy (USA) Corp.	146	0.40	295.70	146	0.22	-0.46
Operator Number	150	0.51	290.65	150	0.23	-0.49
10301						
Well Name and Number	206	1.50	276.5	205.99	0.42	-1.58
Federal 6/7-14-21	266	3.16	278.88	265.94	0.77	-3.99
API Number (if available)	297	4.26	277.82	296.87	1.05	-5.98
05-045-21180-00	357	7.38	273.6	356.55	1.6	-12.03
Location: QQ SEC TWP RGE	447	10.20	272.2	445.49	2.27	-25.77
SW5E 21 6S 91W	538	12.83	274.66	534.65	3.4	-43.89
Citing Type: Planned or Actual	628	15.42	274.04	621.92	5.05	-65.79
Actual	722	19.34	271.14	711.61	6.25	-93.83
Deviation Indicator	812	20.87	269.56	796.13	6.42	-124.76
Directional	902	23.73	267.98	879.39	5.66	-158.9
North Reference	993	26.50	266.83	961.78	3.89	-197.48
True	1088	28.39	267.36	1046.08	1.68	-241.2
Grid Type	1170	29.71	267.45	1117.76	-0.13	-280.98
	1210	29.81	267.21	1152.49	-1.05	-300.81
	1245	29.9	267	1182.84	-1.93	-318.21
	1340	30.9	267.3	1264.78	-4.32	-366.23
	1435	31.25	267.83	1346.15	-6.4	-415.22
	1530	30.59	267.22	1427.65	-8.51	-463.99
	1624	30.41	266.6	1508.64	-11.08	-511.62
	1719	30.28	265.37	1590.63	-14.44	-559.5
	1815	29.71	268.45	1673.77	-17.03	-607.41
	1909	30.85	263.96	1754.96	-20.2	-654.67
	1950	30.85	263.96	1790.16	-22.41	-675.57
	2004	30.98	261.85	1836.49	-25.84	-703.1
	2099	30.54	265.37	1918.13	-31.26	-751.37
	2195	29.58	268.71	2001.22	-33.76	-799.37
	2289	29.27	273.02	2083.1	-33.07	-845.52
	2384	30.32	272.58	2165.55	-30.77	-892.67
	2480	30.76	271.35	2248.23	-29.1	-941.42
	2575	28.52	270.2	2330.79	-28.45	-988.39
	2670	25.44	270.73	2415.44	-28.11	-1031.48
	2765	22.98	270.73	2502.08	-27.61	-1070.43
	2860	22.24	270.03	2589.78	-27.37	-1106.96
	2955	22.68	268.89	2677.57	-27.71	-1143.25
	3050	23.03	268.01	2765.12	-28.71	-1180.13
	3240	22.72	269.94	2940.58	-28.42	-1252.99
	3335	19.9	272.21	3029.08	-27.82	-1287.5
	3430	17.93	271.7	3118.95	-26.76	-1318.28
	3525	18.68	271.26	3209.14	-25.99	-1348.11
	3620	16.88	271	3299.6	-25.42	-1377.11
	3810	14.9	273.63	3482.85	-23.13	-1427.2
	3905	13.36	269.5	3574.97	-22.45	-1450.36
	4095	8.53	275.74	3761.37	-21.12	-1486.91
	4224	7.96	279.32	3889.03	-18.72	-1505.21
	4319	7.91	269.82	3983.13	-17.67	-1518.24
	4414	5.85	270.79	4077.44	-17.63	-1529.62
	4509	3.82	259.19	4172.1	-18.15	-1537.57
	4604	1.89	262.53	4266.97	-18.95	-1542.23
	4890	1.25	135	4552.95	-20.34	-1543.53
	5175	1.41	166.99	4837.92	-23.84	-1542.08
	5365	1.76	174.64	5027.83	-29.6	-1541.2
	5460	1.8	186.85	5122.79	-32.53	-1541.24
	5555	1.67	189.67	5217.75	-35.38	-1541.65
	5745	1.58	166.29	5407.68	-40.46	-1541.09
	5840	1.45	155.74	5502.64	-42.82	-1540.29
	5935	1.27	153.63	5597.62	-44.86	-1539.33
	6030	1.5	155.13	5692.59	-46.93	-1538.34
	6125	1.67	151.26	5787.55	-49.28	-1537.15
	6220	1.36	157.85	5882.52	-51.53	-1536.06
	6315	1.63	161.5	5977.49	-53.86	-1535.2
	6410	1.45	169.8	6072.45	-56.32	-1534.56
	6505	1.58	163.74	6167.42	-58.76	-1533.98
	6600	1.36	161.19	6262.39	-61.09	-1533.25
	6696	1.41	161.28	6358.36	-63.28	-1532.5
	6791	0.88	167.61	6453.34	-65.1	-1531.97
	6886	1.05	177.63	6548.33	-66.69	-1531.78
	6980	1.1	189.32	6642.31	-68.44	-1531.89
	7075	1.1	189.14	6737.27	-70.24	-1532.18
	7170	1.23	184.66	6832.27	-72.15	-1532.41
	7265	0.88	178.94	6927.26	-73.9	-1532.48
	7360	1.1	218.93	7022.24	-75.34	-1533.04
	7455	1.05	196.17	7117.23	-76.88	-1533.85
	7550	0.92	210.32	7212.21	-78.38	-1534.48
	7645	0.53	241.96	7307.21	-79.24	-1535.25
	7740	0.53	230.01	7402.2	-79.73	-1535.98
	7835	0.92	255.67	7497.19	-80.2	-1537.05
	7930	0.57	264.99	7592.19	-80.43	-1538.26
	8025	0.75	268.5	7687.18	-80.49	-1539.36
	8120	1.19	311.04	7782.17	-79.86	-1540.72
	8215	1.71	321.85	7877.14	-78.1	-1542.34
	8310	1.93	308.23	7972.09	-75.99	-1544.47
	8372	2.11	321.59	8034.05	-74.45	-1546