

FORM  
5A

Rev  
06/12

State of Colorado

Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE ET OE ES

Document Number:

400539228

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 100322

2. Name of Operator: NOBLE ENERGY INC

3. Address: 1625 BROADWAY STE 2200

City: DENVER State: CO Zip: 80202

4. Contact Name: Kathleen Mills

Phone: (720) 587-2226

Fax: (303) 228-4286

Email: kmills@nobleenergyinc.com

5. API Number 05-123-37472-00

7. Well Name: Rohn State

8. Location: QtrQtr: SESE Section: 4 Township: 9N Range: 58W Meridian: 6

9. Field Name: WILDCAT Field Code: 99999

6. County: WELD

Well Number: LD09-69HN

Completed Interval

FORMATION: NIOBRARA

Status: PRODUCING

Treatment Type: FRACTURE  
STIMULATION

Treatment Date: 11/05/2013 End Date: 11/05/2013 Date of First Production this formation: 12/15/2013

Perforations Top: 6327 Bottom: 9633 No. Holes: 0 Hole size:

Provide a brief summary of the formation treatment: Open Hole: ☒

FRAC'D W/2024581 GAL SILVERSTIM AND SLICK WATER AND 2057082# OTTAWA SAND

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): 48204

Max pressure during treatment (psi): 5183

Total gas used in treatment (mcf):

Fluid density at initial fracture (lbs/gal): 8.43

Type of gas used in treatment:

Min frac gradient (psi/ft): 0.85

Total acid used in treatment (bbl):

Number of staged intervals: 18

Recycled water used in treatment (bbl): 2876

Flowback volume recovered (bbl): 11113

Fresh water used in treatment (bbl): 45328

Disposition method for flowback: RECYCLE

Total proppant used (lbs): 2057082

Rule 805 green completion techniques were utilized: ☒

Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 12/24/2013 Hours: 24 Bbl oil: 68 Mcf Gas: 144 Bbl H2O: 379

Calculated 24 hour rate: Bbl oil: 68 Mcf Gas: 144 Bbl H2O: 379 GOR: 2118

Test Method: FLOWING Casing PSI: 985 Tubing PSI: 300 Choke Size: 18/64

Gas Disposition: SOLD Gas Type: WET Btu Gas: 1138 API Gravity Oil: 38

Tubing Size: 2 + 7/8 Tubing Setting Depth: 6017 Tbg setting date: 11/30/2013 Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

Comment:

--

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_

Print Name: Kathleen Mills

Title: Regulatory Analyst

Date: \_\_\_\_\_

Email kmills@nobleenergyinc.com

:

### **Attachment Check List**

**Att Doc Num**      **Name**

--	--

Total Attach: 0 Files

### **General Comments**

**User Group**      **Comment**

**Comment Date**

--	--	--

Total: 0 comment(s)