NABORS

NABORS DRILLING
A NABORS COMPANY

Rig: 1 AC-SCR-MW (1 - AC)

Well: 3H Fed 16-21-28-33 Com

Job: 3477000001

Date: 01/29/2022

Crew: Day

Bit #: 1 Size: 8.75 Type: MM55D Serial #: 7190

In: 10,750 Out: 20,750 Total Hrs: 24.00 Total Rev: 31,000

Mud Type: Oil Based Mud Density: 10.00 Viscosity: 58

Nozzles: 6 - 14 6 - 14 6 - 14 Pressure: 2,500

Jet Velocity: 0.00 Pump Output: 0.00

Hydraulic HP: 0.00 HP/in²: 0.00

Weight on Bit: 0 Flow %: 0

Rotary RPM: 0 Max Pump PSI: 0

Avg String RPM: 0 Pump SPM: 0

Ann Velocity DP: 0.00 Ann Velocity DC: 0.00

Slow Pump Rate: 0 Slow Pump PSI: 0

Total Strokes: 0 Total Circ Time: 0.00

Bottoms Up Time: 0.00 Bottoms Up Strokes: 0

Gallons/Stroke: 0.00 Pump Output: 0.00

Pump Eff %: 0.00

Activity	Start Time	End Time	Duration
Rig Down	00:00	06:00	6.00
Rig Move	06:00	18:00	12.00
Rig Up	18:00	24:00	6.00

Total Duration: 24.00

Comments:

Rig Down

Rig Move

Rig Up

Daily Totals: 24.00

Cumulative Totals: 24.00

Prepared By: Jeremy Thomas

Approved By:

Nabors Well Services Ltd.
Suite 2100, 517 - 10th Ave SW
Calgary, Alberta T2R 0A8
Phone: (403) 262-7996
Fax: (403) 262-7992

Nabors Well Services (U.S.), Inc.
3990 Rogerdale Road
Houston, Texas 77042
Phone: (713) 346-7100
Fax: (713) 346-7105



Calibration Report

Database File: cbl noble vetting.pmf 25-2 db
Dataset Pathname: pass3
Dataset Creation: Fri Feb 28 07:26:19 2014 by Log SCH 123400

Gamma Ray Calibration Report

Type / Serial: Probe2TSdgi / 110795

Fri Nov 08 09:38:30 2013

	Counts/Sec	Gain	Offset	Jig	Units
SHOP CALIBRATION					
Background	0.0				cps
Calibrator	1.0				cps
		0.4400			GAPI/cps
PRIMARY VERIFICATION					
Background	0.0				cps
Calibrator	0.0				cps
Difference			0.0		GAPI
BEFORE SURVEY VERIFICATION					
Background	0.0				cps
Calibrator	0.0				cps
Difference			0.0		GAPI
AFTER SURVEY VERIFICATION					
Background	0.0				cps
Calibrator	0.0				cps
Difference			0.0		GAPI

Cement Bond Log Calibration Report

Serial Number:	110002		
Tool Model:	Probe2TSDgital		
Performed:	Fri Feb 28 07:13:28 2014		
Depth:	1148.3	ft	
Casing Diameter:	4.5	in	
	3' Spacing	5' Spacing	
Signal Zero:	0.7	0	mV
Calibrated Amplitude:	81.1561	81.1561	mV
Reading at Signal Zero:	-0.00595703	-0.00605469	V
Reading in Free Pipe:	2.46055	2.3106	V
Gain:	32.2435	35.0489	
Offset:	0.892075	0.21221	