

Header Information	measured depth (ft)	inclination (°)	azimuth (°)	true vertical depth (ft)	northing +N/-S (ft)	easting +E/-W (ft)
Operator Name	0.0	0.00	0.00	0.0	0.0	0.0
Great Western Oil & Gas Company LLC	4000.0	0.00	0.00	4000.0	0.0	0.0
Operator Number	4100.0	3.00	343.08	4100.0	2.5	-0.8
10110	4200.0	6.00	343.08	4199.6	10.0	-3.0
Well Name and Number	4300.0	9.00	343.08	4298.8	22.5	-6.8
Postle IC 11-002HN	4400.0	12.00	343.08	4397.1	39.9	-12.1
API Number (if available)	4500.0	15.00	343.08	4494.3	62.3	-18.9
	4600.0	18.00	343.08	4590.2	89.4	-27.2
Location: QQ SEC TWP RGE	4700.0	21.00	343.08	4684.4	121.4	-36.9
Sec.11-T3N-R68W	4800.0	24.00	343.08	4776.8	158.0	-48.0
Citing Type: Planned or Actual	4900.0	27.00	343.08	4867.1	199.2	-60.6
Planned	4998.8	29.96	343.08	4953.9	244.2	-74.3
Deviation Indicator	5000.0	29.96	343.08	4954.9	244.8	-74.5
Horizontal ▼	5100.0	29.96	343.08	5041.6	292.6	-89.0
North Reference	5200.0	29.96	343.08	5128.2	340.4	-103.5
True ▼	5300.0	29.96	343.08	5214.8	388.2	-118.1
Grid Type	5400.0	29.96	343.08	5301.5	435.9	-132.6
▼	5500.0	29.96	343.08	5388.1	483.7	-147.1
	5600.0	29.96	343.08	5474.7	531.5	-161.6
	5700.0	29.96	343.08	5561.4	579.3	-176.2
	5800.0	29.96	343.08	5648.0	627.1	-190.7
	5900.0	29.96	343.08	5734.6	674.9	-205.2
	6000.0	29.96	343.08	5821.3	722.6	-219.8
	6100.0	29.96	343.08	5907.9	770.4	-234.3
	6200.0	29.96	343.08	5994.5	818.2	-248.8
	6300.0	29.96	343.08	6081.2	866.0	-263.4
	6400.0	29.96	343.08	6167.8	913.8	-277.9
	6500.0	29.96	343.08	6254.5	961.6	-292.4
	6600.0	29.96	343.08	6341.1	1009.3	-307.0

6700.0	29.96	343.08	6427.7	1057.1	-321.5
6800.0	29.96	343.08	6514.4	1104.9	-336.0
6900.0	29.96	343.08	6601.0	1152.7	-350.6
7000.0	29.96	343.08	6687.6	1200.5	-365.1
7027.5	29.96	343.08	6711.5	1213.6	-369.1
7100.0	28.94	2.20	6774.7	1248.5	-373.7
7200.0	31.94	27.34	6861.3	1296.4	-360.6
7300.0	38.88	46.46	6943.0	1341.7	-325.5
7400.0	48.05	59.94	7015.6	1382.2	-270.4
7500.0	58.38	69.83	7075.5	1415.6	-197.9
7600.0	69.32	77.67	7119.6	1440.4	-111.9
7700.0	80.56	84.44	7145.6	1455.2	-16.7
7783.1	90.00	89.71	7152.4	1459.4	65.9
7783.9	90.00	89.72	7152.4	1459.4	66.7
7800.0	90.00	89.72	7152.4	1459.5	82.8
7900.0	90.00	89.72	7152.4	1460.0	182.8
8000.0	90.00	89.72	7152.4	1460.5	282.8
8100.0	90.00	89.72	7152.4	1461.0	382.8
8200.0	90.00	89.72	7152.4	1461.5	482.8
8300.0	90.00	89.72	7152.4	1462.0	582.8
8400.0	90.00	89.72	7152.4	1462.4	682.8
8500.0	90.00	89.72	7152.4	1462.9	782.8
8600.0	90.00	89.72	7152.4	1463.4	882.8
8700.0	90.00	89.72	7152.4	1463.9	982.8
8800.0	90.00	89.72	7152.4	1464.4	1082.8
8900.0	90.00	89.72	7152.4	1464.9	1182.8
9000.0	90.00	89.72	7152.4	1465.4	1282.8
9100.0	90.00	89.72	7152.4	1465.9	1382.8
9200.0	90.00	89.72	7152.4	1466.4	1482.8
9300.0	90.00	89.72	7152.4	1466.9	1582.8
9400.0	90.00	89.72	7152.4	1467.4	1682.8
9500.0	90.00	89.72	7152.4	1467.9	1782.8
9600.0	90.00	89.72	7152.4	1468.3	1882.8
9700.0	90.00	89.72	7152.4	1468.8	1982.8

9800.0	90.00	89.72	7152.4	1469.3	2082.8
9900.0	90.00	89.72	7152.4	1469.8	2182.8
10000.0	90.00	89.72	7152.4	1470.3	2282.8
10100.0	90.00	89.72	7152.4	1470.8	2382.8
10200.0	90.00	89.72	7152.4	1471.3	2482.8
10300.0	90.00	89.72	7152.4	1471.8	2582.8
10400.0	90.00	89.72	7152.4	1472.3	2682.8
10500.0	90.00	89.72	7152.4	1472.8	2782.8
10600.0	90.00	89.72	7152.4	1473.3	2882.8
10700.0	90.00	89.72	7152.4	1473.8	2982.8
10800.0	90.00	89.72	7152.4	1474.2	3082.8
10900.0	90.00	89.72	7152.4	1474.7	3182.8
11000.0	90.00	89.72	7152.4	1475.2	3282.8
11100.0	90.00	89.72	7152.4	1475.7	3382.8
11200.0	90.00	89.72	7152.4	1476.2	3482.8
11300.0	90.00	89.72	7152.4	1476.7	3582.8
11400.0	90.00	89.72	7152.4	1477.2	3682.8
11500.0	90.00	89.72	7152.4	1477.7	3782.8
11600.0	90.00	89.72	7152.4	1478.2	3882.8
11700.0	90.00	89.72	7152.4	1478.7	3982.8
11800.0	90.00	89.72	7152.4	1479.2	4082.8
11900.0	90.00	89.72	7152.4	1479.7	4182.8
12000.0	90.00	89.72	7152.4	1480.2	4282.8
12100.0	90.00	89.72	7152.4	1480.6	4382.8
12159.3	90.00	89.72	7152.4	1480.9	4442.1