



DRILLING COMPANY, INC.
WICHITA, KANSAS

Wellbore Diagram

		Date:	3/27/2014
		Well Name:	Gerweck #1-4
		Location:	NW NW 4-13S-44W
	13-3/8" csg set @ 486'. Cmt w/460 sks.		660' FNL & 660' FWL
	TOC @ 550'	County:	Cheyenne
		State:	Colorado
		API:	05-017-07772
		KB:	4272'
		GL:	4261'
		Spud Date:	11/9/2013
	TOC @ 1450'.		
	8-5/8" csg set at 1733'. Cmt. w/100 sks.		
3104' DV Tool cmt w/150 sks.			
3830' Top of cmt from Perf & Pump. Perfs @ 4140' - 4186' (TA)			
4200' - Perf & Pump 175 sks., then squeeze 150 sks. 4290' - Base of cmt from squeeze. Top of Cement at 4530'.	LOG TOPS:	DEPTH:	
	Anhydrite	3084	
	B/Anhydrite	3124	
	Shawnee	4127	
	Heebner Shale	4320	
CIBP set @ 5280'.	Lansing	4360	
	Stark Shale	4595	
Perfs @ 5298' - 5380' (D&A).	B/KC	4694	
CIBP set @ 5422' w/2 sks cmt.	Marmaton	4717	
Perfs @ 5438' - 5442' (D&A).	Ft. Scott	4798	
CIBP set @ 5443' w/2 sks cmt.	Cherokee Shale	4857	
Perfs @ 5446' - 5454' (D&A).	Atoka	5003	
	Morrow Shale	5125	
	Keyes	5234	
5-1/2", 15.5# csg set at 5498'. Cmt w/210 sks.	Miss-St. Louis	5281	
	Spergen	5382	
	RTD	5500	
	LTD	5499	