

EnCana Oil & Gas (USA) Inc.

Well : GRENEMEYER CD26-A
Field : Wattenberg
County : Weld County **State** : Colorado
Surface : Lat: 40.018031 Long: -104.862281
: 1168 FSL, 1400 FWL SESW Sec 26 T1N R67W
API # : 05-123-21028
Grd Elev : 5034' GR **KB Elevation:** 5050' KB

Log Tops:

Fox Hills Base	935'
Sussex	4779'
Niobrara	7331'
Codell	7754'
J Sand	8193'

Well History:

Spud	07/20/2002
TD	07/23/2002

Surface Casing

8-5/8" Surface Casing set
@ 1077', cmt'd w/ 400 sx

DV TOOL

production casing STAGE TOOL set
@ 5706'. Cmt w/ 350 sx
TOC @ 4170'
CBL dated 08/01/2002

TOC @ 6900'
CBL dated 08/01/2002

Production Casing

4-1/2", 10.5#, N-80 production casing
set @ 8349'. Cmt w/ 280 sx

Production Tubing

2-3/8" Tubing set @ 8245',
259 JTS (05/24/2011)

Annular Fill Remediation

RIH with 1-1/4" tubing down the 4-1/2" by 8-5/8" annulus. Pumped 500 sxs Class G Neat cement (03/20/2014)
Continuous Cement column from 2220' to 70'
CBL dated 03/21/2014

Niobrara Perfs

Perfed 7342-7354, 7514-7532, 4 spf,
120 holes.
Frac'd w/145,362 gal frac fluid and
250,380 # sand. (4/30/11)

Codell Perfs

7754-7774, 2 spf, 40 holes
Frac'd w/ 115,962 gal frac fluid and
250,740 # sand. (4/30/11)

J Sand Perfs

8245' - 8203', 2 spf, 66 holes
Frac'd w/ 305,000# 20/40 sand,
687 bbls, CO2 and 2716 gal
Dynaflow-2 frac fluid

TD 8355'

Drawn by:
Nicholas Ronan

Date:
03/26/2014