

FORM  
5A

Rev  
06/12

State of Colorado

Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

400590593

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 100322  
2. Name of Operator: NOBLE ENERGY INC  
3. Address: 1625 BROADWAY STE 2200  
City: DENVER State: CO Zip: 80202  
4. Contact Name: Kathleen Mills  
Phone: (720) 587-2226  
Fax: (303) 228-4286  
Email: kmills@nobleenergyinc.com

5. API Number 05-123-37489-00  
6. County: WELD  
7. Well Name: Timbro State  
Well Number: LD16-65HN  
8. Location: QtrQtr: SENE Section: 16 Township: 9N Range: 58W Meridian: 6  
9. Field Name: WILDCAT Field Code: 99999

Completed Interval

FORMATION: NIOBRARA Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 01/16/2014 End Date: 01/17/2014 Date of First Production this formation: 02/20/2014

Perforations Top: 6269 Bottom: 9603 No. Holes: 0 Hole size:

Provide a brief summary of the formation treatment: Open Hole: ☒

FRAC'D W/2022876 GALS SILVERSTIM AND SLICK WATER AND 2441966# OTTWA SAND

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): 48163 Max pressure during treatment (psi): 4584

Total gas used in treatment (mcf): Fluid density at initial fracture (lbs/gal): 8.43

Type of gas used in treatment: Min frac gradient (psi/ft): 0.74

Total acid used in treatment (bbl): Number of staged intervals: 18

Recycled water used in treatment (bbl): 2631 Flowback volume recovered (bbl): 3006

Fresh water used in treatment (bbl): 45532 Disposition method for flowback: RECYCLE

Total proppant used (lbs): 2441966 Rule 805 green completion techniques were utilized: ☒

Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 02/28/2014 Hours: 24 Bbl oil: 100 Mcf Gas: 52 Bbl H2O: 12

Calculated 24 hour rate: Bbl oil: 100 Mcf Gas: 52 Bbl H2O: 12 GOR: 520

Test Method: FLOWING Casing PSI: 887 Tubing PSI: 429 Choke Size: 20/64

Gas Disposition: SOLD Gas Type: WET Btu Gas: 1265 API Gravity Oil: 39

Tubing Size: 2 + 7/8 Tubing Setting Depth: 6012 Tbg setting date: 01/29/2014 Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

Comment:

--

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Kathleen Mills

Title: Regulatory Analyst Date: \_\_\_\_\_ Email: kmills@nobleenergyinc.com  
:

### **Attachment Check List**

**Att Doc Num**      **Name**

--	--

Total Attach: 0 Files

### **General Comments**

**User Group**      **Comment**      **Comment Date**

--	--	--

Total: 0 comment(s)