
Client: NEW ZEALAND OIL & GAS LTD
Well: KAHU-1 ST1
Field: TARANAKI BASIN
Location: OFFSHORE TARANAKI
Country: NEW ZEALAND
Permit: PEP 38481
Rig: OCEAN PATRIOT
Spud Date: 15-Jan-2014
Log Date: 19-Jan-2014
Run No: 1
Depth Datum: RT
Elevation: 0.00 m
Log Measured From: RT
Permanent Datum: MSL
Elevation: 0.00 m
Drilling Measured From: RT
Elevation: 0.00 m
Total Depth: 3,000.0 m
Bottom Log Interval: 2,998.0 m
Top Log Interval: 1,000.0 m
Casing Driller: 1,000.0 m
Casing Logger: 1,000.0 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 60.0 s
Fluid Loss: 4.0 cm3/30min
Resistivity: 0.200 ohm.m @ 20.0 degC
Resistivity: 0.200 ohm.m @ 20.0 degC
Resistivity: 0.200 ohm.m @ 20.0 degC
Source: Measured
Time Since Circulation: 12.0 hr
Max Rec Temperature: 20.0 degC
Equipment: 1
Location: 1
Recorded By: SCHLUMBERGER
Witnessed By: NEW ZEALAND OIL & GAS LTD
Schlumberger
Kahu-1 ST1
Run 1
Logging Services
Client: NEW ZEALAND OIL & GAS LTD
Well: KAHU-1 ST1
Field: TARANAKI BASIN
Location: OFFSHORE TARANAKI
Country: NEW ZEALAND
Permit: PEP 38481
Rig: OCEAN PATRIOT
Spud Date: 15-Jan-2014
Log Date: 19-Jan-2014
Run No: 1
Depth Datum: RT
Elevation: 0.00 m
Log Measured From: RT
Permanent Datum: MSL
Elevation: 0.00 m
Drilling Measured From: RT
Elevation: 0.00 m
Total Depth: 3,000.0 m
Bottom Log Interval: 2,998.0 m
Top Log Interval: 1,000.0 m
Casing Driller: 1,000.0 m
Casing Logger: 1,000.0 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 60.0 s
Fluid Loss: 4.0 cm3/30min
Resistivity: 0.200 ohm.m @ 20.0 degC
Resistivity: 0.200 ohm.m @ 20.0 degC
Resistivity: 0.200 ohm.m @ 20.0 degC
Source: Measured
Time Since Circulation: 12.0 hr
Max Rec Temperature: 20.0 degC
Equipment: 1
Location: 1
Recorded By: SCHLUMBERGER
Witnessed By: NEW ZEALAND OIL & GAS LTD
Schlumberger
Kahu-1 ST1
Run 1
Logging Services
Client: NEW ZEALAND OIL & GAS LTD
Well: KAHU-1 ST1
Field: TARANAKI BASIN
Location: OFFSHORE TARANAKI
Country: NEW ZEALAND
Permit: PEP 38481
Rig: OCEAN PATRIOT
Spud Date: 15-Jan-2014
Log Date: 19-Jan-2014
Run No: 1
Depth Datum: RT
Elevation: 0.00 m
Log Measured From: RT
Permanent Datum: MSL
Elevation: 0.00 m
Drilling Measured From: RT
Elevation: 0.00 m
Total Depth: 3,000.0 m
Bottom Log Interval: 2,998.0 m
Top Log Interval: 1,000.0 m
Casing Driller: 1,000.0 m
Casing Logger: 1,000.0 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 60.0 s
Fluid Loss: 4.0 cm3/30min
Resistivity: 0.200 ohm.m @ 20.0 degC
Resistivity: 0.200 ohm.m @ 20.0 degC
Resistivity: 0.200 ohm.m @ 20.0 degC
Source: Measured
Time Since Circulation: 12.0 hr
Max Rec Temperature: 20.0 degC
Equipment: 1
Location: 1
Recorded By: SCHLUMBERGER
Witnessed By: NEW ZEALAND OIL & GAS LTD
Schlumberger
Kahu-1 ST1
Run 1
Logging Services



Calibration Report

Database File: ackerson, ellanora m gu1.db
Dataset Pathname: pass6
Dataset Creation: Wed May 08 16:28:52 2013 by Log 0

Gamma Ray Calibration Report

Serial Number:	168	
Tool Model:	Tek-Co	
Performed:	Sun Jun 13 13:33:21 1993	
Calibrator Value:	1.0	
Background Reading:	0.0	cps
Calibrator Reading:	1.0	cps
Sensitivity:	1.0000	/cps

Segmented Cement Bond Log Calibration Report

Serial Number:	1681	
Tool Model:	168	
Calibration Casing Diameter:	4.500	in
Calibration Depth:	7299.658	ft

Master Calibration, performed Wed May 08 16:21:04 2013:

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.000	2.462	1.000	81.196	32.578	1.000
CAL	0.000	1.326				
5'	0.000	2.500	1.000	81.196	32.078	1.000
SUM						
S1						
S2						
S3						
S4						
S5						
S6						
S7						
S8						

Internal Reference Calibration, performed Wed Dec 31 17:00:00 1969:

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	0.000	1.326	1.000	0.000

Air Zero Calibration, performed Wed Dec 31 17:00:00 1969:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1			
S2			
S3			
S4			
S5			
S6			
S7			
S8			

Temperature Calibration Report

Serial Number:	1681			
Tool Model:	168			
Performed:	Wed Mar 10 08:15:15 2010			
	Reference		Reading	
Low Reference:	0.00	degF	0.00	usec
High Reference:	1.00	degF	1.00	usec
Gain:	1.00			
Offset:	-200.00			
Delta Spacing	2			