Company: High Plains Energy LLC
Well: Sure Ridge Well 13-7
Field: Sure Ridge
County: Logan
State:
Country: United States
Job Number: 1
Run Number: 1
Date: 2014-03-17
Surface Coordinates: Not Specified
Declination: 0.00
Grid Convention: No Grid Correction
Vertical Section Azimuth: 0.00
Vertical Section Origin: 0.00 ft, 0.00 ft
Permanent Datum: Ground Level
Elevation: 3,240.00 ft
Log Measured From: Kelly Bushing
Above Permanent Datum: 12.00 ft
Elevation: 3,252.00 ft

PRIMARY
HIGH RESOLUTION SECTION GAMMA RAY

All interpretations are expressed and intended as opinions or best assessments by Pioneer Wireline Services, LLC and its employees. Pioneer Wireline Services, LLC will not be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of its officers, agents or employees.

Comments

Annular volume calculated for 5 1/2" casing
Mid Continent Rig 1
Thank you for using Pioneer Energy Services

Service	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	ID (in)
GR	0.00		CHC-I-75	1.00	3.75	90.00
CNL/DC CNSDC	0.07 4.17		CNT-PS (853)	2.83	3.50	40.00
DCAL CAL SDC	11.84 13.84 13.17		CNT-PS (853)	5.00	3.50	70.00
RILLT	17.52		CDL-PSI (934)	4.50	5.00	295.00
CILD	23.67		CNL-PS (1524)	18.25	3.75	175.00
CILM	28.42					
SP	32.42					

Caliper1 Total Length: 32.42 ft
Tool String ID: 1 Total Weight: 600.00 lb
Instrument Set: Neutron/Dual Rad
OD: 5.38 in

Database File: 13445.db
Dataset Pathname: pass1
Presentation Format: gamma
Dataset Creation: Sat Mar 29 04:07:37 2014
Charted by: Depth only scale 1:240

		Deep Resistivity (Ohm-m)	2000
0	SP (mV) 200	0.2 Shallow Resistivity (Ohm-m)	2000
		0.2 Medium Resistivity (Ohm-m)	2000
		0.2 Rt (Ohm-m)	2000

Gamma Ray (GAPI) 0 400

3550
3600
3650
3700
3750
3800
3850
4000
4050
4100
4150
4200
4250
4300
4350
4400
4450
4500
4550
4600
4650
4700
4750
4800
4850
4900
4950
5000

Gamma Ray
Medium Resistivity
Deep Resistivity
Logger's TD - 4531

		Deep Resistivity (Ohm-m)	2000
0	Gamma Ray (GAPI) 200	0.2 Shallow Resistivity (Ohm-m)	2000
	SP (mV) 200	0.2 Medium Resistivity (Ohm-m)	2000
		0.2 Rt (Ohm-m)	2000

Database File: 13445.db
Dataset Pathname: pass1
Presentation Format: gamma
Dataset Creation: Sat Mar 29 03:41:35 2014 by Calc Open Cavern 10X2
Charted by: Depth only scale 1:240 Caliper1 Total Length: 32.42 ft String ID: 1 Total Weight: 600.00 lb

		Deep Resistivity (Ohm-m)	2000
0	SP (mV) 200	0.2 Shallow Resistivity (Ohm-m)	2000
		0.2 Medium Resistivity (Ohm-m)	2000
		0.2 Rt (Ohm-m)	2000

Gamma Ray (GAPI) 0 400

4000
4050
4100
4150
4200
4250
4300
4350
4400
4450
4500
4550
4600
4650
4700
4750
4800
4850
4900
4950
5000

Gamma Ray
Medium Resistivity
Deep Resistivity
Logger's TD - 4531

		Deep Resistivity (Ohm-m)	2000
0	Gamma Ray (GAPI) 200	0.2 Shallow Resistivity (Ohm-m)	2000
	SP (mV) 200	0.2 Medium Resistivity (Ohm-m)	2000
		0.2 Rt (Ohm-m)	2000

Database File: 13445.db
Dataset Pathname: pass1
Presentation Format: gamma
Dataset Creation: Sat Mar 29 04:07:37 2014 by Calc Open Cavern 10X2
Charted by: Depth only scale 1:240

Calibration Report

Dual Induction Calibration Report

Serial Number	Date Performed
1	Wed Mar 05 17:46:16 2014

	Readings			References			Results	
Units	Air	Loop		Air	Loop		m	b
Deep Conductor	0.000 0.000	1.000 1.000		0.000 0.000	1.000 1.000	mmho/m mmho/m	0.978 0.981	-0.000 -0.000

Compensated Density Calibration Report

Serial Number	Date Performed
1	Wed Mar 05 17:46:21 2014

Master Calibration (Master Calibration Performed)

Density		Pe Detector	Near Detector
Standard	Measured		
Magnesium	1.740 g/cc	4523.22	3537.00 cps
Aluminum	2.710 g/cc	4523.22	3537.00 cps
Spine Angle = 75.67		Density/Spine Ratio = 0.744	
Bore		Reading	
Small Ring	4.750 in	1.48	
Large Ring	5.500 in	1.48	

Compensated Neutron Calibration Report

Serial Number	ID
853	853

CALIBRATION

Detector	Readings	Target	Normalization
Short Space	1.00 n/a	1.00 n/a	1.0000
Long Space	1.00 n/a	1.00 n/a	1.0000

Gamma Ray Calibration Report

Serial Number	ID
853	853

Calibration Performed
Wed Mar 05 17:46:16 2014

Calibrator Value	1.0 GAPI
Background Reading	n/a cps
Calibration Reading	1.0 cps
Sensitivity	0.0000 GAPI/cps