

Linn Operating, Inc.
Chevron 18-434D
API # 05-045-11037-0000
NWNW Sec 20 Twn 6S Rng 96W
Garfield County, Colorado

Prepared Kelly Ramirez
Updated 6/17/2014

Rig Nabors 903

5847 KB
5831 GL
16 KB-GL

237 BHT

TOC @ 1715'

11/29/2005 Spud
12/3/2005 Set Surf
12/16/2005 Set Prod
2/17/2006 Logging
3/13/2006 Frac Stgs 1-10
4/21/2006 Land tbg
5/1/2014 Sand cleanout
and Tubing repair

Marker Jts @
4092.1 & 6381.66

Wellhead

20" hole @ 108'
16" 109# C-75 Conductor @ 108'

12-1/4" hole @ 2532'
56 jts 9-5/8" 36# J-55 surf csg @ 2530', FS @ 2507' FC @ 2461'
Cmtd 740 sx 35/65 lead @ 12.7 ppg & 1.93 yld and 300 sx G tail @ 15.8 ppg & 1.16 yld

Equipment in Hole	Qty	Length	Depth
KB		16.00	16.00
Tbg hanger		0.85	16.85
2-3/8" 4.7# L-80 Tbg	219	7051.09	7067.94
SN 1.78" ID	1	1.10	7069.04
2-3/8" 4.7# L-80 Tbg	1	32.40	7101.44
Notched Collar	1	0.45	7101.89

Stage 10: 5246 - 5358', 20 holes @ 2 spf
Frac'd 125805 lb 20/40 white sand, ?? bbl

Stage 9: 5430 - 5554', 20 holes @ 2 spf
Frac'd 103850 lb 20/40 white sand, 2219 bbl

Stage 8: 5622 - 5748', 24 holes @ 2 spf
Frac'd 179139 lb 20/40 white sand, 3670 bbl

Stage 7: 8544 - 6046', 24 holes @ 2 spf
Frac'd 256197 lb 20/40 white sand, 5360 bbl

Stage 6: 6186 - 6338', 24 holes @ 2 spf
Frac'd 106976 lb 20/40 white sand, ?? Bbl

Stage 5: 6427 - 6580', 22 holes @ 2 spf
Frac'd 130018 lb 20/40 white sand, 3586 bbl

Stage 4: 6636 - 6824', 24 holes @ 2 spf
Frac'd 109927 lb 20/40 white sand, ?? Bbl

Stage 3: 6930 - 7061', 22 holes @ 2 spf
Frac'd 75368 lb 20/40 white sand, 2305 bbl

Stage 2: 7120 - 7308', 24 holes @ 2 spf
Frac'd 79491 lb 20/40 white sand, 2689 bbl

Stage 1: 7378 - 7706', 20 holes @ 2 spf
Frac'd 138511 lb 20/40 white sand, 3626 bbl

7-7/8" hole @ 7925'
209 jts 4-1/2" 11.6# N-80 prod csg @ 7898'
Cmtd 150 sx lead @ 12 ppg & 1.78 Yld & 1055 sx tail @ 13.5 ppg, 1.68 Yld

PBTD @ 7855' WL Tag on 2/17/2006