



**LEASE INFORMATION**

Using standard QtrQtr, Sec, Twp, Rng format, describe one entire mineral lease that will be produced by this well (Describe lease beneath surface location if produced. Attach separate description page or map if necessary.)

T6S, R54W, SEC 33:ALL

Total Acres in Described Lease: 640 Described Mineral Lease is:  Fee  State  Federal  Indian

Federal or State Lease # \_\_\_\_\_

Distance from Completed Portion of Wellbore to Nearest Lease Line of described lease: 640 Feet

**CULTURAL DISTANCE INFORMATION**

Distance to nearest:

Building: 3305 Feet

Building Unit: 3316 Feet

High Occupancy Building Unit: 5280 Feet

Designated Outside Activity Area: 5280 Feet

Public Road: 3111 Feet

Above Ground Utility: 3210 Feet

Railroad: 5280 Feet

Property Line: 416 Feet

**INSTRUCTIONS:**

- All measurements shall be provided from center of the Proposed Well to nearest of each cultural feature as described in Rule 303.a.(5).

- Enter 5280 for distance greater than 1 mile.

- Building - nearest building of any type. If nearest Building is a Building Unit, enter same distance for both.

- Building Unit, High Occupancy Building Unit, and Designated Outside Activity Area - as defined in 100-Series Rules.

**DESIGNATED SETBACK LOCATION INFORMATION**

Check all that apply. This location is within a:  Buffer Zone  
 Exception Zone  
 Urban Mitigation Area

- Buffer Zone – as described in Rule 604.a.(2), within 1,000' of a Building Unit

- Exception Zone - as described in Rule 604.a.(1), within 500' of a Building Unit.

- Urban Mitigation Area - as defined in 100-Series Rules.

Pre-application Notifications (required if location is within 1,000 feet of a building unit):

Date of Rule 305.a.(1) Urban Mitigation Area Notification to Local Government: \_\_\_\_\_

Date of Rule 305.a.(2) Buffer Zone Notification to Building Unit Owners: \_\_\_\_\_

**SPACING and UNIT INFORMATION**

Distance from Completed Portion of Wellbore to Nearest Wellbore Permitted or Completed in the same formation: 1248 Feet

Distance from Completed Portion of Wellbore to Nearest Unit Boundary \_\_\_\_\_ Feet (Enter 5280 for distance greater than 1 mile.)

Federal or State Unit Name (if appl): \_\_\_\_\_ Unit Number: \_\_\_\_\_

**SPACING & FORMATIONS COMMENTS**

\_\_\_\_\_

**OBJECTIVE FORMATIONS**

Objective Formation(s)	Formation Code	Spacing Order Number(s)	Unit Acreage Assigned to Well	Unit Configuration (N/2, SE/4, etc.)
ATOKA	ATOK			
CHEROKEE	CHRK			
LANSING-KANSAS CITY	LGKC			
MARMATON	MRTN			
MISSISSIPPIAN-SPERGEN	MS-SP			
WOLFCAMP	WFCMP			

**DRILLING PROGRAM**

Proposed Total Measured Depth: 9012 Feet

Distance to nearest permitted or existing wellbore penetrating objective formation: 1248 Feet (Including plugged wells)

Will a closed-loop drilling system be used? No

Is H<sub>2</sub>S gas reasonably expected to be encountered during drilling operations at concentrations greater than or equal to 100 ppm? No (If Yes, attach an H<sub>2</sub>S Drilling Operations Plan)

Will salt sections be encountered during drilling? No

Will salt based (>15,000 ppm Cl) drilling fluids be used? No

Will oil based drilling fluids be used? No

BOP Equipment Type:  Annular Preventor  Double Ram  Rotating Head  None

### GROUNDWATER BASELINE SAMPLING AND MONITORING AND WATER WELL SAMPLING

Water well sampling required per Rule 609

### DRILLING WASTE MANAGEMENT PROGRAM

Drilling Fluids Disposal: ONSITE Drilling Fluids Disposal Methods: Recycle/reuse

Cuttings Disposal: ONSITE Cuttings Disposal Method: Drilling pit

Other Disposal Description:

BACKFILL WHEN DRY

Beneficial reuse or land application plan submitted? \_\_\_\_\_

Reuse Facility ID: \_\_\_\_\_ or Document Number: \_\_\_\_\_

### CASING PROGRAM

Casing Type	Size of Hole	Size of Casing	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top
SURF	12+1/4	8+5/8	24	0	350	122	350	0
1ST	7+7/8	5+1/2	17	0	9012	1109	9012	0

Conductor Casing is NOT planned

### DESIGNATED SETBACK LOCATION EXCEPTIONS

Check all that apply:

- Rule 604.a.(1)A. Exception Zone (within 500' of Building Unit)
- Rule 604.b.(1)A. Exception Location (existing or approved Oil & Gas Location now within a Designated Setback as a result of Rule 604.a.)
- Rule 604.b.(1)B. Exception Location (existing or approved Oil & Gas Location is within a Designated Setback due to Building Unit construction after Location approval)
- Rule 604.b.(2) Exception Location (SUA or site-specific development plan executed on or before August 1, 2013)
- Rule 604.b.(3) Exception Location (Building Units constructed after August 1, 2013 within setback per an SUA or site-specific development plan)

### GREATER WATTENBERG AREA LOCATION EXCEPTIONS

Check all that apply:

- Rule 318A.a. Exception Location (GWA Windows).
- Rule 318A.c. Exception Location (GWA Twinning).

### RULE 502.b VARIANCE REQUEST

- Rule 502.b. Variance Request from COGCC Rule or Spacing Order Number \_\_\_\_\_

**OTHER LOCATION EXCEPTIONS**

Check all that apply:

Rule 318.c. Exception Location from Rule or Spacing Order Number \_\_\_\_\_

Rule 603.a.(2) Exception Location (Property Line Setback).

ALL exceptions and variances require attached Request Letter(s). Refer to applicable rule for additional required attachments (e.g. waivers, certifications, SUAs).

**OPERATOR COMMENTS AND SUBMITTAL**

Comments CEMENT DESIGN FOR FIRST STRING:  
12.0 PPG LEAD CEMENT DESIGNED TO SURFACE W/745 SACKS OF CEMENT  
13.0 PPG TAIL CEMENT DESIGNED TO 6000' W/364 SACKS OF CEMENT

This application is in a Comprehensive Drilling Plan \_\_\_\_\_ CDP #: \_\_\_\_\_

Location ID: \_\_\_\_\_

Is this application being submitted with an Oil and Gas Location Assessment application? Yes

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: KYLA HOWL

Title: AGENT FOR NIGHTHAWK Date: 6/3/2014 Email: KHOWL@LTENV.COM

Operator must have a valid water right or permit allowing for industrial use or purchased water from a seller that has a valid water right or permit allowing for industrial use, otherwise an application for a change in type of use is required under Colorado law. Operator must also use the water in the location set forth in the water right decree or well permit, otherwise an application for a change in place of use is required under Colorado law. Section 37-92-103(5), C.R.S. (2011).

Based on the information provided herein, this Application for Permit-to-Drill complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved:  Director of COGCC Date: 7/12/2014

Expiration Date: 07/11/2016

**API NUMBER**  
05 073 06626 00

## Conditions Of Approval

All representations, stipulations and conditions of approval stated in the Form 2A for this location shall constitute representations, stipulations and conditions of approval for this Form 2 Permit-to-Drill and are enforceable to the same extent as all other representations, stipulations and conditions of approval stated in this Permit-to-Drill.

<u>COA Type</u>	<u>Description</u>
	<p>1) Provide 48 hour notice prior to spud via electronic Form 42.</p> <p>2) If production casing is set provide cement coverage to at least 200' above shallowest completed interval and cement Cheyenne/Dakota interval: (5150'-4550' minimum). Run and submit CBL to verify cemented intervals.</p> <p>3) If well is a dry hole set plugs at the following depths: 40 sks cement +/- 50' above the Spergen, 40 sks cement +/- 50' above any DST w/ show, 40 sks cement at 5150' up, 40 sks cement at 4550' up, 50 sks cement from 50' below surface casing shoe up into surface casing, 15 sks cement in top of surface casing, cut 4 ft below GL, weld on plate, 5 sks cement each in rat hole and mouse hole.</p>
	<p>Open hole resistivity and gamma logs shall be run to describe the stratigraphy of the entire well bore and to adequately verify the setting depth of surface casing and aquifer coverage. On a multi-well pad, these open hole logs are only required on one of the first wells drilled on the pad and the Drilling Completion Report - Form 5 for every well on the pad shall identify which well was logged.</p>

## Best Management Practices

<u>No</u>	<u>BMP/COA Type</u>	<u>Description</u>
1	Construction	<p>Certificate to Discharge Under CDPHE Under General Permit No. COR-030000 Stormwater Discharges Associated with Construction Certification No. COR031825</p> <p>Prior to construction, perimeter controls will be installed utilizing cuttings from the clearing operations.</p> <p>Once the well pad has been constructed a variety of BMP's shall be utilized for the site specific conditions.</p> <p>BMP's to be utilized may include, but are not limited to:</p> <ul style="list-style-type: none"> <li>-Dirt Ditch/Berm</li> <li>-Erosion Control Blankets</li> <li>-Straw Bale Barrier</li> <li>-Straw Wattles</li> <li>-Seeding</li> <li>-Imported Hard Armor</li> <li>-Check Dams</li> <li>-Culvert/Culvert Protection</li> <li>-Crimped Straw</li> <li>-Silt Fence</li> <li>-Surface Roughening/Surface Rip</li> </ul> <p>During construction, each site will be inspected every 14 days and 24-72 hours after any precipitation event causing erosion depending on the current site activities. These inspections will be recorded and maintained at Nighthawk's office. Repairs shall be completed as soon as possible after an inspection reporting BMP repairs are required.</p> <p>Any site specific modifications will be revised on the site plan when implemented at the site. A field wide Stormwater Management Plan (SWMP) for the Project Area is located at Nighthawk's office. Spill Protection Control and Countermeasures (SPCC) plans for the Project Area are stored on file at Nighthawk's office.</p> <p>The field wide SWMP addresses SPCC during construction operations.</p>

Total: 1 comment(s)

## Applicable Policies and Notices to Operators

Notice Concerning Operating Requirements for Wildlife Protection.

## Attachment Check List

<b>Att Doc Num</b>	<b>Name</b>
2519160	WELL LOCATION PLAT
400602532	FORM 2 SUBMITTED
400602554	WELL LOCATION PLAT
400602556	DEVIATED DRILLING PLAN
400602557	TOPO MAP
400602560	SURFACE AGRMT/SURETY
400620805	DIRECTIONAL DATA

Total Attach: 7 Files

### General Comments

<b>User Group</b>	<b>Comment</b>	<b>Comment Date</b>
Final Review	Changed production casing (5+1/2" first string) cement top from 6000 feet to 0 feet (surface) to reflect operator's comment, which states, "...LEAD CEMENT DESIGNED TO SURFACE..."	7/12/2014 6:42:07 PM
Permit	Final review completed; no public comment received.	7/10/2014 9:51:53 AM
Permit	Added additional well location plat that shows the whole section.	6/10/2014 8:48:14 AM
Permit	Well location plat describes only the NW/4. Missing map that describes the whole section.	5/6/2014 8:05:25 AM
LGD	County Permit #1469	5/4/2014 2:54:30 PM
Permit	Passed completeness. All total MDs match up and directional data has been attached.	5/4/2014 2:33:18 PM
Permit	Return to draft: 1. Missing directional data attachment 2. Proposed MD and casing reflect the total TVD of 9000 ft rather than 9012 MD.	6/4/2014 11:23:00 AM

Total: 7 comment(s)