

FORM  
2A

Rev  
08/13

State of Colorado  
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203  
Phone: (303) 894-2100 Fax: (303) 894-2109



Document Number:

400610770

Date Received:

07/21/2014

Oil and Gas Location Assessment

New Location     Refile     Amend Existing Location    Location#: \_\_\_\_\_

Submit signed original form. This Oil and Gas Location Assessment is to be submitted to the COGCC for approval prior to any ground disturbance activity associated with oil and gas operations. Approval of this Oil and Gas Location Assessment will allow for the construction of the below specified Location; however, it does not supersede any land use rules applied by the local land use authority. Please see the COGCC website at <http://cogcc.state.co.us/> for all accompanying information pertinent this Oil and Gas Location Assessment.

Location ID:

**438722**

Expiration Date:

**08/30/2017**

This location assessment is included as part of a permit application.

CONSULTATION

This location is included in a Comprehensive Drilling Plan. CDP # \_\_\_\_\_

This location is in a sensitive wildlife habitat area.

This location is in a wildlife restricted surface occupancy area.

This location includes a Rule 306.d.(1)A.ii. variance request.

Operator

Operator Number: 100185  
Name: ENCANA OIL & GAS (USA) INC  
Address: 370 17TH ST STE 1700  
City: DENVER State: CO Zip: 80202-5632

Contact Information

Name: Bonnie Lamond  
Phone: (720) 876-5156  
Fax: ( )  
email: bonnie.lamond@encana.com

RECLAMATION FINANCIAL ASSURANCE

Plugging and Abandonment Bond Surety ID: 20100017     Gas Facility Surety ID: \_\_\_\_\_  
 Waste Management Surety ID: \_\_\_\_\_

LOCATION IDENTIFICATION

Name: Kiyota Number: 35H-O367

County: WELD

Quarter: SWSE Section: 35 Township: 3N Range: 67W Meridian: 6 Ground Elevation: 4838

Define a single point as a location reference for the facility location. When the location is to be used as a well site then the point shall be a well location.

Footage at surface: 450 feet FSL from North or South section line

1509 feet FEL from East or West section line

Latitude: 40.175556 Longitude: -104.853718

PDOP Reading: 1.4 Date of Measurement: 07/11/2014

Instrument Operator's Name: C. Bettencourt

## RELATED REMOTE LOCATIONS

(Enter as many Related Locations as necessary. Enter the Form 2A document # only if there is no established COGCC Location ID#)

This proposed Oil and Gas Location is:

LOCATION ID # FORM 2A DOC #



## FACILITIES

Indicate the number of each type of oil and gas facility planned on location

Wells	<u>12</u>	Oil Tanks	<u>28</u>	Condensate Tanks	<u>        </u>	Water Tanks	<u>6</u>	Buried Produced Water Vaults	<u>        </u>
Drilling Pits	<u>        </u>	Production Pits	<u>        </u>	Special Purpose Pits	<u>        </u>	Multi-Well Pits	<u>        </u>	Temporary Large Volume Above Ground Tanks	<u>        </u>
Pump Jacks	<u>        </u>	Separators	<u>12</u>	Injection Pumps	<u>        </u>	Cavity Pumps	<u>        </u>		
Gas or Diesel Motors	<u>        </u>	Electric Motors	<u>        </u>	Electric Generators	<u>        </u>	Fuel Tanks	<u>        </u>	Gas Compressors	<u>        </u>
Dehydrator Units	<u>        </u>	Vapor Recovery Unit	<u>8</u>	VOC Combustor	<u>13</u>	Flare	<u>        </u>	LACT Unit	<u>        </u>
								Pigging Station	<u>        </u>

## OTHER FACILITIES

Other Facility Type

Number

<input type="text"/>	<input type="text"/>
----------------------	----------------------

Per Rule 303.b.(3)C, description of all oil, gas, and/or water pipelines:

In addition to the equipment above, there will be 1 VRT and 1 buffer.

## CONSTRUCTION

Date planned to commence construction: 11/15/2014 Size of disturbed area during construction in acres: 16.00

Estimated date that interim reclamation will begin: 11/15/2015 Size of location after interim reclamation in acres: 6.50

Estimated post-construction ground elevation: 4839

## DRILLING PROGRAM

Will a closed loop system be used for drilling fluids: Yes

Is H<sub>2</sub>S anticipated? No

Will salt sections be encountered during drilling: No

Will salt based mud (>15,000 ppm Cl) be used? No

Will oil based drilling fluids be used? No

## DRILLING WASTE MANAGEMENT PROGRAM

Drilling Fluids Disposal: OFFSITE Drilling Fluids Disposal Method: Commercial Disposal

Cutting Disposal: OFFSITE Cuttings Disposal Method: Commercial Disposal

Other Disposal Description:

Beneficial reuse or land application plan submitted?         

Reuse Facility ID:          or Document Number:         

Centralized E&P Waste Management Facility ID, if applicable:         

## SURFACE & MINERALS & RIGHT TO CONSTRUCT

Name: Kiyota Properties, LLC

Phone:

Address: 11964 County Rd 21.5

Fax: \_\_\_\_\_

Address: \_\_\_\_\_

Email: \_\_\_\_\_

City: Fort Lupton State: CO Zip: 80621

Surface Owner:  Fee  State  Federal  Indian

Check all that apply. The Surface Owner:  is the mineral owner  
 is committed to an oil and Gas Lease  
 has signed the Oil and Gas Lease  
 is the applicant

The Mineral Owner beneath this Oil and Gas Location is:  Fee  State  Federal  Indian

The Minerals beneath this Oil and Gas Location will be developed from or produced to this Oil and Gas Location: Yes

The right to construct this Oil and Gas Location is granted by: Surface Use Agreement

Surface damage assurance if no agreement is in place: \_\_\_\_\_ Surface Surety ID: \_\_\_\_\_

Date of Rule 306 surface owner consultation 03/17/2014

### CURRENT AND FUTURE LAND USE

Current Land Use (Check all that apply):

Crop Land:  Irrigated  Dry land  Improved Pasture  Hay Meadow  CRP

Non-Crop Land:  Rangeland  Timber  Recreational  Other (describe): \_\_\_\_\_

Subdivided:  Industrial  Commercial  Residential

Future Land Use (Check all that apply):

Crop Land:  Irrigated  Dry land  Improved Pasture  Hay Meadow  CRP

Non-Crop Land:  Rangeland  Timber  Recreational  Other (describe): \_\_\_\_\_

Subdivided:  Industrial  Commercial  Residential

## CULTURAL DISTANCE INFORMATION

Distance to nearest:

Building: 357 Feet  
Building Unit: 930 Feet  
High Occupancy Building Unit: 5280 Feet  
Designated Outside Activity Area: 5280 Feet  
Public Road: 1128 Feet  
Above Ground Utility: 450 Feet  
Railroad: 5280 Feet  
Property Line: 450 Feet

### INSTRUCTIONS:

- All measurements shall be provided from center of nearest Well or edge of nearest Production Facility to nearest of each cultural feature as described in Rule 303.b.(3)A.  
- Enter 5280 for distance greater than 1 mile.  
- Building - nearest building of any type. If nearest Building is a Building Unit, enter same distance for both.  
- Building Unit, High Occupancy Building Unit, and Designated Outside Activity Area - as defined in 100-Series Rules.

## DESIGNATED SETBACK LOCATION INFORMATION

Check all that apply. This location is within a:  Buffer Zone  
 Exception Zone  
 Urban Mitigation Area

- Buffer Zone - as described in Rule 604.a.(2), within 1,000' of a Building Unit.  
- Exception Zone - as described in Rule 604.a.(1), within 500' of a Building Unit.  
- Urban Mitigation Area - as defined in 100-Series Rules.

Pre-application Notifications (required if location is within 1,000 feet of a building unit):

Date of Rule 305.a.(1) Urban Mitigation Area Notification to Local Government: \_\_\_\_\_  
Date of Rule 305.a.(2) Buffer Zone Notification to Building Unit Owners: 05/21/2014

## SOIL

List all soil map units that occur within the proposed location. attach the National Resource Conservation Service (NRCS) report showing the "Map Unit Description" report listing the soil typical vertical profile. This data is to used when segregating topsoil.

The required information can be obtained from the NRCS web site at <http://soildatamart.nrcs.usda.org/> or from the COGCC web site GIS Online map page found at <http://colorado.gov/cogcc>. Instructions are provided within the COGCC web site help section.

NRCS Map Unit Name: Vona sandy loam, 1 to 3 percent slopes  
NRCS Map Unit Name: \_\_\_\_\_  
NRCS Map Unit Name: \_\_\_\_\_

## PLANT COMMUNITY:

Complete this section only if any portion of the disturbed area of the location's current land use is on non-crop land.

Are noxious weeds present: Yes  No   
Plant species from:  NRCS or,  field observation Date of observation: \_\_\_\_\_  
List individual species: \_\_\_\_\_

Check all plant communities that exist in the disturbed area.

- Disturbed Grassland (Cactus, Yucca, Cheatgrass, Rye)  
 Native Grassland (Bluestem, Grama, Wheatgrass, Buffalograss, Fescue, Oatgrass, Brome)  
 Shrub Land (Mahogany, Oak, Sage, Serviceberry, Chokecherry)  
 Plains Riparian (Cottonwood, Willow, Aspen, Maple, Poplar, Russian Olive, Tamarisk)  
 Mountain Riparian (Cottonwood, Willow, Blue Spruce)  
 Forest Land (Spruce, Fir, Ponderosa Pine, Lodgepole Pine, Juniper, Pinyon, Aspen)  
 Wetlands Aquatic (Bullrush, Sedge, Cattail, Arrowhead)  
 Alpine (above timberline)  
 Other (describe): \_\_\_\_\_

## WATER RESOURCES

Is this a sensitive area:  No  Yes

Distance to nearest

downgradient surface water feature: 817 Feet

water well: 530 Feet

Estimated depth to ground water at Oil and Gas Location 20 Feet

Basis for depth to groundwater and sensitive area determination:

Basis for depth to ground water and sensitive area determination is from Division of Water Resources Water Well Data.

Is the location in a riparian area:  No  Yes

Was an Army Corps of Engineers Section 404 permit filed  No  Yes If yes attach permit.

Is the location within a Rule 317B Surface Water Supply Area buffer No zone:

If the location is within a Rule 317B Surface Water Supply Area buffer have all public water supply systems within 15 miles been notified: \_\_\_\_\_

## GROUNDWATER BASELINE SAMPLING AND MONITORING AND WATER WELL SAMPLING

Water well sampling required per Rule 318A

## DESIGNATED SETBACK LOCATION EXCEPTIONS

Check all that apply:

- Rule 604.a.(1)A. Exception Zone (within 500' of Building Unit)
- Rule 604.b.(1)A. Exception Location (existing or approved Oil & Gas Location now within a Designated Setback as a result of Rule 604.a.)
- Rule 604.b.(1)B. Exception Location (existing or approved Oil & Gas Location is within a Designated Setback due to Building Unit construction after Location approval)
- Rule 604.b.(2) Exception Location (SUA or site-specific development plan executed on or before August 1, 2013)
- Rule 604.b.(3) Exception Location (Building Units constructed after August 1, 2013 within setback per an SUA or site-specific development plan)

## RULE 502.b VARIANCE REQUEST

- Rule 502.b. Variance Request from COGCC Rule or Spacing Order Number \_\_\_\_\_

ALL exceptions and variances require attached Request Letter(s). Refer to applicable rule for additional required attachments (e.g. waivers, certifications, SUAs).

## OPERATOR COMMENTS AND SUBMITTAL

Comments

A temporary completions area, operated by a 3rd party, approximately four acres will be utilized for up to 3 fresh water storage tanks to be used during completions operations. This area will be completely reclaimed; please see attached map for visual reference. Distances are measured from the proposed 4F-35H-O367 well head.

I hereby certify that the statements made in this form are, to the best of my knowledge, true, correct and complete.

Signed: \_\_\_\_\_ Date: 07/21/2014 Email: bonnie.lamond@encana.com

Print Name: Bonnie Lamond Title: Regulatory Analyst

Based on the information provided herein, this Application for Permit-to-Drill complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved:  Director of COGCC Date: 8/31/2014

### **Conditions Of Approval**

**All representations, stipulations and conditions of approval stated in this Form 2A for this location shall constitute representations, stipulations and conditions of approval for any and all subsequent operations on the location unless this Form 2A is modified by Sundry Notice, Form 4 or an Amended Form 2A.**

<b><u>COA Type</u></b>	<b><u>Description</u></b>

### **Best Management Practices**

<b><u>No</u></b>	<b><u>BMP/COA Type</u></b>	<b><u>Description</u></b>
1	General Housekeeping	Any material not in use that might constitute a fire hazard will be removed a minimum of twenty-five (25) feet from the wellhead, tanks and separator. Any electrical equipment installations inside the bermed area will comply with API RP 500 classifications and comply with the current national electrical code as adopted by the State of Colorado.
2	General Housekeeping	All surface trash, debris, scrap or discarded material connected with the operations of the property shall be removed from the premises or disposed of in a legal manner.
3	General Housekeeping	The well site will be cleared of all non-essential equipment, trash and debris after ninety days of a well P&A.
4	General Housekeeping	Encana will identify plugged and abandoned wellbores according to Rule 319.a.(5). including the location of the wellbore with a permanent monument as specified in Rule 319.a.(5). Encana will also inscribe or imbed the well number and date of plugging upon the permanent monument.
5	Material Handling and Spill Prevention	"• Annual hydrostatic test on the oil dump line from the separator to the tank battery. • Annual hydrostatic "static" tests on our oil tanks. • Annual hydrostatic "static" tests on our produced water tank and water dump line from the separator to the produced water tank. • Lease Operator inspections of all equipment not to exceed 48 hours. • Monthly documented inspections (EU). • Annual environmental inspections of all battery and well equipment and pads. • Annual UT inspections of the pressure vessels and input into Encana's RIPL Predictive Integrity Maintenance Program. (HLP separators and fuel gas separators)"
6	Material Handling and Spill Prevention	Well effluent containing more than ten (10) barrels per day of condensate or within two (2) hours after first encountering hydrocarbon gas of salable quality will be directed to a combination of sand traps, separators, surge vessels, and tanks as needed to ensure safe separation of sand, hydrocarbon liquids, water, and gas and to ensure salable products are efficiently recovered for sale or conserved and that non-salable products are disposed of in a safe and environmentally responsible manner.
7	Construction	The pad will be constructed in such a manner that noise mitigation may be installed and removed without disturbing the site or landscaping.

8	Construction	Subject pad will have all weather access roads to allow for operator and emergency response.
9	Construction	Encana utilizes 24" tall corrugated galvanized metal berm walls with a capacity in excess of 150% of the largest tank contained within the wall. In addition, Encana best practices mandates the use of impervious liners that extends under each storage tank and up the walls, permanently affixed to the top of the metal berm wall. Protrusions of piping that come through the liner include a fully sealed "boot" to prevent leakage.
10	Construction	At the time of construction, all leasehold roads will be constructed to accommodate local emergency vehicle access requirements, and will be maintained in a reasonable condition.
11	Noise mitigation	Encana will perform a baseline noise survey prior to any operational activity measuring dBA at a distance 350 feet from the noise source (unless there is an occupied structure closer than that – then measurement will be taken 25 feet from the structure). If low frequency noise is a concern, measurement of dBC will be taken 25 feet from the occupied structure towards the noise source. As necessary, based on the survey, Encana will install temporary sound walls to minimize noise and light impacts during drilling and completions and will install permanent noise mitigation at the facility location as necessary to meet all COGCC regulations.
12	Noise mitigation	The subject location will be constructed to allow potential future noise mitigation installation without disturbance.
13	Emissions mitigation	Flow lines, separators, and sand traps capable of supporting green completions as described in Rule 805 will be installed on subject location at which commercial quantities of gas are reasonably expected to be produced based on existing adjacent wells within 1 mile.
14	Emissions mitigation	Temporary flowback flaring and oxidizing equipment will include: adequately sized equipment to handle 1.5 times the largest flowback volume of gas experienced in a ten mile radius. If there is overrun, Encana will shut in the well versus freely venting
15	Drilling/Completion Operations	Closed-top tanks will utilize backpressure systems that exert a minimum of four (4) ounces of backpressure and a maximum that does not exceed the pressure rating of the tank to facilitate gathering and combustion of tank.
16	Drilling/Completion Operations	Upon initial rig-up and at least once every thirty (30) days during drilling operations thereafter, pressure testing of the casing string and each component of the blowout prevention equipment including flange connections will be performed to seventy percent (70%) of working pressure or seventy percent (70%) of the internal yield of casing, whichever is less. Pressure testing shall be conducted and the documented results will be retained by the operator for inspection by the Director for a period of one (1) year. Activation of the pipe rams for function testing shall be conducted on a daily basis when practicable.
17	Drilling/Completion Operations	Adequate blowout prevention equipment will be used on all well servicing operations.
18	Drilling/Completion Operations	Backup stabbing valves shall be required on well servicing operations during reverse circulation. Valves shall be pressure tested before each well servicing operation using both low-pressure air and high-pressure fluid.
19	Drilling/Completion Operations	Guy line anchors in the DJ Basin are not installed. Encana will use an engineered base beam that we guy wire anchor the derricks to.

20	Drilling/Completion Operations	All newly installed or replaced crude oil and condensate storage tanks will be designed, constructed, and maintained in accordance with National Fire Protection Association (NFPA) Code 30 (2008 version). Encana will maintain written records verifying proper design, construction, and maintenance, and will make these records available for inspection by the Director. In addition, onsite inspections are conducted internally to insure guidelines are met.
21	Drilling/Completion Operations	Prior to drilling operations, Operator will perform an anti-collision scan of existing offset wells that have the potential of being within close proximity of the proposed well. This anti-collision scan will include definitive MWD or gyro surveys of the offset wells with included error of uncertainty per survey instrument, and compared against the proposed wellpath with its respective error of uncertainty. If current surveys do not exist for the offset wells, Operator may have gyro surveys conducted to verify bottomhole location. The proposed well will only be drilled if the anti-collision scan results indicate that there is not a risk for collision, or harm to people or the environment. For the proposed well, upon conclusion of drilling operations, an as-constructed gyro survey will be submitted to COGCC with the Form 5.
22	Drilling/Completion Operations	Encana will comply with the "COGCC Policy for Bradenhead Monitoring During Hydraulic Fracturing Treatments in the Greater Wattenberg Area", dated May 29, 2012.
23	Drilling/Completion Operations	Encana will utilize a closed-loop system for drilling operations at this location.
24	Drilling/Completion Operations	Encana will not utilize pits.
25	Drilling/Completion Operations	Upon initial rig-up and at least once every thirty (30) days during drilling operations thereafter, pressure testing of the casing string and each component of the blowout prevention equipment including flange connections will be performed to seventy percent (70%) of working pressure or seventy percent (70%) of the internal yield of casing, whichever is less. Pressure testing will be conducted and the documented results will be retained by the operator for inspection by the Director for a period of one (1) year. Activation of the pipe rams for function testing will be conducted on a daily basis when practicable.
26	Drilling/Completion Operations	Adequate blowout prevention equipment will be used on all well servicing operations.
27	Drilling/Completion Operations	Backup stabbing valves will be used on well servicing operations during reverse circulation. Valves will be pressure tested before each well servicing operation using both low-pressure air and high-pressure fluid.

Total: 27 comment(s)

## Attachment Check List

<b>Att Doc Num</b>	<b>Name</b>
400610770	FORM 2A SUBMITTED
400643406	ACCESS ROAD MAP
400643414	MULTI-WELL PLAN
400643418	OTHER
400648287	LOCATION DRAWING
400648288	LOCATION PICTURES
400648289	LOCATION PICTURES
400648290	RULE 306.E. CERTIFICATION
400648291	WASTE MANAGEMENT PLAN
400648292	FACILITY LAYOUT DRAWING
400648293	SURFACE AGRMT/SURETY
400648312	OTHER
400648317	HYDROLOGY MAP
400648318	NRCS MAP UNIT DESC

Total Attach: 14 Files

## General Comments

<b>User Group</b>	<b>Comment</b>	<b>Comment Date</b>
Final Review	Removed "Well Site is served by Production Facilities FORM 2A DOC #400610776"; form was deleted from system - all production facilities are on this location.	8/31/2014 10:22:24 AM
Permit	Final Review Completed. No LGD or public comment received.	8/29/2014 9:44:15 AM
Permit	The Certification of Compliance with Rule 305.a is under other. ok to pass.	8/15/2014 2:16:09 PM
OGLA	Changed distance to nearest building unit to 930 feet as shown on the Location Drawing. Changed land use to improved pasture as indicated on the Location Pictures. Review completed 8/6/2014.	7/30/2014 12:56:46 PM
Permit	Passed completeness.	7/23/2014 9:08:42 AM

Total: 5 comment(s)