Company: SCHLUMBERGER
Well: 15/9-F-15 A
Field: SLEIPNER
Location: 58° 25' 54.00" N 2° 27' 29.00" E
Country: NORWAY

Run No. 1 | Run No. 2 | Run No. 3
Depth Datum: Rotary Table | Depth Datum: Rotary Table | Depth Datum: Rotary Table
Permanent Datum: MEAN SEA LEVEL | Permanent Datum: MEAN SEA LEVEL | Permanent Datum: MEAN SEA LEVEL
Elevation: 0 m | Elevation: 0 m | Elevation: 0 m
Log Measured From: Rotary Table, 24 m Above Permanent Datum | Log Measured From: Rotary Table, 24 m Above Permanent Datum | Log Measured From: Rotary Table, 24 m Above Permanent Datum
Drilling Measured From: Rotary Table | Drilling Measured From: Rotary Table | Drilling Measured From: Rotary Table

	Run No. 1	Run No. 2	Run No. 3
Date	15-Jul-08		
Time Logger on Bottom	15:00		
Max. Recorded Temperature	0 degC		
Bottom Log Interval	4000 m		
Top Log Interval	3700 m		
Casing Driller Size @ Depth	0 m		
Casing Logger Size @ Depth	0 m		
Type Fluid in Hole	WBM		
Density / Viscosity	0 kg/m3		
Ph / Fluid Loss	0		
Source of Sample	Flowline		
Rm @ Meas. Temp	0 ohmm @ 0 degC		
Rmf @ Meas. Temp	0 ohmm @ 0 degC		
Rmc @ Meas. Temp	0 ohmm @ 0 degC		
Source of Rmf / Rmc	Flowline		
Rm @ BHT	0 ohmm @ 0 degC		
Time Since Circulation	0 hr		
Max. Rec. Temp.	0 degC		
Equipment Number	0		
Location	0		
Recorded By	0		
Witnessed By	0		

PRELIMINARY
Schlumberger

Gamma Ray (GR) (GAPI) 0 to 150 | Resistivity (RT) (OHMM) 0.2 to 2000 | Neutron Porosity (NPHI) (V/V) 0.45 to -0.15 | Bulk Density (RHOB) (G/C3) 1.95 to 2.95

Comments

Disclaimer

The information in or associated with this document is provided by Schlumberger for informational purposes only and is provided "as is" and without any warranty of any kind, express or implied. Schlumberger does not warrant the accuracy, adequacy or completeness of the information and will not be liable for any errors, omissions, damages or losses in connection with the information. Reliance on the information is at the sole risk of the user. Any dispute shall be governed by the laws of England and subject to the exclusive jurisdiction of the courts of England.

Comments

Service	Effective Run	Instrument	Description	Log Top	Log Base
			ARMaPS	3.66	4.70
MGR-H	1 to 1		GR_Probe (GR)	3.66	4.70	46.18
MGR-H	1 to 1		Gamma Ray Sensor Assembly			
			ARMaPS	4.56	4.74
CN	1 to 1		CMR Pad_tool (TX_Pad)	4.26	4.70
CN	1 to 1		Type Pad Compensated Neutron			

Calibration Report

Calibration Run	Run(s) 01-02 / Drilling Job
Calibration Reference	Schlumberger Stavanger Log Center

Calibration Report

Service Run / Calibration Report

Service Name	ARMaPS
Run Number	1
Calibration Report	ARMaPS_1_1.pdf
Calibration Date	15-Jul-08
Calibration Reference	Schlumberger Stavanger Log Center
Accuracy	0.0000 0.0000

Service Run / Calibration Report

Service Name	GR_Probe
Run Number	1
Calibration Report	GR_Probe_1_1.pdf
Calibration Date	15-Jul-08
Calibration Reference	Schlumberger Stavanger Log Center
Accuracy	0.0000 0.0000

Calibration For	Run(s) 01-02 / Drilling Job
Calibration Reference	Schlumberger Stavanger Log Center

Service Run / Calibration Report

Service Name	Gamma Ray Sensor Assembly
Run Number	1
Calibration Report	Gamma Ray Sensor Assembly_1_1.pdf
Calibration Date	15-Jul-08
Calibration Reference	Schlumberger Stavanger Log Center
Accuracy	0.0000 0.0000

Calibration For	Run(s) 01-02 / Drilling Job
Calibration Reference	Schlumberger Stavanger Log Center

Service Run / Calibration Report

Service Name	Compensated Neutron
Run Number	1
Calibration Report	Compensated Neutron_1_1.pdf
Calibration Date	15-Jul-08
Calibration Reference	Schlumberger Stavanger Log Center
Accuracy	0.0000 0.0000

Logging Engineer: | Operating Rig Time: | Logging Unit Number: | Max Rec Temp:

Gamma Ray (GR) (GAPI) 0 to 150 | Resistivity (RT) (OHMM) 0.2 to 2000 | Neutron Porosity (NPHI) (V/V) 0.45 to -0.15 | Bulk Density (RHOB) (G/C3) 1.95 to 2.95