

**FORM
INSP**Rev
05/11**State of Colorado
Oil and Gas Conservation Commission**1120 Lincoln Street, Suite 801, Denver, Colorado 80203
Phone: (303) 894-2100 Fax: (303) 894-2109

DE ET OE ES

Inspection Date:

09/04/2014

Document Number:

675200491

Overall Inspection:

SATISFACTORY**FIELD INSPECTION FORM**

Location Identifier	Facility ID	Loc ID	Inspector Name:	On-Site Inspection	2A Doc Num:
	432260	432260	CONKLIN, CURTIS	<input type="checkbox"/>	

Operator Information:OGCC Operator Number: 10150Name of Operator: BLACK HILLS PLATEAU PRODUCTION LLCAddress: 1515 WYNKOOP ST STE 500City: DENVER State: CO Zip: 80202

- ☐ THIS IS A FOLLOW UP INSPECTION
- ☐ FOLLOW UP INSPECTION REQUIRED
- ☐ NO FOLLOW UP INSPECTION REQUIRED
- ☐ INSPECTOR REQUESTS FORM 42 WHEN CORRECTIVE ACTIONS ARE COMPLETED

Contact Information:

Contact Name	Phone	Email	Comment
Lindholm, Stan	(970) 257-0727	stan.lindholm@blackhillscorp.com	
Kellerby, Shaun		shuan.kellerby@state.co.us	NW Supervisor
Lupton, Robert		robertlupton2002@yahoo.com	Company Man
Danahue, Jessica	(720) 210-1333	jessica.donahue@blackhillscorp.com	

Compliance Summary:QtrQtr: NENE Sec: 9 Twp: 8S Range: 98W**Inspector Comment:****Related Facilities:**

Facility ID	Type	Status	Status Date	Well Class	API Num	Facility Name	Insp Status	
432258	WELL	DG	05/30/2014	LO	045-21934	Homer Deep Unit 9-41BH	DG	<input checked="" type="checkbox"/>
432261	WELL	DG	06/24/2014	LO	045-21935	Homer Deep Unit 9-41AH	DG	<input checked="" type="checkbox"/>
432420	PIT		04/08/2013		-	Homer Deep Unit 9-41		<input checked="" type="checkbox"/>
438407	WELL	XX	08/01/2014		045-22488	Homer Deep Unit 9-41CH	XX	<input type="checkbox"/>

Equipment:**Location Inventory**

Special Purpose Pits: <u> </u>	Drilling Pits: <u> </u>	Wells: <u>3</u>	Production Pits: <u> </u>
Condensate Tanks: <u> </u>	Water Tanks: <u>6</u>	Separators: <u>3</u>	Electric Motors: <u> </u>
Gas or Diesel Motors: <u> </u>	Cavity Pumps: <u> </u>	LACT Unit: <u> </u>	Pump Jacks: <u> </u>
Electric Generators: <u> </u>	Gas Pipeline: <u>1</u>	Oil Pipeline: <u>1</u>	Water Pipeline: <u>1</u>
Gas Compressors: <u> </u>	VOC Combustor: <u> </u>	Oil Tanks: <u>3</u>	Dehydrator Units: <u> </u>
Multi-Well Pits: <u>1</u>	Pigging Station: <u> </u>	Flare: <u> </u>	Fuel Tanks: <u> </u>

Location

Lease Road:				
Type	Satisfactory/Action Required	comment	Corrective Action	Date
Access	SATISFACTORY			
Main	SATISFACTORY			

Emergency Contact Number (S/A/V): _____ Corrective Date: _____

Comment: _____

Corrective Action: _____

Good Housekeeping:				
Type	Satisfactory/Action Required	Comment	Corrective Action	CA Date
STORAGE OF SUPL	ACTION REQUIRED	Pallets of material uncovered. See attached photo	Cover material	09/12/2014

Spills:				
Type	Area	Volume	Corrective action	CA Date
<input type="checkbox"/> Multiple Spills and Releases?				

Venting:		
Yes/No	Comment	

Flaring:				
Type	Satisfactory/Action Required	Comment	Corrective Action	CA Date

Predrill

Location ID: 432260

Site Preparation:

Lease Road Adeq.: _____ Pads: _____ Soil Stockpile: _____

S/A/V: _____

Corrective Action: _____ Date: _____ CDP Num.: _____

Form 2A COAs:

Group	User	Comment	Date
OGLA	kubeczkod	<p>GROUNDWATER/SURFACE WATER BASELINE WATER SAMPLING COA:</p> <p>Baseline Water Testing: Prior to drilling, operator shall sample at a minimum two (2) domestic water wells or springs within a one (1) mile radius of the proposed oil and gas location. Testing preference shall be given to domestic water wells and springs over surface water. If possible, the water wells or springs selected should be on opposite sides of the oil and gas location not exceeding a one (1) mile radius. If water wells or springs on opposite sides of the oil and gas location cannot be identified, then the two (2) closest wells or springs within a one (1) mile radius of the oil and gas location shall be sampled. The sample location shall be surveyed in accordance with Rule 215. Sampling and analysis shall be conducted in conformance with an accepted industry standard as described in Rule 910.b.(2). Initial baseline testing shall include: pH, specific conductance, total dissolved solids (TDS), dissolved gases (methane, ethane, propane), alkalinity (total bicarbonate and carbonate as CaCO₃), major anions (bromide, chloride, fluoride, sulfate, nitrate and nitrite as N, phosphorus), major cations (calcium, iron, magnesium, manganese, potassium, sodium), other elements (barium, boron, selenium and strontium), presence of bacteria (iron related, sulfate reducing, slime and coliform), total petroleum hydrocarbons (TPH) and BTEX compounds (benzene, toluene, ethylbenzene and xylenes). Hydrogen sulfide shall also be measured using a field test method. Field observations such as pH, temperature, specific conductance, odor, water color, sediment, bubbles, and effervescence shall also be included. COGCC recommends that the latest version of EPA SW 846 analytical methods be used where possible and that analyses of samples be performed by laboratories that maintain state or national accreditation programs. If free gas or a dissolved methane concentration greater than 1.0 milligram per liter (mg/l) is detected in a water well, gas compositional analysis and stable isotope analysis of the methane (carbon and hydrogen – 12C, 13C, 1H and 2H) shall be performed to determine gas type. If test results indicated thermogenic or a mixture of thermogenic and biogenic gas. If the methane concentration increases by more than 5.0 mg/l between sampling periods, or increases to more than 10. mg/l, the operator shall notify the Director and the owner of the water well immediately. After 90 days, but less than 180 days of completion of the first proposed well a “post-completion” test shall be performed for the same analytical parameters listed above and repeated once within 60 to 72 months. If the well is a non-producing well, then the 60- to 72-month sample will not be required. Additional “post-completion” test(s) may be required if changes in water quality are identified during follow-up testing. The Director may require further water well sampling at any time in response to complaints from water well owners. Copies of all test results described above shall be provided to the Director and the landowner where the water quality testing well is located within three (3) months of collecting the samples used for the test. The analytical data and surveyed well locations shall also be submitted to the Director in an electronic data deliverable format. Documented refusal to grant access by well owner or surface owner (for spring sampling) shall not constitute a violation of this COA.</p>	03/19/2013

OGLA	kubeczko	<p>SITE SPECIFIC COAs:</p> <p>Notify the COGCC 48 hours prior to start of pad construction, rig mobilization, spud, pit liner installation, and start of hydraulic stimulation operations using Form 42 (the appropriate COGCC individuals will automatically be email notified, including the LGD for hydraulic stimulation operations).</p> <p>Operator must implement best management practices to contain any unintentional release of fluids, including any fluids conveyed via temporary surface or buried pipelines.</p> <p>Operator must ensure secondary containment for any volume of fluids contained at well site during drilling and completion operations (as described and shown on the Construction Layout Drawings attachment); including, but not limited to, construction of a berm or diversion dike, diversion/collection trenches within and/or outside of berms/dikes, site grading, or other comparable measures (i.e., best management practices (BMPs) associated with stormwater management) sufficiently protective of nearby surface water. Any berm constructed at the well pad location will be stabilized, inspected at regular intervals (at least every 14 days), and maintained in good condition.</p> <p>The moisture content of any freshwater generated cuttings in a cuttings pit, trench, or pile shall be as low as practicable to prevent accumulation of liquids greater than de minimis amounts. At the time of closure, if the drill cuttings are to be left onsite, they must also meet the applicable standards of Table 910-1.</p> <p>Flowback and stimulation fluids must be sent to tanks, separators, or other containment/filtering equipment before the fluids can be placed into any pipeline, storage vessel, or lined pit located on the well pad; or into tanker trucks for offsite disposal. The flowback and stimulation fluid tanks, separators, or other containment/filtering equipment must be placed on the well pad in an area with additional downgradient perimeter berming. The area where flowback fluids will be stored/reused must be constructed to be sufficiently impervious to contain any spilled or released material.</p> <p>Berms or other containment devices shall be constructed to be sufficiently impervious (preferably corrugated steel with poly liner) to contain any spilled or released material around crude oil, condensate, and produced water storage tanks.</p>	03/19/2013
OGLA	kubeczko	<p>FORM 15 EARTHEN PIT PERMIT COAs:</p> <p>Per Black Hills Plateau Production's De Beque Exploratory Proposal (which is currently being analyzed by BLM), "It is estimated that initially the flowback fluids (before evaporation) would contain about 3,500 ppm of total dissolved solids (TDS). The concentration of solids in the fluid would increase as water evaporated. The fluids pit would be double lined, with both liners a minimum of 24 mil thick, and they would be installed in accordance with Colorado Oil and Gas Conservation Commission (COGCC) regulations as well as the BLM GJFO Standard Conditions. The pit liner would be maintained in good working condition, with no tears or holes, until the pit was closed."; the multi-well pit must be double-lined.</p> <p>After installation of the uppermost liner and prior to operating the pit, the synthetic liner(s) shall be tested by filling the pit with at least 70 percent of operating capacity of water, measured from the base of the pit (not to exceed the 2-foot freeboard requirement). The operator shall monitor the pit for leaks for a period of 72 hours prior to either draining the pit or commencing operations. Operator shall notify the COGCC Oil and Gas Location Assessment (OGLA) Specialist for Western Colorado (Dave Kubeczko; email dave.kubeczko@state.co.us) 48 hours prior to start of the hydrotest. Hydrotest monitoring results must be maintained by the operator for the life of the pit and provided to COGCC prior to using the pit.</p> <p>In lieu of conducting an initial hydrostatic test of the pit, the operator can monitor fluid levels in the pit continuously using a minimum of two pressure transducers located at the upgradient and downgradient ends of the pit (based on the original topographic profile). These pressure transducers should be linked to the operator's</p>	03/19/2013

SCADA system such that they can be remotely monitored. In addition, the pit liner will be marked at the two foot freeboard depth line so that operations personnel (as well as COGCC inspectors) can easily verify that the required fluid free board is being maintained. The electronically collected water level measurement data shall be used to confirm changes in pit inflow and outflow during operations based on estimates from truck and/or pipeline delivery or removal activities. Any abnormalities that are noticed during operations will be reported to the operator's field supervisor immediately so that any necessary follow-up can be scheduled.

No portion of any pit that will be used to hold liquids shall be constructed on fill material, unless the pit and fill slope are designed and certified by a professional engineer, subject to review and approval by the director prior to construction of the pit. The construction and lining of the pit shall be supervised by a professional engineer or their agent. The entire base of the pit must be in cut.

For pits containing fluids other than freshwater only; the pit must be fenced. If the pit is not drained, or closure has not begun within 30 days after last use for well completion, the pit must be netted. The operator must maintain the fencing and netting until the pit is closed.

Surface water samples (one upgradient and one downgradient from the pit/well pad location) from Dry Fork (if water is present) shall be collected prior to pit use and every 12 months (until pit closure) to evaluate potential impacts from pit operations. At a minimum, the surface water samples will be analyze for the following parameters: major cations/anions (chloride, fluoride, sulfate, sodium); total dissolved solids (TDS); and BTEX/DRO.

The operator shall submit, and receive approval of, a reuse and recycling plan per Rule 907.a.(3), prior to any offsite reuse/recycling of pit fluids.

Pits used exclusively for drilling shall be closed in accordance with the 1000-Series Rules. Any pit(s) used for purposes other than drilling shall be closed in accordance with Rule 905. Closure of Pits, and Buried or Partially Buried Produced Water Vessels; with an approved Site Investigation and Remediation Workplan, Form 27.

Submit additional disposal facilities (wells, pits, etc.), if necessary (i.e., if original disposal option changes), for pit liquid contents to COGCC via a Form 4 Sundry prior to disposal.

At the time of pit closure, operator must submit disposal information for solids, if necessary, via a Form 4 Sundry Notice to the COGCC Location Specialist for Western Colorado (Dave Kubeczko; email dave.kubeczko@state.co.us). The disposal method will need to be approved prior to operator starting pit closure.

S/AV: _____ **Comment:** Pit is lined and fenced.

CA: _____ **Date:** _____

Wildlife BMPs:

BMP Type	Comment
Wildlife	Operator commits to following all mitigation outlined in the Black Hills Wildlife Mitigation Plan.

S/AV: _____ **Comment:** _____

CA: _____ **Date:** _____

Stormwater:

Comment: _____

Staking:

On Site Inspection (305):

Surface Owner Contact Information:

Name: _____ Address: _____

Inspector Name: CONKLIN, CURTIS

Phone Number: _____	Cell Phone: _____	
<u>Operator Rep. Contact Information:</u>		
Landman Name: _____	Phone Number: _____	
Date Onsite Request Received: _____	Date of Rule 306 Consultation: _____	
Request LGD Attendance: _____		
<u>LGD Contact Information:</u>		
Name: _____	Phone Number: _____	Agreed to Attend: _____
<u>Summary of Landowner Issues:</u>		
<u>Summary of Operator Response to Landowner Issues:</u>		
<u>Onsite Inspection Memorandum Summarizing Discussions at Inspection as Attachment:</u>		

Facility

Facility ID: 432258	Type: WELL	API Number: 045-21934	Status: DG	Insp. Status: DG
---------------------	------------	-----------------------	------------	------------------

Facility ID: 432261	Type: WELL	API Number: 045-21935	Status: DG	Insp. Status: DG
---------------------	------------	-----------------------	------------	------------------

Well Drilling

Rig: Rig Name: SST 66 Pusher/Rig Manager: Robert Lupton
Permit Posted: SATISFACTORY Access Sign: SATISFACTORY

Well Control Equipment:

Pipe Ram: YES Blind Ram: YES Hydril Type: YES
Pressure Test BOP: Pass Test Pressure PSI: 5000 Safety Plan: _____

Drill Fluids

Management:

Lined Pit: YES Unlined Pit: _____ Closed Loop: YES Semi-Closed Loop: _____
Multi-Well: YES Disposal Location: _____

Comment:

Rig was at 14000 ft depth on current hole

Facility ID: 432420	Type: PIT	API Number: -	Status: _____	Insp. Status: _____
---------------------	-----------	---------------	---------------	---------------------

Environmental

Spills/Releases:

Type of Spill: _____ Description: _____ Estimated Spill Volume: _____
Comment: _____
Corrective Action: _____ Date: _____
Reportable: _____ GPS: Lat _____ Long _____
Proximity to Surface Water: _____ Depth to Ground Water: _____

Water Well:

DWR Receipt Num: _____ Owner Name: _____ GPS : _____ Lat _____ Long _____

Field Parameters:

Inspector Name: CONKLIN, CURTIS

Sample Location: _____

Emission Control Burner (ECB): _____

Comment: _____

Pilot: _____ Wildlife Protection Devices (fired vessels): _____

Reclamation - Storm Water - Pit

Interim Reclamation:

Date Interim Reclamation Started: _____ Date Interim Reclamation Completed: _____

Land Use: RANGELAND

Comment: _____

1003a. Debris removed? _____ CM _____
CA _____ CA Date _____
Waste Material Onsite? _____ CM _____
CA _____ CA Date _____
Unused or unneeded equipment onsite? _____ CM _____
CA _____ CA Date _____
Pit, cellars, rat holes and other bores closed? _____ CM _____
CA _____ CA Date _____
Guy line anchors removed? _____ CM _____
CA _____ CA Date _____
Guy line anchors marked? _____ CM _____
CA _____ CA Date _____

1003b. Area no longer in use? _____ Production areas stabilized ? _____

1003c. Compacted areas have been cross ripped? _____

1003d. Drilling pit closed? _____ Subsidence over on drill pit? _____

Cuttings management: _____

1003e. Areas no longer needed for drilling or subsequent operations for have been re-vegetated to 80% of pre-existing? _____

Production areas have been stabilized? _____ Segregated soils have been replaced? _____

RESTORATION AND REVEGETATION

Cropland

Top soil replaced _____ Recontoured _____ Perennial forage re-established _____

Non-Cropland

Top soil replaced _____ Recontoured _____ 80% Revegetation _____

1003 f. Weeds Noxious weeds? _____

Comment: _____

Overall Interim Reclamation _____

Final Reclamation/ Abandoned Location:

Date Final Reclamation Started: _____ Date Final Reclamation Completed: _____

Final Land Use: RANGELAND

Inspector Name: CONKLIN, CURTIS

Reminder:

Comment:

Well plugged _____ Pit mouse/rat holes, cellars backfilled _____
Debris removed _____ No disturbance /Location never built _____
Access Roads _____ Regraded _____ Contoured _____ Culverts removed _____
Gravel removed _____
Location and associated production facilities reclaimed _____ Locations, facilities, roads, recontoured _____
Compaction alleviation _____ Dust and erosion control _____
Non cropland: Revegetated 80% _____ Cropland: perennial forage _____
Weeds present _____ Subsidence _____

Comment:

Corrective Action:

Date

Overall Final Reclamation _____

Well Release on Active Location ☐

Multi-Well Location ☐

Storm Water:

Loc Erosion BMPs	BMP Maintenance	Lease Road Erosion BMPs	Lease BMP Maintenance	Chemical BMPs	Chemical BMP Maintenance	Comment

S/A/V: _____ Corrective Date: _____

Comment:

CA:

Pits: ☐ NO SURFACE INDICATION OF PIT

Pit Type: Drilling Pit Lined: YES Pit ID: 432420 Lat: 39.379660 Long: -108.323210

Lining:

Liner Type: _____ Liner Condition: _____

Comment:

Fencing:

Fencing Type: Wildlife Fencing Condition: Adequate

Comment:

Netting:

Netting Type: Mesh Netting Condition: Good

Comment:

Anchor Trench Present: _____ Oil Accumulation: NO 2+ feet Freeboard: _____

Pit (S/A/V): SATISFACTOR

Comment:

Corrective Action:

Date:

Permit:	Facility ID	Permit Num	Expiration Date
	432420	400358504	
	432420	400358504	

Attached Documents

You can go to COGCC Images (<https://cogcc.state.co.us/weblink/>) and search by document number:

Inspector Name: CONKLIN, CURTIS

Document Num	Description	URL
675200492	Photo1	http://ogccweblink.state.co.us/DownloadDocumentPDF.aspx?DocumentId=3425152
675200493	Photo2	http://ogccweblink.state.co.us/DownloadDocumentPDF.aspx?DocumentId=3425153