

FORM 5A Rev 06/12

State of Colorado Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



Table with columns DE, ET, OE, ES

Document Number: 400679919

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 100322 2. Name of Operator: NOBLE ENERGY INC 3. Address: 1625 BROADWAY STE 2200 City: DENVER State: CO Zip: 80202 4. Contact Name: Kathleen Mills Phone: (720) 587-2226 Fax: (303) 228-4286 Email: kmills@nobleenergyinc.com

5. API Number 05-123-38322-00 6. County: WELD 7. Well Name: CHANDLER STATE 8. Location: QtrQtr: NENE Section: 15 Township: 3N Range: 64W Meridian: 6 9. Field Name: WATTENBERG Field Code: 90750

Completed Interval

FORMATION: NIOBRARA Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 06/20/2014 End Date: 06/22/2014 Date of First Production this formation: 07/12/2014 Perforations Top: 7308 Bottom: 11445 No. Holes: 0 Hole size:

Provide a brief summary of the formation treatment: Open Hole: [X] FRAC'D W/3596880 GALS SILVERSTIM AND SLICK WATER AND 4468522# OTTAWA SAND

This formation is commingled with another formation: [] Yes [X] No

Total fluid used in treatment (bbl): 85640 Max pressure during treatment (psi): 5877 Total gas used in treatment (mcf): Fluid density at initial fracture (lbs/gal): 8.43 Type of gas used in treatment: Min frac gradient (psi/ft): 0.92 Total acid used in treatment (bbl): Number of staged intervals: 23 Recycled water used in treatment (bbl): 4849 Flowback volume recovered (bbl): 6534 Fresh water used in treatment (bbl): 80791 Disposition method for flowback: RECYCLE Total proppant used (lbs): 4468522 Rule 805 green completion techniques were utilized: [X]

Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 07/30/2014 Hours: 24 Bbl oil: 430 Mcf Gas: 1060 Bbl H2O: 202 Calculated 24 hour rate: Bbl oil: 430 Mcf Gas: 1060 Bbl H2O: 202 GOR: 2465 Test Method: FLOWING Casing PSI: 1090 Tubing PSI: 1330 Choke Size: 18/64 Gas Disposition: SOLD Gas Type: WET Btu Gas: 1185 API Gravity Oil: 41 Tubing Size: 2 + 7/8 Tubing Setting Depth: 7050 Tbg setting date: 07/07/2014 Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: [] Yes [] No If yes, number of sacks cmt

** Bridge Plug Depth: ** Sacks cement on top: ** Wireline and Cement Job Summary must be attached.

Comment:

--

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Kathleen Mills

Title: Regulatory Analyst Date: _____ Email: kmills@nobleenergyinc.com
:

Attachment Check List

Att Doc Num **Name**

--	--

Total Attach: 0 Files

General Comments

User Group **Comment** **Comment Date**

--	--	--

Total: 0 comment(s)