



FIELD TICKET & TREATMENT REPORT CEMENT

LOCATION Oaklev KS

FOREMAN Dane P. 11.15

JOB TYPE <u>Surface</u>	HOLE SIZE <u>1 1/2</u>	HOLE DEPTH <u>530</u>	CASING SIZE & WEIGHT <u>9 5/8 26 LB/50'</u>
CASING DEPTH <u>537.55</u>	DRILL PIPE	TUBING	OTHER
SLURRY WEIGHT <u>14.8</u>	SLURRY VOL <u>31.1</u>	WATER gal/sk <u>6.5</u>	CEMENT LEFT in CASING <u>40</u>
DISPLACEMENT <u>37.68</u>	DISPLACEMENT PSI	MIX PSI	RATE

REMARKS: Safety meeting. Rig up. mix 125 sks class A 2% cc 29 gal. Display Putover. Plug

37.3/4 BAIS 2.6F water pump & lines Release pressure. Current will circulate.

which is to be performed

specific depths, pressures, or materials used for any service;

representative of the Customer shall be present to

equipment in the well, and the purchaser shall be present to

custody, and control of the well, the drilling and production

WARRANTIES - LIMITATION OF LIABILITY

minerals. THERE ARE NO OTHER WARRANTIES

that the same are free from defects in workmanship and

COWS warrants title to the products, supplies and materials, and

(c) CUYTS shall not be responsible for any claim, cause of action or demand (hereinafter referred to as "claim") for which CUYTS extends beyond those stated in the "MISFEASANTLY OR FITNESS FOR PURPOSE" section.

[illegible]

Bayin 3737

AUTHORIZATION *Acme & Co*

TITLE

DATE _____

I acknowledge that the payment terms, unless specifically amended in writing on the front of the form or in the customer's account records, at our office, and conditions of service on the back of this form are in effect for services identified on this form.