

FORM INSP
Rev 05/11

**State of Colorado
Oil and Gas Conservation Commission**

1120 Lincoln Street, Suite 801, Denver, Colorado 80203
Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Inspection Date:
08/20/2014

Document Number:
669500310

Overall Inspection:
SATISFACTORY

FIELD INSPECTION FORM

Location Identifier	Facility ID	Loc ID	Inspector Name:	On-Site Inspection	2A Doc Num:
	<u>438279</u>	<u>438277</u>	<u>ROY, CATHERINE</u>	<input type="checkbox"/>	

Operator Information:

OGCC Operator Number: 46685

Name of Operator: KINDER MORGAN CO2 CO LP

Address: 17801 HWY 491

City: CORTEZ State: CO Zip: 81321

- THIS IS A FOLLOW UP INSPECTION
- FOLLOW UP INSPECTION REQUIRED
- NO FOLLOW UP INSPECTION REQUIRED
- INSPECTOR REQUESTS FORM 42 WHEN CORRECTIVE ACTIONS ARE COMPLETED

Contact Information:

Contact Name	Phone	Email	Comment
Antipas, Andrew		andrew_antipas@kindermorgan.com	
Millican, Chris		chris_millican@kindermorgan.com	
Conway, Jamie		James_Conway@kindermorgan.com	All inspections
Kennedy, Phil	970-270-7512	phil_kennedy@kindermorgan.com	

Compliance Summary:

QtrQtr: tr68 Sec: 4 Twp: 40N Range: 18W

Inspector Comment:

This is a construction inspection. Construction of the well pad was nearly complete at the time of the inspection.

Related Facilities:

Facility ID	Type	Status	Status Date	Well Class	API Num	Facility Name	Insp Status
438279	WELL	XX	07/25/2014		033-06180	Doe Canyon 17	XX <input checked="" type="checkbox"/>

Equipment:

Location Inventory

Special Purpose Pits: _____	Drilling Pits: _____	Wells: <u>1</u>	Production Pits: _____
Condensate Tanks: _____	Water Tanks: _____	Separators: _____	Electric Motors: _____
Gas or Diesel Mortors: _____	Cavity Pumps: _____	LACT Unit: _____	Pump Jacks: _____
Electric Generators: _____	Gas Pipeline: _____	Oil Pipeline: _____	Water Pipeline: _____
Gas Compressors: _____	VOC Combustor: _____	Oil Tanks: _____	Dehydrator Units: _____
Multi-Well Pits: _____	Pigging Station: _____	Flare: _____	Fuel Tanks: _____

Location

Emergency Contact Number (S/A/V): _____ Corrective Date: _____

Comment: _____

Corrective Action: _____

Spills:				
Type	Area	Volume	Corrective action	CA Date
<input type="checkbox"/> Multiple Spills and Releases?				

Venting:	
Yes/No	Comment

Flaring:				
Type	Satisfactory/Action Required	Comment	Corrective Action	CA Date

Predrill

Location ID: 438279

Site Preparation:

Lease Road Adeq.: _____ Pads: _____ Soil Stockpile: _____

S/AV: _____

Corrective Action: _____ Date: _____ CDP Num.: _____

Form 2A COAs:

Group	User	Comment	Date
OGLA	kubeczkd	Operator shall pressure test pipelines in accordance with Rule 1101.e.(1) prior to putting into initial service any temporary surface or permanent buried pipelines and following any reconfiguration of the pipeline network.	05/20/2014
OGLA	kubeczkd	A closed loop system (which operator has indicated on the Form 2A) must be implemented during drilling. All cuttings generated during drilling with high chloride mud must be kept in containers or on a lined/bermed portion of the well pad; prior to analysis and/or offsite disposal. The moisture content of any drill cuttings in a cuttings area or pile shall be as low as practicable to prevent accumulation of liquids greater than de minimis amounts.	05/20/2014
OGLA	kubeczkd	Notify the COGCC 48 hours prior to start of pad construction, rig mobilization, spud, start of hydraulic stimulation operations (if applicable), start of flowback operations (if applicable), and pipeline testing using Form 42 (the appropriate COGCC individuals will automatically be email notified, including the LGD for hydraulic stimulation operations). All personnel must be H2S trained and proper air monitoring for H2S must be implemented during drilling, completion, and production operations. Emergency response plan for H2S must be onsite at all times.	05/20/2014

S/AV: _____ **Comment:** _____

CA: _____ **Date:** _____

Wildlife BMPs:

BMP Type	Comment
Drilling/Completion Operations	<p>Blowout preventer equipment (BOPE) complies with COGCC equipment regulations.</p> <p>Kinder Morgan conducts a BOPE test and files a 24 hour notice (Form 42) at the initial rig-up time, after each casing emplacement, and/or every 30 days.</p> <p>Adequate blowout prevention equipment is used on all well servicing operations.</p> <p>Backup stabbing valves are used on well servicing operations during reverse circulation and are pressure tested before each well servicing operation using both low-pressure air and high-pressure fluid.</p> <p>No pits are present at the well site.</p>
Planning	<p>Any material not in use that might constitute a fire hazard will be removed a minimum of 25 feet from the wellhead, tanks and separator.</p> <p>Any electrical installations inside the bermed area will comply with API RP 500 classifications and comply with the current national electrical code as adopted by the State of Colorado.</p>
Emissions mitigation	<p>Non-flammable CO₂ will be produced from the Leadville formation and thus green completion per rule 805 (3) does not apply.</p> <p>All CO₂ wells are equipped with a CO₂ leak detection monitor during drilling.</p>
Material Handling and Spill Prevention	<p>The use of a closed-loop drilling system will reduce the amount of waste produced and water used during drilling operations. Solid cuttings will be disposed of at a solid waste facility.</p> <p>Water that can no longer be reused or recycled will be disposed of in a Class I disposal well.</p> <p>Sufficiently impervious containment devices will be constructed around any condensate and produced water tanks. The containment devices will be sufficiently impervious to contain any spilled or released material. All containment devices will be inspected at regular intervals and maintained in good condition.</p> <p>Tanks are designed to meet all API 650 guidelines.</p>
Storm Water/Erosion Control	<p>Diversion ditches will be implemented to divert run-on and run-off around the well pad. Compacted earthen berms will also be utilized to control stormwater run-on and runoff.</p> <p>Tackifier will be added to the stored topsoil piles and all slopes to prevent erosion.</p> <p>Stockpiled soils will have slopes not greater than 3:1.</p> <p>Stormwater BMPs will be maintained/amended by Kinder Morgan as site conditions change throughout the construction and reclamation process.</p>
Noise mitigation	<p>During normal operations, the well will remain within COGCC regulations for noise. However, during the construction phase of the project, this standard may be exceeded occasionally.</p>
General Housekeeping	<p>Erosion control barriers, namely fiber wattles, will be placed at the edge of disturbance where necessary. Care will be taken to avoid disturbance outside of the project area unless it is deemed necessary for equipment stability and fire safety.</p> <p>During the construction, drilling, and completion phases, on-site trash dumpsters are emptied regularly by the local waste management company.</p> <p>The proposed well location will be drilled using a closed loop system and will therefore not use open pits.</p> <p>During drilling and completion operations, safety officers are present on location to ensure that livestock, wildlife, and unauthorized personnel do not enter the location.</p>
Traffic control	<p>All access roads are fully compliant with local county road standards. Access roads are composed of compacted gravel. In an effort to mitigate dust, magnesium-chloride applications to the road surface are performed per an agreement with Dolores County.</p>
Final Reclamation	<p>All disturbed areas that are not necessary for operational procedures will be restored to at least 80 percent of pre-disturbance vegetative cover.</p>

Construction	All equipment will be stored within the right-of-way (ROW) area of disturbance. Top soil will be removed to create a level pad for drilling and access road. Vegetation that does not need to be removed will be avoided during construction and removed vegetation will be cut near ground level, leaving the root system intact except where permanent facilities, roads, or ROWs, and wellpads require the complete removal of vegetation.
Dust control	In an effort to mitigate dust, magnesium-chloride applications to the road surface are performed per an agreement with Dolores County.
Interim Reclamation	Surface roughening, surface contouring, seeding, and weed control will be employed to facilitate vegetation reestablishment. Tackifier will be added to reclaimed areas.

S/AV: _____ **Comment:** _____

CA: _____ **Date:** _____

Stormwater:

Comment: _____

Staking:

On Site Inspection (305):

Surface Owner Contact Information:

Name: _____ Address: _____

Phone Number: _____ Cell Phone: _____

Operator Rep. Contact Information:

Landman Name: _____ Phone Number: _____

Date Onsite Request Received: _____ Date of Rule 306 Consultation: _____

Request LGD Attendance: _____

LGD Contact Information:

Name: _____ Phone Number: _____ Agreed to Attend: _____

Summary of Landowner Issues:

Summary of Operator Response to Landowner Issues:

Onsite Inspection Memorandum Summarizing Discussions at Inspection as Attachment:

Facility

Facility ID: 438279 Type: WELL API Number: 033-06180 Status: XX Insp. Status: XX

Environmental

Spills/Releases:

Type of Spill: _____ Description: _____ Estimated Spill Volume: _____

Comment: _____

Corrective Action: _____ Date: _____

Reportable: _____ GPS: Lat _____ Long _____

Proximity to Surface Water: _____ Depth to Ground Water: _____

Water Well:

DWR Receipt Num: _____ Owner Name: _____ GPS: _____ Lat _____ Long _____

Field Parameters: _____

Sample Location: _____

Emission Control Burner (ECB): _____

Comment: _____

Pilot: _____ Wildlife Protection Devices (fired vessels): _____

Reclamation - Storm Water - Pit

Interim Reclamation:

Date Interim Reclamation Started: _____ Date Interim Reclamation Completed: _____

Land Use: DRY LAND

Comment: _____

1003a. Debris removed? _____ CM _____

CA _____ CA Date _____

Waste Material Onsite? _____ CM _____

CA _____ CA Date _____

Unused or unneeded equipment onsite? _____ CM _____

CA _____ CA Date _____

Pit, cellars, rat holes and other bores closed? _____ CM _____

CA _____ CA Date _____

Guy line anchors removed? _____ CM _____

CA _____ CA Date _____

Guy line anchors marked? _____ CM _____

CA _____ CA Date _____

1003b. Area no longer in use? _____ Production areas stabilized ? _____

1003c. Compacted areas have been cross ripped? _____

1003d. Drilling pit closed? _____ Subsidence over on drill pit? _____

Cuttings management: _____

1003e. Areas no longer needed for drilling or subsequent operations for have been re-vegetated to 80% of pre-existing? _____

Production areas have been stabilized? _____ Segregated soils have been replaced? _____

RESTORATION AND REVEGETATION

Cropland

Top soil replaced _____ Recontoured _____ Perennial forage re-established _____

Non-Cropland

Top soil replaced _____ Recontoured _____ 80% Revegetation _____

1003 f. Weeds Noxious weeds? _____

Comment: _____

Overall Interim Reclamation _____

Final Reclamation/ Abandoned Location:

Date Final Reclamation Started: _____ Date Final Reclamation Completed: _____

Final Land Use: DRY LAND
 Reminder: _____

Comment: _____

Well plugged _____ Pit mouse/rat holes, cellars backfilled _____
 Debris removed _____ No disturbance /Location never built _____
 Access Roads Regraded _____ Contoured _____ Culverts removed _____
 Gravel removed _____
 Location and associated production facilities reclaimed _____ Locations, facilities, roads, recontoured _____
 Compaction alleviation _____ Dust and erosion control _____
 Non cropland: Revegetated 80% _____ Cropland: perennial forage _____
 Weeds present _____ Subsidence _____

Comment: _____

Corrective Action: _____ Date _____

Overall Final Reclamation _____ Well Release on Active Location Multi-Well Location

Storm Water:						
Loc Erosion BMPs	BMP Maintenance	Lease Road Erosion BMPs	Lease BMP Maintenance	Chemical BMPs	Chemical BMP Maintenance	Comment

S/A/V: SATISFACTOR _____ Corrective Date: _____
 Y _____

Comment: See inspectors comments below.

CA: _____

Pits: NO SURFACE INDICATION OF PIT

COGCC Comments

Comment	User	Date
The working area of the well pad was being stabilized and compacted during the inspection. There are two, approximately 10 inch drains on the eastern and western edges of the working area that drain a well pad diversion ditch. The outlet side of the drains is armored with cobble.	RoyC	08/21/2014
Straw wattles and wildlife fencing are present around the perimeter of the well pad. Straw wattles are also present on the signed topsoil stockpile. Sediment discharge from the project area and rill erosion was observed on the southeastern and southwestern corners of the well pad. During the inspection a truck arrived with additional straw wattles. A representative communicated that the straw wattles were going to be installed in the problem areas identified in this inspection		
The cut and fill slopes and topsoil stockpile slopes are exposed and not protected. A trailer was observed on the location with bagged hydromulch. A representative on the location expressed that he thought the hydromulch would be installed later that day or later this week.		
The culvert at the entrance to the well pad is crushed and needs to be repaired.		
See attached photos for additional detail.		

Attached Documents

Inspector Name: ROY, CATHERINE

You can go to COGCC Images (<https://cogcc.state.co.us/weblink/>) and search by document number:

Document Num	Description	URL
669500311	Inspection Photos 2014.08.20	http://ogccweblink.state.co.us/DownloadDocumentPDF.aspx?DocumentId=3445410